

NAME

`t1dotlessj` – create a dotless-j PostScript Type 1 font

SYNOPSIS

`t1dotlessj` [OPTIONS...] *font* [*outputfile*]

DESCRIPTION

`T1dotlessj` creates a PostScript Type 1 font whose only character is a dotless 'j' matching the input font's design. It works simply by removing the dot from the input font's 'j'. The output font has three characters: '.notdef', 'space', and 'uni0237', where 'uni0237' is the dotless 'j'. The command fails if the input font already has a dotless 'j' character, or if there seems to be no dot to remove. `T1dotlessj` writes the created PFA or PFB font to the standard output (but see the `--output` option); if no input file is supplied, it reads a PFA or PFB font from the standard input.

OPTIONS

`--output=`*file*, `-o` *file*

Send output to *file* instead of standard output.

`--pfb`, `-b`

Output a PFB font. This is the default.

`--pfa`, `-a`

Output a PFA font.

`--name=`*name*, `-n` *name*

Set the output font's PostScript name to *name*. The default is *InputFontNameLCDFJ*.

`-q`, `--quiet`

Do not generate any error messages.

`-h`, `--help`

Print usage information and exit.

`-v`, `--version`

Print the version number and some short non-warranty information and exit.

RETURN VALUES

`T1dotlessj` exits with one of the following values:

- 0 A dotless-j font was successfully generated.
- 1 The font already contained a dotless-j character.
- 2 The font's "j" character had no dot to remove.
- 3 The font had no "j" character.
- >3 An error occurred.

SEE ALSO

Adobe Type 1 Font Format

AUTHOR

Eddie Kohler (ekohler@gmail.com)