

The `fvextra` package

Geoffrey M. Poore
gpoore@gmail.com
github.com/gpoore/fvextra

v1.14.0 from 2026/02/25

Abstract

`fvextra` provides several extensions to `fancyvrb`, including automatic line breaking and improved math mode. `\Verb` is reimplemented so that it works (with a few limitations) inside other commands, even in movable arguments and PDF bookmarks. The new command `\EscVerb` is similar to `\Verb` except that it works everywhere without limitations by allowing the backslash to serve as an escape character. `fvextra` also patches some `fancyvrb` internals.

Contents

1	Introduction	5
2	Usage	5
2.1	Pandoc compatibility	5
3	General options	6
4	General commands	13
4.1	Inline-only settings with <code>\fvinline</code>	13
4.2	Custom formatting for inline commands like <code>\Verb</code> with <code>\FancyVerbFormatInline</code>	13
4.3	Custom formatting for environments like <code>Verbatim</code> with <code>\FancyVerbFormatLine</code> and <code>\FancyVerbFormatText</code>	13
5	Reimplemented commands	14
5.1	<code>\Verb</code>	14
5.2	<code>\SaveVerb</code>	15
5.3	<code>\UseVerb</code>	16
6	New commands and environments	16
6.1	<code>\EscVerb</code>	16
6.2	<code>VerbEnv</code>	17
6.3	<code>VerbatimWrite</code>	17
6.4	Buffers	18
6.4.1	<code>VerbatimBuffer</code>	18
6.4.2	<code>\VerbatimInsertBuffer</code>	21
6.4.3	<code>\VerbatimClearBuffer</code>	22
6.4.4	<code>\InsertBuffer</code>	22
6.4.5	<code>\ClearBuffer</code>	23
6.4.6	<code>\BufferMdfivesum</code>	23
6.4.7	<code>\IterateBuffer</code>	23
6.4.8	<code>\WriteBuffer</code>	23
7	Line breaking	23
7.1	Line breaking options	23
7.2	Line breaking and tab expansion	30
7.3	Advanced line breaking	31
7.3.1	A few notes on algorithms	31
7.3.2	Breaks within macro arguments	31
7.3.3	Customizing break behavior	33
8	Pygments support	33
8.1	Options for users	33
8.2	For package authors	34

9 Patches	34
9.1 Visible spaces	34
9.2 <code>obeytabs</code> with visible tabs and with tabs inside macro arguments	34
9.3 Math mode	35
9.3.1 Spaces	35
9.3.2 Symbols and fonts	36
9.4 Orphaned labels	36
9.5 <code>rulecolor</code> and <code>fillcolor</code>	36
9.6 Command lookahead tokenization	36
10 Additional modifications to <code>fancyvrb</code>	37
10.1 Backtick and single quotation mark	37
10.2 Line numbering	37
11 Undocumented features of <code>fancyvrb</code>	37
11.1 Undocumented option	37
11.2 Undocumented macros	37
12 Implementation	38
12.1 Required packages	38
12.2 Utility macros	38
12.2.1 <code>fancyvrb</code> space and tab tokens	38
12.2.2 ASCII processing	39
12.2.3 Sentinels	46
12.2.4 Active character definitions	46
12.3 pdfTeX with <code>inputenc</code> using UTF-8	47
12.4 Reading and processing command arguments	50
12.4.1 Tokenization and lookahead	50
12.4.2 Reading arguments	51
12.4.3 Reading and protecting arguments in expansion-only contexts	55
12.4.4 Converting detokenized tokens into PDF strings	58
12.4.5 Detokenizing verbatim arguments	59
12.4.6 Retokenizing detokenized arguments	77
12.5 Hooks	78
12.6 Escaped characters	79
12.7 Inline-only options	79
12.8 Reimplementations	80
12.8.1 <code>extra</code> option	80
12.8.2 <code>\FancyVerbFormatInline</code>	80
12.8.3 <code>\Verb</code>	80
12.8.4 <code>\SaveVerb</code>	82
12.8.5 <code>\UseVerb</code>	83
12.9 New commands and environments	84
12.9.1 <code>\EscVerb</code>	84
12.9.2 <code>VerbEnv</code>	85
12.9.3 <code>VerbatimWrite</code>	87
12.9.4 <code>VerbatimBuffer</code>	88
12.9.5 <code>\VerbatimInsertBuffer</code>	91
12.9.6 <code>\VerbatimClearBuffer</code>	93
12.9.7 <code>\InsertBuffer</code>	93

12.9.8	<code>\ClearBuffer</code>	94
12.9.9	<code>\BufferMdfivesum</code>	94
12.9.10	<code>\IterateBuffer</code> , <code>\IterateBufferBreak</code>	95
12.10	Patches	96
12.10.1	Delimiting characters for verbatim commands	96
12.10.2	<code>\CustomVerbatimCommand</code> compatibility with <code>\FVExtraRobustCommand</code>	97
12.10.3	Visible spaces	98
12.10.4	<code>obeytabs</code> with visible tabs and with tabs inside macro arguments	98
12.10.5	Fonts and symbols in math mode	102
12.10.6	Ophaned label	104
12.10.7	<code>rulecolor</code> and <code>fillcolor</code>	104
12.11	Extensions	105
12.11.1	New options requiring minimal implementation	105
12.11.2	Formatting with <code>\FancyVerbFormatLine</code> , <code>\FancyVerbFormatText</code> , and <code>\FancyVerbHighlightLine</code>	108
12.11.3	Line numbering	109
12.11.4	Background color	113
12.11.5	Line highlighting or emphasis	117
12.12	Line breaking	120
12.12.1	Options and associated macros	120
12.12.2	Line breaking implementation	130
12.13	Pygments compatibility	148

1 Introduction

The `fancyvrb` package had its first public release in January 1998. In July of the same year, a few additional features were added. Since then, the package has remained almost unchanged except for a few bug fixes. `fancyvrb` has become one of the primary \LaTeX packages for working with verbatim text.

Additional verbatim features would be nice, but since `fancyvrb` has remained almost unchanged for so long, a major upgrade could be problematic. There are likely many existing documents that tweak or patch `fancyvrb` internals in a way that relies on the existing implementation. At the same time, creating a completely new verbatim package would require a major time investment and duplicate much of `fancyvrb` that remains perfectly functional. Perhaps someday there will be an amazing new verbatim package. Until then, we have `fvextra`.

`fvextra` is an add-on package that gives `fancyvrb` several additional features, including automatic line breaking. Because `fvextra` patches and overwrites some of the `fancyvrb` internals, it may not be suitable for documents that rely on the details of the original `fancyvrb` implementation. `fvextra` tries to maintain the default `fancyvrb` behavior in most cases. All reimplementations (section 5), patches (section 9), and modifications to `fancyvrb` defaults (section 10) are documented. In most cases, there are options to switch back to original implementations or original default behavior.

Some features of `fvextra` were originally created as part of the `pythontex` and `minted` packages. `fancyvrb`-related patches and extensions that currently exist in those packages will gradually be migrated into `fvextra`.

2 Usage

`fvextra` may be used as a drop-in replacement for `fancyvrb`. It will load `fancyvrb` if it has not yet been loaded, and then proceeds to patch `fancyvrb` and define additional features.

The `upquote` package is loaded to give correct backticks (```) and typewriter single quotation marks (`'`). When this is not desirable within a given environment, use the option `curlyquotes`. `fvextra` modifies the behavior of these and other symbols in typeset math within verbatim, so that they will behave as expected (section 9.3). `fvextra` uses the `lineno` package for working with automatic line breaks. `lineno` gives a warning when the `csquotes` package is loaded before it, so `fvextra` should be loaded before `csquotes`. The `etoolbox` package is required. `color` or `xcolor` should be loaded manually to use color-dependent features.

While `fvextra` attempts to minimize changes to the `fancyvrb` internals, in some cases it completely overwrites `fancyvrb` macros with new definitions. New definitions typically follow the original definitions as much as possible, but code that depends on the details of the original `fancyvrb` implementation may be incompatible with `fvextra`.

2.1 Pandoc compatibility

`fvextra` supports line breaking in `Pandoc` \LaTeX output that includes highlighted source code. Enabling basic line breaking at spaces is as simple as adding

`\usepackage{fvextra}` and `\fvset{breaklines}` to the Pandoc Markdown `header-includes`.

By default, more advanced line breaking features such as `breakanywhere`, `breakbefore`, and `breakafter` will not work with Pandoc highlighted output, due to the presence of the syntax highlighting macros. This can be fixed by using `breaknonspaceingroup`, which enables all line breaking features within macros. For example, the following YAML metadata in a Markdown document would redefine the Pandoc `Highlighting` environment to enable line breaking anywhere.

```
---
header-includes:
- |
  ```{=latex}
 \usepackage{fvextra}
 \DefineVerbatimEnvironment{Highlighting}{Verbatim}{
 commandchars=\\\{\},
 breaklines, breaknonspaceingroup, breakanywhere}
  ```
---
```

3 General options

`fvextra` adds several general options to `fancyvrb`. All options related to automatic line breaking are described separately in section 7. All options related to syntax highlighting using Pygments are described in section 8.

`backgroundcolor` (string) (default: none)
Background color behind commands and environments. This is only a basic, lightweight implementation of background colors using `\colorbox`. For more control of background colors, consider `tcolorbox` or a similar package, or a custom background color implementation.

Background colors are implemented with `\colorbox`, which prevents line breaking for `\Verb`, `\UseVerb`, and `\EscVerb`. Background colors are only compatible with `fvextra`'s reimplemented `\Verb` and `\UseVerb` (`extra=true`).

When there is a background color in environments such as `Verbatim` that typeset blocks of text, some PDF readers and browsers can introduce rendering artifacts. These appear in between lines of text as extremely thin horizontal rules that are the color of the page behind the background. They tend to be more noticeable for dark background colors on a light page. `fvextra` attempts to prevent rendering artifacts by slightly oversizing the `\colorbox` behind each line and then slightly overlapping these boxes. This overlap can be fine-tuned if necessary with `backgroundcolorboxoverlap`. If rendering artifacts are an issue with your software in spite of a small overlap, consider `tcolorbox` or a similar package, or a custom background color implementation.

See `backgroundcolorvphantom` to customize the height of the background for each line of text, especially for `\Verb`, `\EscVerb`, and `BVerbatim`.

When `backgroundcolor` is used with `Verbatim` with a `frame`, it may be necessary to adjust `framesep` and `fillcolor` depending on the desired result. `backgroundcolorpadding` provides a shortcut for this.

`backgroundcolorboxoverlap` (length) (default: 0.25pt)

The amount by which `\colorboxes` that are used to provide `backgroundcolor` are oversized and then overlapped, to prevent rendering artifacts.

When there is a background color in environments such as `Verbatim` that typeset blocks of text, some PDF readers and browsers can introduce rendering artifacts. These appear in between lines of text as extremely thin horizontal rules that are the color of the page behind the background. They tend to be more noticeable for dark background colors on a light page. `fvextra` attempts to prevent rendering artifacts by slightly oversizing the `\colorbox` behind each line by `backgroundcolorboxoverlap`, and then slightly overlapping these boxes by the same amount.

Chrome and Adobe Acrobat Reader generally work correctly even with no overlap (`backgroundcolorboxoverlap=0pt`). Many PDF previews in \TeX editing software and PDF readers need an overlap in the 0.1pt to 0.15pt range. Whether Firefox needs overlap, and if so the amount needed, seems to depend on resolution and possibly operating system. Safari and macOS Preview may show artifacts, particularly when zoomed out, even with overlaps of 0.25pt or greater.

`backgroundcolorpadding` (length) (default: none)

Padding when `backgroundcolor` is set. For `\Verb`, `\UseVerb`, `\EscVerb`, and `BVerbatim`, this sets `\fboxsep` for the `\colorbox` that is used to create the background color. For `Verbatim`, `fancyvrb`'s frame options are used instead, particularly `framesep` and `fillcolor`.

For `Verbatim`, this amounts to a shortcut for a combination of frame-related settings that provide padding when there is a background color. This is only intended for cases with `frame=none` or `frame=single`. In other cases, it may be better to modify the `fancyvrb` frame settings directly, and it may be necessary to modify the `fancyvrb` internals to obtain padding on all sides.

For `Verbatim`, if `frame=single`, then this is equivalent to the following settings:

- `framesep=\backgroundcolorpadding`
- `fillcolor=\FancyVerbBackgroundColor`

For `Verbatim`, if `frame` has any value other than `single`, then this is equivalent to the following settings:

- `frame=single`
- `framerule=0pt`
- `rulecolor=\FancyVerbBackgroundColor`
- `framesep=\backgroundcolorpadding`
- `fillcolor=\FancyVerbBackgroundColor`

`backgroundcolorvphantom` (macro) (default: `\vphantom{"Apgjy}`)

`\vphantom` or similar macro such as `\strut` that is inserted at the beginning of each line of text using `backgroundcolor`. This allows the height of the background for each line of text to be customized, especially for `\Verb`, `\EscVerb`, and `BVerbatim`. `backgroundcolorvphantom` will typically have no effect on `Verbatim`-based environments unless it is set to a size larger than `\strut`.

`bgcolor` (string) (default: none)

Alias for `backgroundcolor`.

`bgcolorboxoverlap` (length) (default: 0.25pt)
Alias for `backgroundcolorboxoverlap`.

`bgcolorpadding` (length) (default: none)
Alias for `backgroundcolorpadding`.

`bgcolorvphantom` (macro) (default: `\vphantom{"Apgjy}`)
Alias for `backgroundcolorvphantom`.

`beameroverlays` (boolean) (default: false)
Give the `<` and `>` characters their normal text meanings, so that `beamer` overlays of the form `\only<1>{...}` will work. Note that something like `commandchars=\\\{\}` is required separately to enable macros. This is not incorporated in the `beameroverlays` option because essentially arbitrary command characters could be used; only the `<` and `>` characters are hard-coded for overlays.

With some font encodings and language settings, `beameroverlays` prevents literal (non-overlay) `<` and `>` characters from appearing correctly, so they must be inserted using commands.

`curlyquotes` (boolean) (default: false)
Unlike `fancyvrb`, `fvextra` requires the `upquote` package, so the backtick (```) and typewriter single quotation mark (`'`) always appear literally by default, instead of becoming the left and right curly single quotation marks (`'``'`). This option allows these characters to be replaced by the curly quotation marks when that is desirable.

| | |
|--|----------------------------|
| <code>\begin{Verbatim}</code>
<code>`quoted text'</code>
<code>\end{Verbatim}</code> | <code>`quoted text'</code> |
|--|----------------------------|

| | |
|---|----------------------------|
| <code>\begin{Verbatim}[curlyquotes]</code>
<code>`quoted text'</code>
<code>\end{Verbatim}</code> | <code>'quoted text'</code> |
|---|----------------------------|

`extra` (boolean) (default: true)
Use `fvextra` reimplementations of `fancyvrb` commands and environments when available. For example, use `fvextra`'s reimplemented `\Verb` that works (with a few limitations) inside other commands, rather than the original `fancyvrb` implementation that essentially functions as `\texttt` inside other commands.

`fontencoding` (string) (default: `<document font encoding>`)
Set the font encoding inside `fancyvrb` commands and environments. Setting `fontencoding=none` resets to the default document font encoding.

`highlightcolor` (string) (default: `LightCyan`)
Set the color used for `highlightlines`, using a predefined color name from `color` or `xcolor`, or a color defined via `\definecolor`.

`highlightlines` (string) (default: `<none>`)

This highlights a single line or a range of lines based on line numbers. The line numbers refer to the line numbers that `fancyvrb` would show if `numbers=left`, etc. They do not refer to original or actual line numbers before adjustment by `firstnumber`.

The highlighting color can be customized with `highlightcolor`.

```

\begin{Verbatim}[numbers=left, highlightlines={1, 3-4}]
First line
Second line
Third line
Fourth line
Fifth line
\end{Verbatim}

```

```

1 First line
2 Second line
3 Third line
4 Fourth line
5 Fifth line

```

The actual highlighting is performed by a set of commands. These may be customized for additional fine-tuning of highlighting. See the default definition of `\FancyVerbHighlightLineFirst` as a starting point.

- `\FancyVerbHighlightLineFirst`: First line in a range.
- `\FancyVerbHighlightLineMiddle`: Inner lines in a range.
- `\FancyVerbHighlightLineLast`: Last line in a range.
- `\FancyVerbHighlightLineSingle`: Single highlighted lines.
- `\FancyVerbHighlightLineNormal`: Normal lines without highlighting.

If these are customized in such a way that indentation or inter-line spacing is changed, then `\FancyVerbHighlightLineNormal` may be modified as well to make all lines uniform. When working with the `First`, `Last`, and `Single` commands, keep in mind that `fvextra` merges all numbers ranges, so that `{1, 2-3, 3-5}` is treated the same as `{1-5}`.

Highlighting is applied after `\FancyVerbFormatText`, so any text formatting defined via that command will work with highlighting. Highlighting is applied before `\FancyVerbFormatLine`, so if `\FancyVerbFormatLine` puts a line in a box, the box will be behind whatever is created by highlighting. This prevents highlighting from vanishing due to user-defined customization.

`linenos` (boolean) (default: `false`)
`fancyvrb` allows line numbers via the options `numbers=<position>`. This is essentially an alias for `numbers=left`. It primarily exists for better compatibility with the `minted` package.

`mathescape` (boolean) (default: `false`)
This causes everything between dollar signs `$...$` to be typeset as math. The ampersand `&`, caret `^`, and underscore `_` have their normal math meanings.

This is equivalent to

codes={\catcode`\\$=3\catcode`\&=4\catcode`\^=7\catcode`_ =8}

`mathscape` is always applied *before* `codes`, so that `codes` can be used to override some of these definitions.

Note that `fvextra` provides several patches that make math mode within `verbatim` as close to normal math mode as possible (section 9.3).

`numberfirstline` (boolean) (default: `false`)

When line numbering is used with `stepnumber` $\neq 1$, the first line may not always be numbered, depending on the line number of the first line. This causes the first line always to be numbered.

| |
|---|
| <pre>\begin{Verbatim}[numbers=left, stepnumber=2, numberfirstline] First line Second line Third line Fourth line \end{Verbatim}</pre> |
| <pre>1 First line 2 Second line Third line 4 Fourth line</pre> |

`numbers` (none | left | right | both) (default: `none`)

`fvextra` adds the `both` option for line numbering.

| | |
|--|---|
| <pre>\begin{Verbatim}[numbers=both] First line Second line Third line Fourth line \end{Verbatim}</pre> | <pre>1 First line 1 2 Second line 2 3 Third line 3 4 Fourth line 4</pre> |
|--|---|

`retokenize` (boolean) (default: `false`)

By default, `\UseVerb` inserts saved verbatim material with the catcodes (`commandchars`, `codes`, etc.) under which it was originally saved with `\SaveVerb`. When `retokenize` is used, the saved verbatim material is retokenized under the settings in place at `\UseVerb`.

This only applies to the reimplemented `\UseVerb`, when paired with the reimplemented `\SaveVerb`. It may be extended to environments (`\UseVerbatim`, etc.) in the future, if the relevant commands and environments are reimplemented.

`space` (macro) (default: `_`)

Redefine the visible space character. Note that this is only used if `showspaces=true`. The color of the character may be set with `spacecolor`.

`spacebreak` (macro) (default: `\discretionary{}{}{}`)

This determines the break that is inserted around spaces when `breaklines=true` and one or more of the following conditions applies: `breakcollapsespaces=false`, `showspaces=true`, or the space is affected by `breakbefore` or `breakafter`. If it is redefined, it should typically be similar to `\FancyVerbBreakAnywhereBreak`, `\FancyVerbBreakBeforeBreak`, and `\FancyVerbBreakAfterBreak` to obtain consistent breaks.

`spacecolor` (string) (default: none)
Set the color of visible spaces. By default (none), they take the color of their surroundings.

```
\color{gray}
\begin{Verbatim}[showspaces, spacecolor=red]
One two three
\end{Verbatim}
```

One two three

`stepnumberfromfirst` (boolean) (default: false)
By default, when line numbering is used with `stepnumber ≠ 1`, only line numbers that are a multiple of `stepnumber` are included. This offsets the line numbering from the first line, so that the first line, and all lines separated from it by a multiple of `stepnumber`, are numbered.

```
\begin{Verbatim}[numbers=left, stepnumber=2,
                 stepnumberfromfirst]
First line
Second line
Third line
Fourth line
\end{Verbatim}
```

1 First line
Second line
3 Third line
Fourth line

`stepnumberoffsetvalues` (boolean) (default: false)
By default, when line numbering is used with `stepnumber ≠ 1`, only line numbers that are a multiple of `stepnumber` are included. Using `firstnumber` to offset the numbering will change which lines are numbered and which line gets which number, but will not change which *numbers* appear. This option causes `firstnumber` to be ignored in determining which line numbers are a multiple of `stepnumber`. `firstnumber` is still used in calculating the actual numbers that appear. As a result, the line numbers that appear will be a multiple of `stepnumber`, plus `firstnumber` minus 1.

This option gives the original behavior of `fancyvrb` when `firstnumber` is used with `stepnumber` $\neq 1$ (section 10.2).

```

\begin{Verbatim}[numbers=left, stepnumber=2,
                  firstnumber=4, stepnumberoffsetvalues]

First line
Second line
Third line
Fourth line
\end{Verbatim}

```

```

First line
5 Second line
Third line
7 Fourth line

```

`tab` (macro) (default: `fancyvrb`'s `\FancyVerbTab`, \rightarrow)
Redefine the visible tab character. Note that this is only used if `showtabs=true`. The color of the character may be set with `tabcolor`.

When redefining the tab, you should include the font family, font shape, and text color in the definition. Otherwise these may be inherited from the surrounding text. This is particularly important when using the `tab` with syntax highlighting, such as with the `minted` or `pythontex` packages.

`fvextra` patches `fancyvrb` tab expansion so that variable-width symbols such as `\rightarrowfill` may be used as tabs. For example,

```

\begin{Verbatim}[obeytabs, showtabs, breaklines,
                  tab=\rightarrowfill, tabcolor=orange]
\rightarrowfill First \rightarrowfill Second \rightarrowfill Third \rightarrowfill And more text that goes on for a
\rightarrowfill \rightarrowfill while until wrapping is needed
\rightarrowfill First \rightarrowfill Second \rightarrowfill Third \rightarrowfill Forth
\end{Verbatim}

```

```

\rightarrowfill First \rightarrowfill Second \rightarrowfill Third \rightarrowfill And more text that goes on for a
\rightarrowfill \rightarrowfill while until wrapping is needed
\rightarrowfill First \rightarrowfill Second \rightarrowfill Third \rightarrowfill Forth

```

`tabcolor` (string) (default: `none`)
Set the color of visible tabs. By default (`none`), they take the color of their surroundings.

`vargsingleline` (boolean) (default: `false`)
This determines whether `fvextra`'s `\Verb` and `\SaveVerb` take multi-line (but not multi-paragraph) verbatim arguments, or if they instead require arguments to be on a single line like the original `fancyvrb` commands.

4 General commands

4.1 Inline-only settings with `\fvlineset`

`\fvlineset{options}`

This is like `\fvset`, except that options only apply to commands that typeset inline verbatim, like `\Verb` and `\EscVerb`. Settings from `\fvlineset` override those from `\fvset`.

Note that `\fvlineset` only works with commands that are reimplemented, patched, or defined by `fvextra`; it is not compatible with the original `fancyvrb` definitions.

4.2 Custom formatting for inline commands like `\Verb` with `\FancyVerbFormatInline`

`\FancyVerbFormatInline`

This can be used to apply custom formatting to inline verbatim text created with commands like `\Verb`. It only works with commands that are reimplemented, patched, or defined by `fvextra`; it is not compatible with the original `fancyvrb` definitions. The default definition does nothing; it is equivalent to `\newcommand{\FancyVerbFormatInline}[1]{#1}`.

This is the inline equivalent of `\FancyVerbFormatLine` and `\FancyVerbFormatText`. In the inline context, there is no need to distinguish between entire line formatting and only text formatting, so only `\FancyVerbFormatInline` exists.

4.3 Custom formatting for environments like `Verbatim` with `\FancyVerbFormatLine` and `\FancyVerbFormatText`

`\FancyVerbFormatLine`

`\FancyVerbFormatText`

`fancyvrb` defines `\FancyVerbFormatLine`, which can be used to apply custom formatting to each individual line of text in environments like `Verbatim`. By default, it takes a line as an argument and inserts it with no modification. This is equivalent to `\newcommand{\FancyVerbFormatLine}[1]{#1}`.¹

`fvextra` introduces line breaking, which complicates line formatting. We might want to apply formatting to the entire line, including line breaks, line continuation symbols, and all indentation, including any extra indentation provided by line breaking. Or we might want to apply formatting only to the actual text of the line. `fvextra` leaves `\FancyVerbFormatLine` as applying to the entire line, and introduces a new command `\FancyVerbFormatText` that only applies to the text part of the line.² By default, `\FancyVerbFormatText` inserts the text unmodified. When it is customized, it should not use boxes that do not allow line breaks to avoid conflicts with line breaking code.

¹The actual definition in `fancyvrb` is `\def\FancyVerbFormatLine#1{\FV@ObeyTabs{#1}}`. This is problematic because redefining the macro could easily eliminate `\FV@ObeyTabs`, which governs tab expansion. `fvextra` redefines the macro to `\def\FancyVerbFormatLine#1{#1}` and patches all parts of `fancyvrb` that use `\FancyVerbFormatLine` so that `\FV@ObeyTabs` is explicitly inserted at the appropriate points.

²When `breaklines=true`, each line is wrapped in a `\parbox`. `\FancyVerbFormatLine` is outside the `\parbox`, and `\FancyVerbFormatText` is inside.

```

\renewcommand{\FancyVerbFormatLine}[1]{%
  \fcolorbox{DarkBlue}{LightGray}{#1}}
\renewcommand{\FancyVerbFormatText}[1]{\textcolor{Green}{#1}}

\begin{Verbatim}[breaklines]
Some text that proceeds for a while and finally wraps onto another line
Some more text
\end{Verbatim}

```

```

Some text that proceeds for a while and finally wraps onto
↪ another line

Some more text

```

5 Reimplemented commands

`fvextra` reimplements parts of `fancyvrb`. These new implementations stay close to the original definitions while allowing for new features that otherwise would not be possible. Reimplemented versions are used by default. The original implementations may be used via `\fvset{extra=false}` or by using `extra=false` in the optional arguments to a command or environment.

Reimplemented commands restrict the scope of catcode-related options compared to the original `fancyvrb` versions. This prevents catcode-related options from interfering with new features such as `\FancyVerbFormatInline`. With `fvextra`, the `codes` option should only be used for catcode modifications. Including non-catcode commands in `codes` will typically have no effect, unlike with `fancyvrb`. If you want to customize verbatim content using general commands, consider `formatcom`.

5.1 `\Verb`

```
\Verb*[(options)](delim char or {)(text)(delim char or }
```

The new `\Verb` works as expected (with a few limitations) inside other commands. It even works in movable arguments (for example, in `\section`), and is compatible with `hyperref` for generating PDF strings (for example, PDF bookmarks). The `fancyvrb` definition did work inside some other commands, but essentially functioned as `\texttt` in that context.

By default, `\Verb` takes a multi-line (but not multi-paragraph) verbatim argument. To restore the `fancyvrb` behavior of requiring a single-line argument, set `vargsingleline=true`.

`\Verb` is compatible with `breaklines` and the relevant line-breaking options.

Like the original `fancyvrb` implementation, the new `\Verb` can be starred (`\Verb*`) and accepts optional arguments. While `fancyvrb`'s starred command `\Verb*` is a shortcut for `showspaces`, `fvextra`'s `\Verb*` is a shortcut for both `showspaces` and `showtabs`. This is more similar to the current behavior of L^AT_EX's `\verb*`, except that `\verb*` converts tabs into visible spaces instead of displaying them as visible tabs.

Delimiters A repeated character like normal `\verb`, or a pair of curly braces `{...}`. If curly braces are used, then `<text>` cannot contain unpaired curly braces. Note that curly braces should be preferred when using `\Verb` inside other commands, and curly braces are *required* when `\Verb` is in a movable argument, such as in a `\section`. Non-ASCII characters now work as delimiters under pdfTeX with inputenc using UTF-8.³ For example, `\Verb$verbs` now works as expected.

Limitations inside other commands While the new `\Verb` does work inside arbitrary other commands, there are a few limitations.

- `#` and `%` cannot be used. If you need them, consider `\EscVerb` or perhaps `\SaveVerb` plus `\UseVerb`.
- Curly braces are only allowed in pairs.
- Multiple adjacent spaces will be collapsed into a single space.
- Be careful with backslashes. A backslash that is followed by one or more ASCII letters will cause a following space to be lost, if the space is not immediately followed by an ASCII letter. For example, `\Verb{\r \n}` becomes `\r\n`, but `\Verb{\r n}` becomes `\r n`. Basically, anything that looks like a L^AT_EX command (control word) will gobble following spaces, unless the next character after the spaces is an ASCII letter.
- A single `^` is fine, but avoid `^^` because it will serve as an escape sequence for an ASCII command character.

Using in movable arguments `\Verb` works automatically in movable arguments, such as in a `\section`. `\protect` or similar measures are not needed for `\Verb` itself, or for any of its arguments, and should not be used. `\Verb` performs operations that amount to applying `\protect` to all of these automatically.

hyperref PDF strings `\Verb` is compatible with `hyperref` for generating PDF strings such as PDF bookmarks. Note that the PDF strings are *always* a literal rendering of the verbatim text, with all `fancyvrb` options ignored. For example, things like `showspaces` and `commandchars` have no effect. If you need options to be applied to obtain desired PDF strings, consider a custom approach, perhaps using `\texorpdfstring`.

Line breaking `breaklines` allows breaks at spaces. `breakbefore`, `breakafter`, and `breakanywhere` function as expected, as do things like `breakaftersymbolpre` and `breakaftersymbolpost`. Break options that are only applicable to block text like a `Verbatim` environment do not have any effect. For example, `breakindent` and `breaksymbol` do nothing.

5.2 `\SaveVerb`

```
\SaveVerb[options]{name}{delim char or { }<text>{delim char or } }
```

`\SaveVerb` is reimplemented so that it is equivalent to the reimplemented `\Verb`. Like the new `\Verb`, it accepts `<text>` delimited by a pair of curly braces

³Under pdfTeX, non-ASCII code points are processed at the byte rather than code point level, so `\Verb` must treat a sequence of multiple bytes as the delimiter.

{...}. It supports `\fvlineset`. It also adds support for the new `retokenize` option for `\UseVerb`.

By default, `\SaveVerb` takes a multi-line (but not multi-paragraph) verbatim argument. To restore the `fancyvrb` behavior of requiring a single-line argument, set `vargsingleline=true`.

5.3 `\UseVerb`

`\UseVerb*[{options}]{<name>}`

`\UseVerb` is reimplemented so that it is equivalent to the reimplemented `\Verb`. It supports `\fvlineset` and `breaklines`.

Like `\Verb`, `\UseVerb` is compatible with `hyperref` for generating PDF strings such as PDF bookmarks. Note that the PDF strings are *always* a literal rendering of the verbatim text, with all `fancyvrb` options ignored. For example, things like `showspaces` and `commandchars` have no effect. The new option `retokenize` also has no effect. If you need options to be applied to obtain desired PDF strings, consider a custom approach, perhaps using `\texorpdfstring`

There is a new option `retokenize` for `\UseVerb`. By default, `\UseVerb` inserts saved verbatim material with the catcodes (`commandchars`, `codes`, etc.) under which it was originally saved with `\SaveVerb`. When `retokenize` is used, the saved verbatim material is retokenized under the settings in place at `\UseVerb`.

For example, consider `\SaveVerb{save}{\textcolor{red}{\#%}}`:

- `\UseVerb{save} ⇒ \textcolor{red}{\#%}`
- `\UseVerb[commandchars=\\\{\}]{save} ⇒ \textcolor{red}{\#%}`
- `\UseVerb[retokenize, commandchars=\\\{\}]{save} ⇒ \#%`

6 New commands and environments

6.1 `\EscVerb`

`\EscVerb*[{options}]{<backslash-escaped text>}`

This is like `\Verb` but with backslash escapes to allow for characters such as `#` and `%`. For example, `\EscVerb{\Verb{\#%}}` gives `\Verb{\#%}`. It behaves exactly the same regardless of whether it is used inside another command. Like the reimplemented `\Verb`, it works in movable arguments (for example, in `\section`), and is compatible with `hyperref` for generating PDF strings (for example, PDF bookmarks).

Delimiters Text must *always* be delimited with a pair of curly braces `{...}`.

This ensures that `\EscVerb` is always used in the same manner regardless of whether it is inside another command.

Escaping rules

- Only printable, non-alphanumeric ASCII characters (symbols, punctuation) can be escaped with backslashes.⁴
- Always escape these characters: `\`, `%`, `#`.

⁴Allowing backslash escapes of letters would lead to ambiguity regarding spaces; see `\Verb`.

- Escape spaces when there are more than one in a row.
- Escape `~` if there are more than one in a row.
- Escape unpaired curly braces.
- Additional symbols or punctuation characters may require escaping if they are made `\active`, depending on their definitions.

Using in movable arguments `\EscVerb` works automatically in movable arguments, such as in a `\section`. `\protect` or similar measures are not needed for `\EscVerb` itself, or for any of its arguments, and should not be used. `\EscVerb` performs operations that amount to applying `\protect` to all of these automatically.

hyperref PDF strings `\EscVerb` is compatible with `hyperref` for generating PDF strings such as PDF bookmarks. Note that the PDF strings are *always* a literal rendering of the verbatim text after backslash escapes have been applied, with all `fancyvrb` options ignored. For example, things like `showspaces` and `commandchars` have no effect. If you need options to be applied to obtain desired PDF strings, consider a custom approach, perhaps using `\texorpdfstring`.

6.2 VerbatimWrite

```
\begin{VerbatimWrite}[\langle options \rangle]
  \langle single line \rangle
\end{VerbatimWrite}
```

This is an environment variant of `\Verb`. The environment must contain only a single line of text, and the closing `\end{VerbatimWrite}` must be on a line by itself. The `\langle options \rangle` and `\langle single line \rangle` are read and then passed on to `\Verb` internally for actual typesetting.

While `VerbatimWrite` can be used by document authors, it is primarily intended for package creators. For example, it is used in `minted` to implement `\mintinline`. In that case, highlighted code is always generated within a `Verbatim` environment. It is possible to process this as inline rather than block verbatim by `\letting \Verbatim` to `\VerbatimWrite`.

| | |
|---|--------------------------------|
| <pre>BEFORE\begin{VerbatimWrite} _inline_ \end{VerbatimWrite} AFTER</pre> | <pre>BEFORE_inline_AFTER</pre> |
|---|--------------------------------|

`VerbatimWrite` is not implemented using the typical `fancyvrb` environment implementation style, so it is not compatible with `\RecustomVerbatimEnvironment`.

6.3 VerbatimOut

```
\begin{VerbatimOut}[\langle opt \rangle]
  \langle lines \rangle
\end{VerbatimOut}
```

This writes environment contents verbatim to an external file. It is similar to `fancyvrb`'s `VerbatimOut`, except that (1) it allows writing to a file multiple times (multiple environments can write to the same file) and (2) by default it uses `\detokenize` to guarantee truly verbatim output.

By default, all `fancyvrb` options except for `VerbatimWrite`-specific options are ignored. This can be customized on a per-environment basis via environment optional arguments.

Options defined specifically for `VerbatimWrite`:

`writefilehandle` (file handle) (default: *none*)
File handle for writing. For example,

```
\newwrite\myfile
\immediate\openout\myfile=myfile.txt\relax

\begin{VerbatimWrite}[writefilehandle=\myfile]
...
\end{VerbatimWrite}

\immediate\closeout\myfile
```

`writer` (macro) (default: `\FancyVerbDefaultWriter`)
This is the macro that processes each line of text in the environment and then writes it to file. This is the default implementation:

```
\def\FancyVerbDefaultWriter#1{%
  \immediate\write\FancyVerbWriteFileHandle{\detokenize{#1}}
```

6.4 Buffers

6.4.1 VerbatimBuffer

```
\begin{VerbatimBuffer}[(opt)]
  <lines>
\end{VerbatimBuffer}
```

This environment stores its contents verbatim in a “buffer,” a sequence of numbered macros each of which contains one line of the environment. The “buffered” lines can then be iterated over for further processing or later use. This is similar to `fancyvrb`’s `SaveVerbatim`, which saves an environment for later use. `VerbatimBuffer` offers additional flexibility by capturing truly verbatim environment contents using `\detokenize` and saving environment contents in a format designed for further processing.

By default, all `fancyvrb` options except for `VerbatimBuffer`-specific options are ignored. This can be customized on a per-environment basis via environment optional arguments.

Below is an extended example that demonstrates what is possible with `VerbatimBuffer` combined with various buffer commands. This uses `\ifstrequal` from the `etoolbox` package.

- `\setformatter` defines an empty `\formatter` macro. Then it defines a `\lineprocessor` macro that takes a buffer line as an argument. If this line contains only the text “red”, then `\lineprocessor` redefines `\formatter` to `\color{red}` and invokes `\IterateBufferBreak` to stop iteration over the buffer. Finally, `\IterateBuffer` is used to apply `\lineprocessor` to each line in the buffer, until the final line is reached or `\IterateBufferBreak` is invoked.

- `afterbuffer` involves two steps: (1) `\setformatter` loops through the buffer and defines `\formatter` based on the buffer contents, and (2) `\VerbatimInsertBuffer` typesets the buffer, using `formatcom=\formatter` to format the text based on whether any line contains only the text “red”.

```

\def\setformatter{%
  \def\formatter{}%
  \def\lineprocessor##1{%
    \ifstrequal{##1}{red}{\def\formatter{\color{red}}\IterateBufferBreak}{}}%
  \IterateBuffer{\lineprocessor}}

\begin{VerbatimBuffer}[
  afterbuffer={\setformatter\VerbatimInsertBuffer[formatcom=\formatter]}
]
first
second
red
\end{VerbatimBuffer}

```

```

first
second
red

```

Here is the same example, but rewritten to use a global buffer with custom buffer name instead.

```

\begin{VerbatimBuffer}[globalbuffer, buffername=exbuff]
first
second
red
\end{VerbatimBuffer}

\def\formatter{}
\def\lineprocessor#1{%
  \ifstrequal{#1}{red}{\def\formatter{\color{red}}\IterateBufferBreak}{}}
\IterateBuffer[buffername=exbuff]{\lineprocessor}

\VerbatimInsertBuffer[buffername=exbuff, formatcom=\formatter]

```

```

first
second
red

```

Options defined specifically for `VerbatimBuffer`:

`afterbuffer` (macro) (default: *none*)
 Macro or macros invoked at the end of the environment, after all lines of the environment have been buffered. This is outside the `\begingroup... \endgroup` that wraps verbatim processing, so `fancyvrb` settings are no longer active. However, the buffer line macros and the buffer length macro are still accessible even when `globalbuffer=false`.

When `afterbuffer` is used to typeset the buffer, the typeset buffer may contain `VerbatimBuffer` or environments based on it. Typically, nested buffering should be avoided for a given buffer; a different buffer should be used at each level of nesting. Otherwise, for nested `VerbatimBuffer` environments, the buffer will contain the contents of the outermost `VerbatimBuffer` environment concatenated with the contents of nested environments.

The current buffer depth is available in `\FancyVerbBufferDepth`. This has a value of 0 outside of any `VerbatimBuffer` environments, a value of 1 within the outermost `VerbatimBuffer` environment, and so forth. This can be used to automatically generate a unique `buffername` at a given nesting depth.

`bufferer` (macro) (default: `\FancyVerbDefaultBufferer`)
 This is the macro that adds lines to the buffer. The default is designed to create a truly verbatim buffer via `\detokenize`. This can be customized if you wish to use `fancyvrb` options related to catcodes to create a buffer that is only partially verbatim (that contains macros).

```
\def\FancyVerbDefaultBufferer#1{%
  \expandafter\xdef\csname\FancyVerbBufferLineName\FancyVerbBufferIndex\endcsname{%
    \detokenize{#1}}
```

A custom `bufferer` must take a single argument `#1` (a line of the environment text) and ultimately store the processed line in a macro called

```
\csname\FancyVerbBufferLineName\FancyVerbBufferIndex\endcsname
```

This macro must be defined globally, so `\xdef` or `\gdef` is necessary (this does not interfere with scoping from `globalbuffer`). Otherwise, there are no restrictions. The `\xdef` and `\detokenize` in the default definition guarantee that the buffer consists only of the literal text from the environment, but this is not required for a custom `bufferer`.

`bufferlengthname` (string) (default: `FancyVerbBufferLength`)
 Name of the macro storing the length of the buffer. This is the number of lines stored.

Macros that operate within a `VerbatimBuffer` environment can access the current value of `bufferlengthname` via `\FancyVerbBufferLengthName`.

`bufferlinename` (string) (default: `FancyVerbBufferLine`)
 The base name of the buffer line macros. The default is `FancyVerbBufferLine`, which will result in buffer macros `\FancyVerbBufferLine<n>` with integer `n` greater than or equal to one and less than or equal to the number of lines (one-based indexing). Since buffer macro names contain a number, they must be accessed differently than typical macros:

```
\csname FancyVerbBufferLine<n>\endcsname
\@nameuse{FancyVerbBufferLine<n>}
```

If the buffer macros are looped over with a counter that is incremented, then `<n>` should be the counter value `\arabic{<counter>}`.

Macros that operate within a `VerbatimBuffer` environment can access the current value of `bufferlinename` via `\FancyVerbBufferLineName`.

`buffername` (string) (default: `<none>`)
Shortcut for setting `bufferlengthname` and `bufferlinename` simultaneously, using the same root name. This sets `bufferlengthname` to `<buffername>length` and `bufferlinename` to `<buffername>line`.

`globalbuffer` (bool) (default: `false`)
This determines whether buffer line macros are defined globally, that is, whether they are accessible after the end of the `VerbatimBuffer` environment. If the line macros are defined globally, then the buffer length macro is also increased appropriately outside the environment. `globalbuffer` does not affect any `afterbuffer` macro, since that is invoked inside the environment.

When buffered lines are used immediately, consider using `afterbuffer` instead of `globalbuffer`. When buffered lines must be used later in a document, consider using `globalbuffer` with custom (and perhaps unique) `bufferlinename` and `bufferlengthname`.

When `globalbuffer=true`, `VerbatimBuffer` environments with the same buffer name will append to a single buffer, so that it ultimately contains the concatenated contents of all environments. A `VerbatimBuffer` environment with `globalbuffer=false` will append to the buffer created by any previous `VerbatimBuffer` that had `globalbuffer=true` and shared the same buffer name. Any `afterbuffer` macro will have access to a buffer containing the concatenated data. At the very end of the environment with `globalbuffer=false`, after any `afterbuffer`, this appended content will be removed. All buffer line macros (from `bufferlinename`) that were created by that environment are “deleted” (`\let` to an undefined macro), and the buffer length macro (from `bufferlengthname`) is reduced proportionally.

6.4.2 `\VerbatimInsertBuffer`

`\VerbatimInsertBuffer[<options>]`

This inserts an existing buffer created by `VerbatimBuffer` as a verbatim environment. The `Verbatim` environment is used by default, but this can be customized by setting `insertenvname`. `\VerbatimInsertBuffer` modifies `Verbatim` and `BVerbatim` internals to function with a buffer in a command context. See the `VerbatimBuffer` documentation for an example of usage.

Options related to catcodes cause the buffer to be retokenized during typesetting. That is, the `fancyvrb` options used for `\VerbatimInsertBuffer` are not restricted by those that were in effect when `VerbatimBuffer` originally created the buffer, so long as the buffer contains a complete representation of the original `VerbatimBuffer` environment contents.

`\VerbatimInsertBuffer` is not implemented using the typical `fancyvrb` command and environment implementation styles, so it is not compatible with `\RecustomVerbatimCommand` or `\RecustomVerbatimEnvironment`.

Options defined specifically for `\VerbatimInsertBuffer`:

`insertenvname` (string) (default: `Verbatim`)
 This is the name of the verbatim environment used for inserting the buffer. `insertenvname` can be any `Verbatim`- or `BVerbatim`-based environment. Environments defined with `\CustomVerbatimEnvironment` and `\RecustomVerbatimEnvironment` are supported. User-implemented environments that serve as wrappers around `Verbatim` or `BVerbatim` should typically be compatible so long as they accept `fancyvrb/fvextra` optional arguments in the same way as `Verbatim` and `BVerbatim`.

6.4.3 `\VerbatimClearBuffer`

`\VerbatimClearBuffer` [*options*]

Clear an existing buffer created with `VerbatimBuffer`. `\global\let` all buffer line macros to an undefined macro and set the buffer length macro to zero.

6.4.4 `\InsertBuffer`

`\InsertBuffer` [*options*]

This inserts an existing buffer created with `VerbatimBuffer` so that it is interpreted as \LaTeX . The result is essentially the same as if the buffered text had been included literally at the insertion point. The buffer is processed with `\scantokens`.

For typesetting verbatim text, `\InsertBuffer` with the `wrapperenv` option set to a verbatim environment can be used as an alternative to `\VerbatimInsertBuffer`. Both typically have similar performance.

`wrapperenvname` (string) (default: *none*)
 Name of environment used to wrap the buffer. This is inserted within the `\scantokens` that is used to process the buffer, so if `wrapperenvname` is set to a verbatim environment, then it will cause the buffer to be typeset verbatim. This is useful for non-`fancyvrb` verbatim environments that are not supported by `\VerbatimInsertBuffer`.

`wrapperenvopt` (string) (default: *none*)
 Optional argument [*opt*] passed to wrapper environment `wrapperenvname`.

`wrapperenvarg` (string) (default: *none*)
 Mandatory argument `{arg}` passed to wrapper environment `wrapperenvname`.

```

\begin{VerbatimBuffer}[buffername=ins, globalbuffer]
Text. Math  $f(x)$ . Verb \Verb|~#\{|.
\begin{Verbatim}
Verbatim. ~#\{|.
\end{Verbatim}
More text.
\end{VerbatimBuffer}

\textbf{BEFORE}\InsertBuffer[buffername=ins]\textbf{AFTER}
-----
BEFOREText. Math  $f(x)$ . Verb ~#\{|.

Verbatim. ~#\{|.

More text.AFTER

```

6.4.5 `\ClearBuffer`

`\ClearBuffer`[*options*] Alias for `\VerbatimClearBuffer`.

6.4.6 `\BufferMdfivesum`

`\BufferMdfivesum` Calculate the MD5 sum of the current buffer.

`\BufferMdfivesum` operates on the current buffer. Because it is fully expandable, it cannot take an optional argument to switch buffers. To switch buffers, use something like `\fvset{buffername=...}` before `\BufferMdfivesum`.

```
\begin{VerbatimBuffer}[afterbuffer=\xdef\bufferhash{\BufferMdfivesum}]
Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do
 eiusmod tempor incididunt ut labore et dolore magna aliqua.
\end{VerbatimBuffer}
```

```
\texttt{\bufferhash}
```

```
8B5FB4E4F759EB41199344C22AE311B70
```

6.4.7 `\IterateBuffer`

`\IterateBuffer`[*options*]{*macro*}

Iterate over buffer from beginning to end, invoking *macro* on each line. *macro* must be a macro or sequence of macros that consumes a single brace-delimited argument, which is the current line in the buffer. `\IterateBufferBreak` is available to break iteration immediately after the current *macro* invocation completes. During iteration, `\FancyVerbBufferLengthName`, `\FancyVerbBufferLineName`, and `\FancyVerbBufferIndex` can be used to access the name of the current buffer and index within it.

6.4.8 `\WriteBuffer`

`\WriteBuffer`[*options*] This writes the current buffer to an external file, using the `writefilehandle` and `writer` options from `VerbatimWrite`. It is the buffer equivalent of `VerbatimWrite`.

7 Line breaking

Automatic line breaking may be turned on with `breaklines=true`. By default, breaks only occur at spaces. Breaks may be allowed anywhere with `breakanywhere`, or only before or after specified characters with `breakbefore` and `breakafter`. Many options are provided for customizing breaks. A good place to start is the description of `breaklines`.

When a line is broken, the result must fit on a single page. There is no support for breaking a line across multiple pages.

7.1 Line breaking options

Options are provided for customizing typical line breaking features. See section 7.3 for details about low-level customization of break behavior.

`breakafter` (string) (default: *none*)

Break lines after specified characters, not just at spaces, when `breaklines=true`. For example, `breakafter=-/` would allow breaks after any hyphens or slashes. Special characters given to `breakafter` should be backslash-escaped (usually `#`, `{`, `}`, `%`, `[`, `]`, and the comma `,`; the backslash `\` may be obtained via `\\` and the space via `\space`).⁵

For an alternative, see `breakbefore`. When `breakbefore` and `breakafter` are used for the same character, `breakbeforeinrun` and `breakafterinrun` must both have the same setting.

Note that when `commandchars` or `codes` are used to include macros within verbatim content, breaks will not occur within mandatory macro arguments by default. Depending on settings, macros that take optional arguments may not work unless the entire macro including arguments is wrapped in a group (curly braces `{}`, or other characters specified with `commandchars`). See section 7.3 for details, and consider `breaknonspaceingroup` as a solution in simple cases.

```
\begin{Verbatim}[breaklines, breakafter=d]
some_string = 'SomeTextThatGoesOnAndOnForSoLongThatItCouldNeverFitOnOneLine'
\end{Verbatim}

-----

some_string = 'SomeTextThatGoesOnAndOnForSoLongThatItCould
↪ NeverFitOnOneLine'
```

`breakafterinrun` (boolean) (default: `false`)

When `breakafter` is used, insert breaks within runs of identical characters. If `false`, treat sequences of identical characters as a unit that cannot contain breaks. When `breakbefore` and `breakafter` are used for the same character, `breakbeforeinrun` and `breakafterinrun` must both have the same setting.

`breakaftersymbolpre` (string) (default: `\,\footnotesize\ensuremath{_}\rfloor`, `_`)

The symbol inserted pre-break for breaks inserted by `breakafter`. This does not apply to breaks inserted next to spaces; see `spacebreak`.

`breakaftersymbolpost` (string) (default: *none*)

The symbol inserted post-break for breaks inserted by `breakafter`. This does not apply to breaks inserted next to spaces; see `spacebreak`.

`breakanywhere` (boolean) (default: `false`)

Break lines anywhere, not just at spaces, when `breaklines=true`.

Note that when `commandchars` or `codes` are used to include macros within verbatim content, breaks will not occur within mandatory macro arguments by default. Depending on settings, macros that take optional arguments may not work unless the entire macro including arguments is wrapped in a group (curly

⁵`breakafter` expands each token it is given once, so when it is given a macro like `\%`, the macro should expand to a literal character that will appear in the text to be typeset. `fextra` defines special character escapes that are activated for `breakafter` so that this will work with common escapes. The only exception to token expansion is non-ASCII characters under pdfTeX; these should appear literally. `breakafter` is not catcode-sensitive.

braces `{}`, or other characters specified with `commandchars`). See section 7.3 for details, and consider `breaknonspaceingroup` as a solution in simple cases.

```
\begin{Verbatim}[breaklines, breakanywhere]
some_string = 'SomeTextThatGoesOnAndOnForSoLongThatItCouldNeverFitOnOneLine'
\end{Verbatim}

-----

some_string = 'SomeTextThatGoesOnAndOnForSoLongThatItCouldNeve
↪ rFitOnOneLine'
```

`breakanywheresymbolpre` (string) (default: `\,\footnotesize\ensuremath{_}\rfloor`, `_]`)
The symbol inserted pre-break for breaks inserted by `breakanywhere`. This does not apply to breaks inserted next to spaces; see `spacebreak`.

`breakanywhereinlinestretch` (length) (default: `(none)`)
Stretch glue to insert at potential `breakanywhere` break locations in inline contexts, to give better line widths and avoid overfull `\hbox`. This allows the spacing between adjacent non-space characters to stretch, so it should not be used when column alignment is important. For typical line lengths, values between `0.01em` and `0.02em` should be sufficient to provide a cumulative stretch per line that is equal to or greater than the width of one character.

This is typically not needed in cases where an overfull `\hbox` only overflows by tiny amount, perhaps a fraction of a pt. In those cases, the overfull `\hbox` could be ignored, `\hfuzz` could be set to `1pt` or `2pt` to suppress tiny overfull `\hbox` warnings, or `breakanywheresymbolpre` might be redefined to adjust spacing.

Implementation: Before each `breakanywhere` break location, this inserts the following sequence of macros:

```
\nobreak\hspace{0pt plus \FV@breaknonspaceinlinestretch}
```

`breakanywheresymbolpost` (string) (default: `(none)`)
The symbol inserted post-break for breaks inserted by `breakanywhere`. This does not apply to breaks inserted next to spaces; see `spacebreak`.

`breakautoindent` (boolean) (default: `true`)
When a line is broken, automatically indent the continuation lines to the indentation level of the first line. When `breakautoindent` and `breakindent` are used together, the indentations add. This indentation is combined with `breaksymbolindentleft` to give the total actual left indentation.

`breakbefore` (string) (default: `(none)`)
Break lines before specified characters, not just at spaces, when `breaklines=true`. For example, `breakbefore=A` would allow breaks before capital A's. Special characters given to `breakbefore` should be backslash-escaped (usually `#`, `{`, `}`, `%`, `[`, `]`, and the comma `,`; the backslash `\` may be obtained via `\\` and the space via `\space`).⁶

⁶`breakbefore` expands each token it is given once, so when it is given a macro like `\%`, the macro should expand to a literal character that will appear in the text to be typeset. `fvextra`

For an alternative, see `breakafter`. When `breakbefore` and `breakafter` are used for the same character, `breakbeforeinrun` and `breakafterinrun` must both have the same setting.

Note that when `commandchars` or `codes` are used to include macros within verbatim content, breaks will not occur within mandatory macro arguments by default. Depending on settings, macros that take optional arguments may not work unless the entire macro including arguments is wrapped in a group (curly braces `{}`), or other characters specified with `commandchars`). See section 7.3 for details, and consider `breaknonspaceingroup` as a solution in simple cases.

```
\begin{Verbatim}[breaklines, breakbefore=A]
some_string = 'SomeTextThatGoesOnAndOnForSoLongThatItCouldNeverFitOnOneLine'
\end{Verbatim}

-----

some_string = 'SomeTextThatGoesOn
→ AndOnForSoLongThatItCouldNeverFitOnOneLine'
```

`breakbeforeinrun` (boolean) (default: `false`)
 When `breakbefore` is used, insert breaks within runs of identical characters. If `false`, treat sequences of identical characters as a unit that cannot contain breaks. When `breakbefore` and `breakafter` are used for the same character, `breakbeforeinrun` and `breakafterinrun` must both have the same setting.

`breakbeforesymbolpre` (string) (default: `\,\footnotesize\ensuremath{_}\rfloor`, `_`)
 The symbol inserted pre-break for breaks inserted by `breakbefore`. This does not apply to breaks inserted next to spaces; see `spacebreak`.

`breakbeforesymbolpost` (string) (default: `none`)
 The symbol inserted post-break for breaks inserted by `breakbefore`. This does not apply to breaks inserted next to spaces; see `spacebreak`.

`breakcollapsespaces` (bool) (default: `true`)
 When `true` (default), a line break within a run of regular spaces (`showspaces=false`) replaces all spaces with a single break, and the wrapped line after the break starts with a non-space character. When `false`, a line break within a run of regular spaces preserves all spaces, and the wrapped line after the break may start with one or more spaces. This causes regular spaces to behave exactly like the visible spaces produced with `showspaces`; both give identical line breaks, with the only difference being the appearance of spaces.

`breakindent` (dimension) (default: `breakindentnchars`)
 When a line is broken, indent the continuation lines by this amount. When `breakautoindent` and `breakindent` are used together, the indentations add. This indentation is combined with `breaksymbolindentleft` to give the total actual left indentation.

defines special character escapes that are activated for `breakbefore` so that this will work with common escapes. The only exception to token expansion is non-ASCII characters under pdfTeX; these should appear literally. `breakbefore` is not catcode-sensitive.

`breakindentnchars` (integer) (default: 0)
This allows `breakindent` to be specified as an integer number of characters rather than as a dimension (assumes a fixed-width font).

`breaklines` (boolean) (default: `false`)
Automatically break long lines.

Limitations for verbatim environments/block text, such as `Verbatim`: When a line is broken, the result must fit on a single page. There is no support for breaking a line across multiple pages.⁷

Limitations for verbatim commands/inline text, such as `\Verb`: When a line break is inserted, the text may still overflow into the margin or cause an overfull `\hbox`, depending on hyphenation settings and various penalties related to line breaks. It may be possible to avoid this by allowing additional break locations with `breakbefore`, `breakafter`, or `breakanywhere`. Small overfull `\hbox` warnings can be suppressed by setting `\hfuzz` to a larger value, for example setting it to `2pt` instead of the default `0.1pt`. It is also possible to combine `breakanywhere` with `breakanywhereinlinestretch` to allow flexible spacing between adjacent non-space characters. In cases where it is better to break before the margin rather than overflowing into the margin, consider setting `\emergencystretch`.

By default, automatic breaks occur at spaces (even when `showspaces=true`). Use `breakanywhere` to enable breaking anywhere; use `breakbefore` and `breakafter` for more fine-tuned breaking.

| | |
|--|--|
| <pre>...text. \begin{Verbatim}[breaklines] def f(x): return 'Some text ' + str(x) \end{Verbatim}</pre> | <pre>...text. def f(x): return 'Some text ' + ↪ str(x)</pre> |
|--|--|

To customize the indentation of broken lines, see `breakindent` and `breakautoindent`. To customize the line continuation symbols, use `breaksymbolleft` and `breaksymbolright`. To customize the separation between the continuation symbols and the text, use `breaksymbolsepleft` and `breaksymbolsepright`. To customize the extra indentation that is supplied to make room for the break symbols, use `breaksymbolindentleft` and `breaksymbolindentright`. Since only the left-hand symbol is used by default, it may also be modified using the alias options `breaksymbol`, `breaksymbolsep`, and `breaksymbolindent`.

An example using these options to customize the `Verbatim` environment is shown below. This uses the `\carriagereturn` symbol from the `dingbat` package.

⁷Following the implementation in `fancyvrb`, each line is typeset within an `\hbox`, so page breaks are not possible.

```

\begin{Verbatim}[breaklines,
                 breakautoindent=false,
                 breaksymbolleft=\raisebox{0.8ex}{
                   \small\reflectbox{\carriagereturn}},
                 breaksymbolindentleft=0pt,
                 breaksymbolsepleft=0pt,
                 breaksymbolright=\small\carriagereturn,
                 breaksymbolindentright=0pt,
                 breaksymbolsepright=0pt]

def f(x):
    return 'Some text ' + str(x) + ' some more text ' +
        → str(x) + ' even more text that goes on for a while'
\end{Verbatim}

```

```

def f(x):
    return 'Some text ' + str(x) + ' some more text ' +
    ↵ str(x) + ' even more text that goes on for a while'

```

Beginning in version 1.6, automatic line breaks work with `showspaces=true` by default. Defining `breakbefore` or `breakafter` for `\space` is no longer necessary. For example,

```

\begin{Verbatim}[breaklines, showspaces]
some_string = 'Some Text That Goes On And On For So Long That It Could Never Fit'
\end{Verbatim}

```

```

some_string = 'Some Text That Goes On And On For So Long That
→ It Could Never Fit'

```

`breaknonspaceingroup` (boolean) (default: `false`)

By using `commandchars`, it is possible to include \LaTeX commands within otherwise verbatim text. In these cases, there can be groups (typically `{...}` but depends on `commandchars`) within verbatim. Spaces within groups are treated as potential line break locations when `breaklines=true`, but by default no other break locations are inserted (`breakbefore`, `breakafter`, `breakanywhere`). This is because inserting non-space break locations can interfere with command functionality. For example, in `\textcolor{red}{text}`, breaks shouldn't be inserted within `red`.

`breaknonspaceingroup` allows non-space breaks to be inserted within groups. This option should only be used when `commandchars` is including \LaTeX commands that do not take optional arguments and only take mandatory arguments that are typeset. Something like `\textit{text}` is fine, but `\textcolor{red}{text}` is not because one of the mandatory arguments is not typeset but rather provides a setting. For more complex commands, it is typically better to redefine them to insert breaks in appropriate locations using `\FancyVerbBreakStart... \FancyVerbBreakStop`.

`breakpreferspaces` (boolean) (default: `true`)
 This determines whether line breaks are preferentially inserted at normal spaces (`breakcollapsespaces=true`, `showspaces=false`) rather than at other locations allowed by `breakbefore`, `breakafter`, or `breakanywhere`.

Using `breakpreferspaces=false` with `breakanywhere=true` will typically result in all broken segments of a line going all the way to the right margin.

`breaksymbol` (string) (default: `breaksymbolleft`)
 Alias for `breaksymbolleft`.

`breaksymbolleft` (string) (default: `\tiny\ensuremath{\hookrightarrow}`, `\rightarrow`)
 The symbol used at the beginning (left) of continuation lines when `breaklines=true`. To have no symbol, simply set `breaksymbolleft` to an empty string ("`=`", "`={}`"). The symbol is wrapped within curly braces `{}` when used, so there is no danger of formatting commands such as `\tiny` "escaping."

The `\hookrightarrow` and `\hookleftarrow` may be further customized by the use of the `\rotatebox` command provided by `graphicx`. Additional arrow-type symbols that may be useful are available in the `dingbat` (`\carriagereturn`) and `mnsymbol` (hook and curve arrows) packages, among others.

`breaksymbolright` (string) (default: `<none>`)
 The symbol used at breaks (right) when `breaklines=true`. Does not appear at the end of the very last segment of a broken line.

`breaksymbolindent` (dimension) (default: `<breaksymbolindentleftnchars>`)
 Alias for `breaksymbolindentleft`.

`breaksymbolindentnchars` (integer) (default: `<breaksymbolindentleftnchars>`)
 Alias for `breaksymbolindentleftnchars`.

`breaksymbolindentleft` (dimension) (default: `<breaksymbolindentleftnchars>`)
 The extra left indentation that is provided to make room for `breaksymbolleft`. This indentation is only applied when there is a `breaksymbolleft`.

`breaksymbolindentleftnchars` (integer) (default: 4)
 This allows `breaksymbolindentleft` to be specified as an integer number of characters rather than as a dimension (assumes a fixed-width font).

`breaksymbolindentright` (dimension) (default: `<breaksymbolindentrightnchars>`)
 The extra right indentation that is provided to make room for `breaksymbolright`. This indentation is only applied when there is a `breaksymbolright`.

`breaksymbolindentrightnchars` (integer) (default: 4)
 This allows `breaksymbolindentright` to be specified as an integer number of characters rather than as a dimension (assumes a fixed-width font).

`breaksymbolsep` (dimension) (default: `<breaksymbolsepleftnchars>`)
 Alias for `breaksymbolsepleft`.

`breaksymbolsepnchars` (integer) (default: `<breaksymbolsepleftnchars>`)
 Alias for `breaksymbolsepleftnchars`.

`breaksymbolsepleft` (dimension) (default: `<breaksymbolsepleftnchars>`)
 The separation between the `breaksymbolleft` and the adjacent text.

- breaksymbolsepleftnchars** (integer) (default: 2)
 Allows **breaksymbolsepleft** to be specified as an integer number of characters rather than as a dimension (assumes a fixed-width font).
- breaksymbolsepright** (dimension) (default: $\langle\text{breaksymbolseprightnchars}\rangle$)
 The *minimum* separation between the **breaksymbolright** and the adjacent text. This is the separation between **breaksymbolright** and the furthest extent to which adjacent text could reach. In practice, **\linewidth** will typically not be an exact integer multiple of the character width (assuming a fixed-width font), so the actual separation between the **breaksymbolright** and adjacent text will generally be larger than **breaksymbolsepright**. This ensures that break symbols have the same spacing from the margins on both left and right. If the same spacing from text is desired instead, **breaksymbolsepright** may be adjusted. (See the definition of **\FV@makeLineNumber** for implementation details.)
- breaksymbolseprightnchars** (integer) (default: 2)
 Allows **breaksymbolsepright** to be specified as an integer number of characters rather than as a dimension (assumes a fixed-width font).
- spacebreak** (macro) (default: $\langle\text{\discretionary}\{\}\{\}\rangle$)
 This determines the break that is inserted around spaces when **breaklines=true** and one or more of the following conditions applies: **breakcollapsespaces=false**, **showspaces=true**, or the space is affected by **breakbefore** or **breakafter**. If it is redefined, it should typically be similar to **\FancyVerbBreakAnywhereBreak**, **\FancyVerbBreakBeforeBreak**, and **\FancyVerbBreakAfterBreak** to obtain consistent breaks.

7.2 Line breaking and tab expansion

fancyvrb provides an **obeytabs** option that expands tabs based on tab stops rather than replacing them with a fixed number of spaces (see **fancyvrb**'s **tabsize**). The **fancyvrb** implementation of tab expansion is not directly compatible with **fvextra**'s line-breaking algorithm, but **fvextra** builds on the **fancyvrb** approach to obtain identical results.

Tab expansion in the context of line breaking does bring some additional considerations that should be kept in mind. In each line, all tabs are expanded exactly as they would have been had the line not been broken. This means that after a line break, any tabs will not align with tab stops unless the total left indentation of continuation lines is a multiple of the tab stop width. The total indentation of continuation lines is the sum of **breakindent**, **breakautoindent**, and **breaksymbolindentleft** (alias **breaksymbolindent**).

A sample **Verbatim** environment that uses **obeytabs** with **breaklines** is shown below, with numbers beneath the environment indicating tab stops (**tabsize=8** by default). The tab stops in the wrapped and unwrapped lines are identical. However, the continuation line does not match up with the tab stops because by default the width of **breaksymbolindentleft** is equal to four monospace characters. (By default, **breakautoindent=true**, so the continuation line gets a tab plus **breaksymbolindentleft**.)

```

\begin{Verbatim}[obeytabs, showtabs, breaklines]
  ↪First  ↪Second ↪Third  ↪And more text that goes on for a
    ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪
    ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪
  ↪First  ↪Second ↪Third  ↪Forth
\end{Verbatim}
1234567812345678123456781234567812345678123456781234567812345678

```

We can set the symbol indentation to eight characters by creating a `dimen`,

```
\newdimen\temporarydimen
```

setting its width to eight characters,

```
\settowidth{\temporarydimen}{\ttfamily AaAaAaAa}
```

and finally adding the option `breaksymbolindentleft=\temporarydimen` to the `Verbatim` environment to obtain the following:

```

  ↪First  ↪Second ↪Third  ↪And more text that goes on for a
    ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪
    ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪   ↪
  ↪First  ↪Second ↪Third  ↪Forth
1234567812345678123456781234567812345678123456781234567812345678

```

7.3 Advanced line breaking

7.3.1 A few notes on algorithms

`breakanywhere`, `breakbefore`, and `breakafter` work by scanning through the tokens in each line and inserting line breaking commands wherever a break should be allowed. By default, they skip over all groups (`{...}`) and all math (`$. . . $`). Note that this refers to curly braces and dollar signs with their normal \LaTeX meaning (catcodes), not verbatim curly braces and dollar signs; such non-verbatim content may be enabled with `commandchars` or `codes`. This means that math and macros that only take mandatory arguments (`{...}`) will function normally within other-wise verbatim text. However, macros that take optional arguments may not work because `[...]` is not treated specially, and thus break commands may be inserted within `[...]` depending on settings. Wrapping an entire macro, including its arguments, in a group will protect the optional argument: `{\macro}[<opt>]{<arg>}`.

`breakbefore` and `breakafter` insert line breaking commands around specified characters. This process is catcode-independent; tokens are `\detokenized` before they are checked against characters specified via `breakbefore` and `breakafter`.

7.3.2 Breaks within macro arguments

```

\FancyVerbBreakStart
\FancyVerbBreakStop

```

When `commandchars` or `codes` are used to include macros within verbatim content, the options `breakanywhere`, `breakbefore`, and `breakafter` will not generate

breaks within mandatory macro arguments. Macros with optional arguments may not work, depending on settings, unless they are wrapped in a group (curly braces {}, or other characters specified via `commandchars`).

If you want to allow breaks within macro arguments (optional or mandatory), then you should (re)define your macros so that the relevant arguments are wrapped in the commands

```
\FancyVerbBreakStart ... \FancyVerbBreakStop
```

For example, suppose you have the macro

```
\newcommand{\mycmd}[1]{\_before:#1:after\_}
```

Then you would discover that line breaking does not occur:

```
\begin{Verbatim}[commandchars=\\\{\}, breaklines, breakafter=a]
\mycmd{1}\mycmd{2}\mycmd{3}\mycmd{4}\mycmd{5}
\end{Verbatim}

_____

\_before:1:after\_before:2:after\_before:3:after\_before:4:after\_before:5:after\_
```

Now redefine the macro:

```
\renewcommand{\mycmd}[1]{\_FancyVerbBreakStart\_before:#1:after\_\_FancyVerbBreakStop}
```

This is the result:

```
\begin{Verbatim}[commandchars=\\\{\}, breaklines, breakafter=a]
\mycmd{1}\mycmd{2}\mycmd{3}\mycmd{4}\mycmd{5}
\end{Verbatim}

_____

\_before:1:after\_before:2:after\_before:3:after\_before:4:a
↪ fter\_before:5:after\_
```

Instead of completely redefining macros, it may be more convenient to use `\let`. For example,

```
\let\originalmycmd\mycmd
\renewcommand{\mycmd}[1]{%
  \expandafter\FancyVerbBreakStart\originalmycmd{#1}\FancyVerbBreakStop}
```

Notice that in this case `\expandafter` is required, because `\FancyVerbBreakStart` does not perform any expansion and thus will skip over `\originalmycmd{#1}` unless it is already expanded. The `etoolbox` package provides commands that may be useful for patching macros to insert line breaks.

When working with `\FancyVerbBreakStart ... \FancyVerbBreakStop`, keep in mind that any groups {...} or math $...$$ between the two commands will be skipped as far as line breaks are concerned, and breaks may be inserted within any optional arguments [...] depending on settings. Inserting breaks within groups requires another level of `\FancyVerbBreakStart` and `\FancyVerbBreakStop`, and

protecting optional arguments requires wrapping the entire macro in a group `{...}`. Also, keep in mind that `\FancyVerbBreakStart` cannot introduce line breaks in a context in which they are never allowed, such as in an `\hbox`.

7.3.3 Customizing break behavior

`\FancyVerbBreakAnywhereBreak`

These macros govern the behavior of breaks introduced by `breakanywhere`, `breakbefore`, and `breakafter`. These do not apply to breaks inserted next to spaces; see `spacebreak`.

By default, these macros use `\discretionary`. `\discretionary` takes three arguments: commands to insert before the break, commands to insert after the break, and commands to insert if there is no break. For example, the default definition of `\FancyVerbBreakAnywhereBreak`:

```
\newcommand{\FancyVerbBreakAnywhereBreak}{%
  \discretionary{\FancyVerbBreakAnywhereSymbolPre}%
  {\FancyVerbBreakAnywhereSymbolPost}{}}
```

The other macros are equivalent, except that “Anywhere” is swapped for “Before” or “After”.

`\discretionary` will generally only insert breaks when breaking at spaces simply cannot make lines short enough (this may be tweaked to some extent with hyphenation settings). This can produce a somewhat ragged appearance in some cases. If you want breaks exactly at the margin (or as close as possible) regardless of whether a break at a space is an option, you may want to use `\allowbreak` instead. Another option is `\linebreak[⟨n⟩]`, where `⟨n⟩` is between 0 to 4, with 0 allowing a break and 4 forcing a break.

8 Pygments support

8.1 Options for users

`fvextra` defines additional options for working code that has been highlighted with `Pygments`. These options work with the `minted` and `pythontex` packages, and may be enabled for other packages that work with `Pygments` output (section 8.2).

`breakbytoken` (boolean) (default: `false`)
When `breaklines=true`, do not allow breaks within `Pygments` tokens. This would prevent, for example, line breaking within strings.

`breakbytokenanywhere` (boolean) (default: `false`)
When `breaklines=true`, do not allow breaks within `Pygments` tokens, but always allow breaks between tokens even when they are immediately adjacent (not separated by spaces). **This option should be used with care.** Due to the details of how each `Pygments` lexer works, and due to the tokens defined in each lexer, this may result in breaks in locations that might not be anticipated. Also keep in mind that this will not allow breaks between tokens if those tokens are actually “subtokens” within another token.

`\FancyVerbBreakByTokenAnywhereBreak`

This defines the break inserted when `breakbytokenanywhere=true`. By default, it is `\allowbreak`.

8.2 For package authors

By default, line breaking will only partially work with Pygments output; `breakbefore` and `breakafter` will not work with any characters that do not appear literally in Pygments output but rather are replaced with a character macro. Also, `breakbytoken` and `breakbytokenanywhere` will not function at all.

```
\VerbatimPygments{<literal_macro>}{<actual_macro>}
```

To enable full Pygments support, use this macro before `\begin{Verbatim}`, etc. This macro must be used within `\begin{group}... \end{group}` to prevent settings from escaping into the rest of the document. It may be used safely at the beginning of a `\newenvironment` definition. When used with `\newcommand`, though, the `\begin{group}... \end{group}` will need to be inserted explicitly.

`<literal_macro>` is the Pygments macro that literally appears in Pygments output; it corresponds to the Pygments `commandprefix`. For `minted` and `pythontex`, this is `\PYG`. `<actual_macro>` is the Pygments macro that should actually be used. For `minted` this is `\PYG`; for `pythontex` this is `\PYG<style>`. In the `minted` and `pythontex` approach, code is only highlighted once (`\PYG`), and then the style is changed by redefining the macro that literally appears to use the appropriate style macro.

`\VerbatimPygments` takes the two Pygments macros and redefines `<literal_macro>` so that it will invoke `<actual_macro>` while fully supporting line breaks, `breakbytoken`, and `breakbytokenanywhere`. No further modification of either `<literal_macro>` or `<actual_macro>` is possible after `\VerbatimPygments` is used.

In packages that do not make a distinction between `<literal_macro>` and `<actual_macro>`, simply use `\VerbatimPygments` with two identical arguments; `\VerbatimPygments` is defined to handle this case.

`\VerbatimPygments` also improves other features of Pygments token macros, including improving support for Pygments options `escapeinside` and `texcomments`. See the implementation for details.

9 Patches

`fvextra` modifies some `fancyvrb` behavior that is the result of bugs or omissions.

9.1 Visible spaces

The command `\FancyVerbSpace` defines the visible space when `showspaces=true`. The default `fancyvrb` definition allows a font command to escape under some circumstances, so that all following text is forced to be teletype font. The command is redefined following <https://tex.stackexchange.com/a/120231/10742>.

9.2 obeytabs with visible tabs and with tabs inside macro arguments

The original `fancyvrb` treatment of visible tabs when `showtabs=true` and `obeytabs=true` did not allow variable-width tab symbols such as `\rightarrowfill` to function correctly. This is fixed through a redefinition of `\FV@TrueTab`.

Various macros associated with `obeytabs=true` are also redefined so that tabs may be expanded regardless of whether they are within a group (within `{...}` with the normal L^AT_EX meaning due to `commandchars`, etc.). In the `fancyvrb`

implementation, using `obeytabs=true` when a tab is inside a group typically causes the entire line to vanish. `fvextra` patches this so that the tab is expanded and will be visible if `showtabs=true`. Note, though, that the tab expansion in these cases is only guaranteed to be correct for leading whitespace that is inside a group. The start of each run of whitespace that is inside a group is treated as a tab stop, whether or not it actually is, due to limitations of the tab expansion algorithm. A more detailed discussion is provided in the implementation.

The example below shows correct tab expansion of leading whitespace within a macro argument. With `fancyvrb`, the line of text would simply vanish in this case.

```
\begin{Verbatim}[obeytabs, showtabs, showspaces, tabsize=4,
  commandchars=\\\{\}, tab=\textcolor{orange}{\rightarrowfill}]
\textcolor{blue}{      ↪      ↪Text after 1 space + 2 tabs}
\end{Verbatim}
```

↳→→→Text after 1 space + 2 tabs

The next example shows that tab expansion inside macros in the midst of text typically does not match up with the correct tab stops, since in such circumstances the beginning of the run of whitespace must be treated as a tab stop.

```
\begin{Verbatim}[obeytabs, showtabs, commandchars=\\\{\},
  tab=\textcolor{orange}{\rightarrowfill}]
\textcolor{blue}{      ↪      ↪2 leading tabs}
\textcolor{blue}{Text ↪      ↪then 2 tabs}
\end{Verbatim}
```

↳→→→2 leading tabs
Text ↳→→→then 2 tabs

9.3 Math mode

9.3.1 Spaces

When typeset math is included within verbatim material, `fancyvrb` makes spaces within the math appear literally.

```
\begin{Verbatim}[commandchars=\\\{\}, mathescape]
Verbatim $\displaystyle\frac{1}{x^2 + y^2}$ verbatim
\end{Verbatim}
```

Verbatim $\frac{1}{x^2 + y^2}$ verbatim

`fvextra` patches this by redefining `fancyvrb`'s space character within math mode so that it behaves as expected:

Verbatim $\frac{1}{x^2 + y^2}$ verbatim

9.3.2 Symbols and fonts

With `fancyvrb`, ASCII symbols may give errors within math or may not appear as expected. `fvextra` redefines all ASCII symbols so that they will behave as literal characters or (if `\active` outside the verbatim context) as macros within math. This behavior is overridden for specific characters by the `codes`, `commandchars`, and `mathescape` options.

With `fancyvrb`, using a single quotation mark (') in typeset math within verbatim material results in an error rather than a prime symbol (').⁸ `fvextra` redefines the behavior of the single quotation mark within math mode to fix this, so that it will become a proper prime.

The `amsmath` package provides a `\text` command for including normal text within math. With `fancyvrb`, `\text` does not behave normally when used in typeset math within verbatim material. `fvextra` redefines the backtick (``) and the single quotation mark so that they function normally within `\text`, becoming left and right quotation marks. It redefines the greater-than sign, less-than sign, comma, and hyphen so that they function normally as well. `fvextra` also switches back to the default document font within `\text`, rather than using the verbatim font, which is typically a monospace or typewriter font.

The result of these modifications is a math mode that very closely mimics the behavior of normal math mode outside of verbatim material.

```
\begin{Verbatim}[commandchars=\\\{\}, mathescape]
Verbatim  $\end{Verbatim}$ 
```

Verbatim $f'''(x) = \text{“Some quoted text—”}$

9.4 Orphaned labels

When `frame=lines` is used with a label, `fancyvrb` does not prevent the label from being orphaned under some circumstances. `\FV@BeginListFrame@Lines` is patched to prevent this.

9.5 rulecolor and fillcolor

The `rulecolor` and `fillcolor` options are redefined so that they accept color names directly, rather than requiring `\color{<color_name>}`. The definitions still allow the old usage.

9.6 Command lookahead tokenization

`\FV@Command` is used internally by commands like `\Verb` to read stars (*) and optional arguments ([...]) before invoking the core of the command. This is redefined so that lookahead tokenizes under a verbatim catcode regime. The original definition could prevent commands like `\Verb` from using characters like %

⁸The single quotation mark is made active within verbatim material to prevent ligatures, via `\@noligs`. The default definition is incompatible with math mode.

as delimiters, because the lookahead for a star and optional argument could read the % and give it its normal meaning of comment character. The new definition fixes this, so that commands like `\Verb` behave as closely to `\verb` as possible.

10 Additional modifications to `fancyvrb`

`fvextra` modifies some `fancyvrb` behavior with the intention of improving logical consistency or providing better defaults.

10.1 Backtick and single quotation mark

With `fancyvrb`, the backtick ``` and typewriter single quotation mark `'` are typeset as the left and right curly single quotation marks `‘`. `fvextra` loads the `upquote` package so that these characters will appear literally by default. The original `fancyvrb` behavior can be restored with the `fvextra` option `curlyquotes` (section 3).

10.2 Line numbering

With `fancyvrb`, using `firstnumber` to offset line numbering in conjunction with `stepnumber` changes which line numbers appear. Lines are numbered if their original line numbers, without the `firstnumber` offset, are a multiple of `stepnumber`. But the actual numbers that appear are the offset values that include `firstnumber`. Thus, using `firstnumber=2` with `stepnumber=5` would cause the original lines 5, 10, 15, ... to be numbered, but with the values 6, 11, 16, ...

`fvextra` changes line numbering so that when `stepnumber` is used, the actual line numbers that appear are always multiples of `stepnumber` by default, regardless of any `firstnumber` offset. The original `fancyvrb` behavior may be turned on by setting `stepnumberoffsetvalues=true` (section 3).

11 Undocumented features of `fancyvrb`

`fancyvrb` defines some potentially useful but undocumented features.

11.1 Undocumented option

`listparameters` (macro) (default: `empty`)
Set list-related lengths to modify spacing around lines of code. For example, `listparameters=\setlength{\topsep}{0pt}` will remove space before and after a `Verbatim` environment.

11.2 Undocumented macros

`\FancyVerbTab`

This defines the visible tab character (`\`) that is used when `showtabs=true`. The default definition is

```
\def\FancyVerbTab{%  
  \valign{%  
    \vfil##\vfil\cr
```

```

\hbox{${\scriptscriptstyle-}$}\cr
\hbox to 0pt{\hss${\scriptscriptstyle}\rangle\mskip -.8mu$}\cr
\hbox{${\scriptstyle}\mskip -3mu\mid\mskip -1.4mu$}\cr}}

```

While this may be redefined directly, `fvextra` also defines a new option `tab`

`\FancyVerbSpace`

This defines the visible space character (`_`) that is used when `showspaces=true`. The default definition (as patched by `fvextra`, section 9.1) follows <https://tex.stackexchange.com/a/120231/10742>. While this may be redefined directly, `fvextra` also defines a new option `space`.

12 Implementation

12.1 Required packages

The `upquote` package performs some font checks when it is loaded to determine whether `textcomp` is needed, but errors can result if the font is changed later in the preamble, so duplicate the package's font check at the end of the preamble. Also check for a package order issue with `lineno` and `csquotes`.

```

1 \RequirePackage{etoolbox}
2 \RequirePackage{fancyvrb}
3 \RequirePackage{upquote}
4 \AtEndPreamble{%
5   \ifx\encodingdefault\upquote@OTone
6     \ifx\ttdefault\upquote@cmtt\else\RequirePackage{textcomp}\fi
7   \else
8     \RequirePackage{textcomp}
9   \fi}
10 \RequirePackage{lineno}
11 \@ifpackageloaded{csquotes}%
12   {\PackageWarning{fvextra}{csquotes should be loaded after fvextra, %
13     to avoid a warning from the lineno package}}{}

```

12.2 Utility macros

12.2.1 `fancyvrb` space and tab tokens

`\FV@ActiveSpaceToken`

Active space for `\ifx` token comparisons.

```

14 \begingroup
15 \catcode`\_ =\active%
16 \gdef\FV@ActiveSpaceToken{ }%
17 \endgroup%

```

`\FV@SpaceCatTen`

Space with catcode 10. Used instead of `_` and `\space` in some contexts to avoid issues in the event that these are redefined.

```

18 \edef\FV@SpaceCatTen{{\detokenize{ }}}

```

`\FV@FVSpaceToken`

Macro with the same definition as `fancyvrb`'s active space. Useful for `\ifx` comparisons, such as `\@ifnextchar` lookaheads.

```

19 \def\FV@FVSpaceToken{\FV@Space}

```

`\FV@FVTabToken`

Macro with the same definition as `fancyvrb`'s active tab. Useful for `\ifx` comparisons, such as `\@ifnextchar` lookaheads.

```
20 \def\FV@FVTabToken{\FV@Tab}
```

12.2.2 ASCII processing

`\FVExtraDoSpecials`

Apply `\do` to all printable, non-alphanumeric ASCII characters (codepoints 0x20 through 0x7E except for alphanumeric characters).

These punctuation marks and symbols are the most likely characters to be made `\active`, so it is convenient to be able to change the catcodes for all of them, not just for those in the `\dospecials` defined in `latex.ltx`:

```
\def\dospecials{\do\ \do\\\do\{\do\}\do\$\do\&%  
\do\#\do\^\do\_ \do%\do\~}
```

If a command takes an argument delimited by a given symbol, but that symbol has been made `\active` and defined as `\outer` (perhaps it is being used as a short `\verb`), then changing the symbol's catcode is the only way to use it as a delimiter.

```
21 \def\FVExtraDoSpecials{%  
22 \do\ \do\!\do\\"\do\#\do\$\do\%\do\&\do\'\do\(\do\)\do\*\do\+\do\,\do\-%  
23 \do\.\do\/\do\:\do\;\do\<\do\=\do\>\do\?\do\@\do\[ \do\]\do\]\do\^\do\_%  
24 \do\^\do\{\do\|\do\}\do\~}
```

`\FV@Char@Special:<char>`

Create macros for all printable, non-alphanumeric ASCII characters. This is used in creating backslash escapes that can only be applied to ASCII symbols and punctuation; these macros serve as `\ifcsname` lookups for valid escapes.

```
25 \begingroup  
26 \def\do#1{%  
27 \expandafter\global\expandafter  
28 \let\csname FV@Char@Special:\number`#1\endcsname\relax}  
29 \FVExtraDoSpecials  
30 \endgroup
```

`\FV@Char@CatTwelve:<char>`

`\FV@Char@CatDetok:<char>`

`\FV@Char@CatActive:<char>`

Macros for accessing printable, non-alphanumeric ASCII characters with various catcodes.

```
31 \begingroup  
32 \catcode`\!=0  
33 \catcode`\<=1  
34 \catcode`\>=2  
35 \catcode`\&=14!relax&  
36 !edef!FVCharNum<!number`!\>&  
37 !catcode`!\=12!relax&  
38 !expandafter!gdef!csname!detokenize<FV@Char@CatTwelve:>!FVCharNum!endcsname<\>&  
39 !expandafter!xdef!csname!detokenize<FV@Char@CatDetok:>!FVCharNum!endcsname<!detokenize<\>>&  
40 !catcode`!\=!active&  
41 !expandafter!gdef!csname!detokenize<FV@Char@CatActive:>!FVCharNum!endcsname<\>&  
42 !edef!FVCharNum<!number`!{>&
```

```

43 !catcode`\!=12!relax&
44 !expandafter!gdef!csname!detokenize<FV@Char@CatTwelve:>!FVCharNum!endcsname<{>&
45 !expandafter!xdef!csname!detokenize<FV@Char@CatDetok:>!FVCharNum!endcsname!detokenize<{>>&
46 !catcode`\!=!active&
47 !expandafter!gdef!csname!detokenize<FV@Char@CatActive:>!FVCharNum!endcsname<{>&
48 !edef!FVCharNum<!number`!>&
49 !catcode`\}=12!relax&
50 !expandafter!gdef!csname!detokenize<FV@Char@CatTwelve:>!FVCharNum!endcsname<}>&
51 !expandafter!xdef!csname!detokenize<FV@Char@CatDetok:>!FVCharNum!endcsname!detokenize<}>>&
52 !catcode`\}=!active&
53 !expandafter!gdef!csname!detokenize<FV@Char@CatActive:>!FVCharNum!endcsname<}>&
54 !edef!FVCharNum<!number`! >&
55 !catcode`\}=12!relax&
56 !expandafter!gdef!csname!detokenize<FV@Char@CatTwelve:>!FVCharNum!endcsname< >&
57 !expandafter!xdef!csname!detokenize<FV@Char@CatDetok:>!FVCharNum!endcsname!detokenize< >>&
58 !catcode`\}=!active&
59 !expandafter!gdef!csname!detokenize<FV@Char@CatActive:>!FVCharNum!endcsname< >&
60 !edef!FVCharNum<!number`!%>&
61 !catcode`\}%=12!relax&
62 !expandafter!gdef!csname!detokenize<FV@Char@CatTwelve:>!FVCharNum!endcsname<%>&
63 !expandafter!xdef!csname!detokenize<FV@Char@CatDetok:>!FVCharNum!endcsname!detokenize<%>>&
64 !catcode`\}%=!active&
65 !expandafter!gdef!csname!detokenize<FV@Char@CatActive:>!FVCharNum!endcsname<%>&
66 !endgroup
67 \begingroup
68 \edef\FVCharNum{\number`\!}
69 \catcode`\!=12
70 \expandafter!gdef!csname!detokenize{FV@Char@CatTwelve:}\FVCharNum!endcsname{!}
71 \expandafter!xdef!csname!detokenize{FV@Char@CatDetok:}\FVCharNum!endcsname{\detokenize{!}}
72 \catcode`\!=!active
73 \expandafter!gdef!csname!detokenize{FV@Char@CatActive:}\FVCharNum!endcsname{!}
74 \endgroup
75 \begingroup
76 \edef\FVCharNum{\number`\"}
77 \catcode`\="=12
78 \expandafter!gdef!csname!detokenize{FV@Char@CatTwelve:}\FVCharNum!endcsname{"}
79 \expandafter!xdef!csname!detokenize{FV@Char@CatDetok:}\FVCharNum!endcsname{\detokenize{"}}
80 \catcode`\="=!active
81 \expandafter!gdef!csname!detokenize{FV@Char@CatActive:}\FVCharNum!endcsname{"}
82 \endgroup
83 \begingroup
84 \edef\FVCharNum{\number`\#}
85 \catcode`\#=12
86 \expandafter!gdef!csname!detokenize{FV@Char@CatTwelve:}\FVCharNum!endcsname{#}
87 \expandafter!xdef!csname!detokenize{FV@Char@CatDetok:}\FVCharNum!endcsname{\detokenize{#}}
88 \catcode`\#=!active
89 \expandafter!gdef!csname!detokenize{FV@Char@CatActive:}\FVCharNum!endcsname{#}
90 \endgroup
91 \begingroup
92 \edef\FVCharNum{\number`\$}
93 \catcode`\$=12
94 \expandafter!gdef!csname!detokenize{FV@Char@CatTwelve:}\FVCharNum!endcsname{$}
95 \expandafter!xdef!csname!detokenize{FV@Char@CatDetok:}\FVCharNum!endcsname{\detokenize{$}}
96 \catcode`\$=!active

```

```

97 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{$}
98 \endgroup
99 \begingroup
100 \edef\FVCharNum{\number`&}
101 \catcode`&=12
102 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{&}
103 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{&}}
104 \catcode`&=\active
105 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{&}
106 \endgroup
107 \begingroup
108 \edef\FVCharNum{\number`'}
109 \catcode`'=12
110 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{'}
111 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{'}}
112 \catcode`'=\active
113 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{'}
114 \endgroup
115 \begingroup
116 \edef\FVCharNum{\number`\()}
117 \catcode`\(=12
118 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{()}
119 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{()}}
120 \catcode`\(=\active
121 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{()}
122 \endgroup
123 \begingroup
124 \edef\FVCharNum{\number`\)}
125 \catcode`\)=12
126 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{)}
127 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{)}}
128 \catcode`\)=\active
129 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{)}
130 \endgroup
131 \begingroup
132 \edef\FVCharNum{\number`*}
133 \catcode`*=12
134 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{*}
135 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{*}}
136 \catcode`*=\active
137 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{*}
138 \endgroup
139 \begingroup
140 \edef\FVCharNum{\number`\+}
141 \catcode`\+=12
142 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{+}
143 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{+}}
144 \catcode`\+=\active
145 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{+}
146 \endgroup
147 \begingroup
148 \edef\FVCharNum{\number`\,}
149 \catcode`\,=12
150 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{,}

```

```

151 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{,}}
152 \catcode`\,=\active
153 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{,}
154 \endgroup
155 \begingroup
156 \edef\FVCharNum{\number`-}
157 \catcode`-=12
158 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{-}
159 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{-}}
160 \catcode`-=\active
161 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{-}
162 \endgroup
163 \begingroup
164 \edef\FVCharNum{\number`.}
165 \catcode`.=12
166 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{.}
167 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{.}}
168 \catcode`.=\active
169 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{.}
170 \endgroup
171 \begingroup
172 \edef\FVCharNum{\number`\/}
173 \catcode`\/=12
174 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{/}
175 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{/}}
176 \catcode`\/=\active
177 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{/}
178 \endgroup
179 \begingroup
180 \edef\FVCharNum{\number`\:}
181 \catcode`\:=12
182 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{:}
183 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{:}}
184 \catcode`\:=\active
185 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{:}
186 \endgroup
187 \begingroup
188 \edef\FVCharNum{\number`;}
189 \catcode`;=12
190 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{;}
191 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{;}}
192 \catcode`;=\active
193 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{;}
194 \endgroup
195 \begingroup
196 \edef\FVCharNum{\number`<}
197 \catcode`<=12
198 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{<}
199 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{<}}
200 \catcode`<=\active
201 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{<}
202 \endgroup
203 \begingroup
204 \edef\FVCharNum{\number`=}

```

```

205 \catcode`\==12
206 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{=}
207 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{=}}
208 \catcode`\==\active
209 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{=}
210 \endgroup
211 \begingroup
212 \edef\FVCharNum{\number`\>}
213 \catcode`\>=12
214 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{>}
215 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{>}}
216 \catcode`\>=\active
217 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{>}
218 \endgroup
219 \begingroup
220 \edef\FVCharNum{\number`?\}
221 \catcode`\?=12
222 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{?}
223 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{?}}
224 \catcode`\?=\active
225 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{?}
226 \endgroup
227 \begingroup
228 \edef\FVCharNum{\number`\@}
229 \catcode`\@=12
230 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{@}
231 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{@}}
232 \catcode`\@=\active
233 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{@}
234 \endgroup
235 \begingroup
236 \edef\FVCharNum{\number`\[]}
237 \catcode`\[]=12
238 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{[]}
239 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{[]}}
240 \catcode`\[]=\active
241 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{[]}
242 \endgroup
243 \begingroup
244 \edef\FVCharNum{\number`\]}
245 \catcode`\]=12
246 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{]}
247 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{]}}
248 \catcode`\]=\active
249 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{]}
250 \endgroup
251 \begingroup
252 \edef\FVCharNum{\number`\^}
253 \catcode`\^=12
254 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{^}
255 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{^}}
256 \catcode`\^=\active
257 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{^}
258 \endgroup

```

```

259 \begingroup
260 \edef\FVCharNum{\number`\_}
261 \catcode`\_ =12
262 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{\_}
263 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{\_}}
264 \catcode`\_ =\active
265 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{\_}
266 \endgroup
267 \begingroup
268 \edef\FVCharNum{\number`\`}
269 \catcode`\` =12
270 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{`}
271 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{`}}
272 \catcode`\` =\active
273 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{`}
274 \endgroup
275 \begingroup
276 \edef\FVCharNum{\number`\|}
277 \catcode`\| =12
278 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{|}
279 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{|}}
280 \catcode`\| =\active
281 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{|}
282 \endgroup
283 \begingroup
284 \edef\FVCharNum{\number`\~}
285 \catcode`\~ =12
286 \expandafter\gdef\csname\detokenize{FV@Char@CatTwelve:}\FVCharNum\endcsname{~}
287 \expandafter\xdef\csname\detokenize{FV@Char@CatDetok:}\FVCharNum\endcsname{\detokenize{~}}
288 \catcode`\~ =\active
289 \expandafter\gdef\csname\detokenize{FV@Char@CatActive:}\FVCharNum\endcsname{~}
290 \endgroup

```

`\FVExtraSaveCodes`

`\FVExtraUseCodes`

`\FancyVerbRestoreCodes`

Save catcodes of all characters in `\FVExtraDoSpecials`, and then restore them. The `\FVExtra*` commands take arguments of the form `[(pkg)]{<name>}`.

`\FancyVerbRestoreCodes` is a shortcut for `\FVExtraUseCodes[fancyvrb]{BeforeVerbatim}`.

```

291 \newcommand{\FVExtraSaveCodes}[2][{}]{%
292   \ifcsname do\endcsname
293     \let\FV@dotmp\do
294     \fi
295   \if\relax\detokenize{#1}\relax
296     \def\do##1{%
297       \expandafter
298       \chardef\csname FV@SVCode:\number`##1@#2\endcsname=%
299       \catcode`##1\relax}%
300   \expandafter\let\csname FV@SVCodes@#2\endcsname\relax
301   \else
302     \def\do##1{%
303       \expandafter
304       \chardef\csname FV@PkgSVCode:\number`##1@#1:#2\endcsname=%
305       \catcode`##1\relax}%

```

```

306     \expandafter\let\csname FV@PkgSVCodes@#1:#2\endcsname\relax
307   \fi
308   \FVExtraDoSpecials
309   \ifcsname FV@dotmp\endcsname
310     \let\do\FV@dotmp
311     \let\FV@dotmp\FV@Undefined
312   \else
313     \let\do\FV@Undefined
314   \fi}
315 \newcommand{\FVExtraUseCodes}[2][\%
316   \if\relax\detokenize{#1}\relax
317     \expandafter\FVExtraUseCodes@NoPkg
318   \else
319     \expandafter\FVExtraUseCodes@Pkg
320   \fi
321   {#1}{#2}}
322 \def\FVExtraUseCodes@NoPkg#1#2{%
323   \ifcsname FV@SVCodes@#2\endcsname
324     \expandafter\FVExtraUseCodes@NoPkg@i
325   \else
326     \PackageError{fvextra}%
327       {Unknown name "#2" for saved catcodes}%
328       {Check name of saved catcodes}%
329     \expandafter\@gobble
330   \fi
331   {#2}}
332 \def\FVExtraUseCodes@NoPkg@i#1{%
333   \FVExtraUseCodes@end{FV@SVCodes}{#1}}
334 \def\FVExtraUseCodes@Pkg#1#2{%
335   \ifcsname FV@PkgSVCodes@#1:#2\endcsname
336     \expandafter\FVExtraUseCodes@Pkg@i
337   \else
338     \PackageError{fvextra}%
339       {Unknown name "#2" for saved catcodes for package "#1"}%
340       {Check name of saved catcodes}%
341     \expandafter\@gobble
342   \fi
343   {#1:#2}}
344 \def\FVExtraUseCodes@Pkg@i#1{%
345   \FVExtraUseCodes@end{FV@PkgSVCodes}{#1}}
346 \def\FVExtraUseCodes@end#1#2{%
347   \ifcsname do\endcsname
348     \let\FV@dotmp\do
349   \fi
350   \def\do##1{%
351     \catcode`##1=%
352     \csname #1:\number`##1@#2\endcsname\relax}%
353   \FVExtraDoSpecials
354   \ifcsname FV@dotmp\endcsname
355     \let\do\FV@dotmp
356     \let\FV@dotmp\FV@Undefined
357   \else
358     \let\do\FV@Undefined
359   \fi}

```

```

360 \AtEndOfPackage{%
361   \FV@AddToHook{\FV@UseKeyValues@Hook}{\FVExtraSaveCodes[fancyvrb]{BeforeVerbatim}}
362   \def\FancyVerbRestoreCodes{\FVExtraUseCodes[fancyvrb]{BeforeVerbatim}}

```

12.2.3 Sentinels

Sentinel macros are needed for scanning tokens.

There are two contexts in which sentinels may be needed. In delimited macro arguments, such as `\def\macro#1\sentinel{...}`, a sentinel is needed as the delimiter. Because the delimiting macro need not be defined, special delimiting macros need not be created for this case. The important thing is to ensure that the macro name is sufficiently unique to avoid collisions. Typically, using `\makeatletter` to allow something like `\@sentinel` will be sufficient. For added security, additional characters can be given catcode 11, to allow things like `\@sent!nel`.

The other context for sentinels is in scanning through a sequence of tokens that is delimited by a sentinel, and using `\ifx` comparisons to identify the sentinel and stop scanning. In this case, using an undefined macro is risky. Under normal conditions, the sequence of tokens could contain an undefined macro due to mistyping. In some `fvextra` applications, the tokens will have been incorrectly tokenized under a normal catcode regime, and need to be retokenized as verbatim, in which case undefined macros must be expected. Thus, a sentinel macro whose expansion is resistant to collisions is needed.

`\FV@<Sentinel>`

This is the standard default `fvextra` delimited-macro sentinel. It is used with `\makeatletter` by changing `<` and `>` to catcode 11. The `<` and `>` add an extra level of collision resistance. Because it is undefined, it is *only* appropriate for use in delimited macro arguments.

`\FV@Sentinel`

This is the standard `fvextra` `\ifx` comparison sentinel. It expands to the control word `\FV@<Sentinel>`, which is very unlikely to be in any other macro since it requires that `@`, `<`, and `>` all have catcode 11 and appear in the correct sequence. Because its definition is itself undefined, this sentinel will result in an error if it escapes.

```

363 \begingroup
364 \catcode`\<=11
365 \catcode`\>=11
366 \gdef\FV@Sentinel{\FV@<Sentinel>}
367 \endgroup

```

12.2.4 Active character definitions

`\FV@OuterDefEOLEmpty`

Macro for defining the active end-of-line character \r , which `fancyvrb` uses to prevent runaway command arguments. `fancyvrb` uses macro definitions of the form

```

\begingroup
\catcode`\r=\active%
\gdef\macro{%
...
\outer\def\r{%

```

```

...
}%
\endgroup

```

While this works, it is nice to avoid the `\begingroup... \endgroup` and especially the requirement that all lines now end with `%` to discard the `^^M` that would otherwise be inserted.

```

368 \begingroup
369 \catcode^^M=\active%
370 \gdef\FV@OuterDefEOLEmpty{\outer\def^^M{}}%
371 \endgroup

```

`\FV@DefEOLEmpty`

The same thing, without the `\outer`. This is used to ensure that `^^M` is not `\outer` when it should be read.

```

372 \begingroup
373 \catcode^^M=\active%
374 \gdef\FV@DefEOLEmpty{\def^^M{}}%
375 \endgroup

```

`\FV@OuterDefSTXEmpty`

Define start-of-text (STX) `^^B` so that it cannot be used inside other macros. This makes it possible to guarantee that `^^B` is not part of a verbatim argument, so that it can be used later as a sentinel in retokenizing the argument.

```

376 \begingroup
377 \catcode^^B=\active
378 \gdef\FV@OuterDefSTXEmpty{\outer\def^^B{}}
379 \endgroup

```

`\FV@OuterDefETXEmpty`

Define end-of-text (ETX) `^^C` so that it cannot be used inside other macros. This makes it possible to guarantee that `^^C` is not part of a verbatim argument, so that it can be used later as a sentinel in retokenizing the argument.

```

380 \begingroup
381 \catcode^^C=\active
382 \gdef\FV@OuterDefETXEmpty{\outer\def^^C{}}
383 \endgroup

```

12.3 pdfTeX with inputenc using UTF-8

Working with verbatim text often involves handling individual code points. While these are treated as single entities under LuaTeX and XeTeX, under pdfTeX code points must be handled at the byte level instead. This means that reading a single code point encoded in UTF-8 may involve a macro that reads up to four arguments.

Macros are defined for working with non-ASCII code points under pdfTeX. These are only for use with the `inputenc` package set to `utf8` encoding.

`\ifFV@pdfTeXinputenc`

All of the UTF macros are only needed with pdfTeX when `inputenc` is loaded, so they are created conditionally, inspired by the approach of the `iftex` package. The tests deal with the possibility that a previous test using `\ifx` rather than the cleaner `\ifcsname` has already been performed. These assume that `inputenc` will be loaded before `fvextra`. The `\inputencodingname` tests should be redundant after the `\@ifpackageloaded` test, but do provide some additional safety if another

package is faking `inputenc` being loaded but not providing an equivalent encoding interface.

Note that an encoding test of the form

```
\ifdefstring{\inputencodingname}{utf8}{<true>}{<false>}
```

is still required before switching to the UTF variants in any given situation. A document using `inputenc` can switch encodings (for example, around an `\input`), so simply checking encoding when `fvextra` is loaded is *not* sufficient.

```
384 \newif\ifFV@pdfTeXinputenc
385 \FV@pdfTeXinputencfalse
386 \ifcsname pdfmatch\endcsname
387 \ifx\pdfmatch\relax
388 \else
389   \@ifpackageloaded{inputenc}%
390     {\ifcsname inputencodingname\endcsname
391       \ifx\inputencodingname\relax
392         \else
393           \FV@pdfTeXinputenctrue
394         \fi\fi}
395     {}%
396 \fi\fi
```

Define UTF macros conditionally:

```
397 \ifFV@pdfTeXinputenc
```

```
\FV@U8:<byte>
```

Define macros of the form `\FV@U8:<byte>` for each active byte. These are used for determining whether a token is the first byte in a multi-byte sequence, and if so, invoking the necessary macro to capture the remaining bytes. The code is adapted from the beginning of `utf8.def`. Completely capitalized macro names are used to avoid having to worry about `\uppercase`.

```
398 \begingroup
399 \catcode`\~=13
400 \catcode`\ "=12
401 \def\FV@UTFviii@loop{%
402   \uccode`\~\count@
403   \uppercase\expandafter{\FV@UTFviii@Tmp}%
404   \advance\count@\@ne
405   \ifnum\count@<\@tempcnta
406     \expandafter\FV@UTFviii@loop
407   \fi}
```

Setting up 2-byte UTF-8:

```
408 \count@"C2
409 \@tempcnta"E0
410 \def\FV@UTFviii@Tmp{\expandafter\gdef\csname FV@U8:\string~\endcsname{%
411   \FV@UTF@two@octets}}
412 \FV@UTFviii@loop
```

Setting up 3-byte UTF-8:

```
413 \count@"E0
414 \@tempcnta"F0
415 \def\FV@UTFviii@Tmp{\expandafter\gdef\csname FV@U8:\string~\endcsname{%
416   \FV@UTF@three@octets}}
417 \FV@UTFviii@loop
```

Setting up 4-byte UTF-8:

```
418 \count"F0
419 \@tempcnta"F4
420 \def\FV@UTFviii@Tmp{\expandafter\gdef\csname FV@U8:\string~\endcsname{%
421   \FV@UTF@four@octets}}
422 \FV@UTFviii@loop
423 \endgroup
\FV@UTF@two@octets
\FV@UTF@three@octets
\FV@UTF@four@octets
```

These are variants of the `utf8.def` macros that capture all bytes of a multi-byte code point and then pass them on to `\FV@UTF@octets@after` as a single argument for further processing. The invoking macro should `\let` or `\def`'ed `\FV@UTF@octets@after` to an appropriate macro that performs further processing.

Typical use will involve the following steps:

1. Read a token, say `#1`.
2. Use `\ifcsname FV@U8:\detokenize{#1}\endcsname` to determine that the token is the first byte of a multi-byte code point.
3. Ensure that `\FV@UTF@octets@after` has an appropriate value, if this has not already been done.
4. Use `\csname FV@U8:\detokenize{#1}\endcsname#1` at the end of the original reading macro to read the full multi-byte code point and then pass it on as a single argument to `\FV@UTF@octets@after`.

All code points are checked for validity here so as to raise errors as early as possible. Otherwise an invalid terminal byte sequence might gobble a sentinel macro in a scanning context, potentially making debugging much more difficult. It would be possible to use `\UTFviii@defined{<bytes>}` to trigger an error directly, but the current approach is to attempt to typeset invalid code points, which should trigger errors without relying on the details of the `utf8.def` implementation.

```
424 \def\FV@UTF@two@octets#1#2{%
425   \ifcsname u8:\detokenize{#1#2}\endcsname
426   \else
427     #1#2%
428   \fi
429   \FV@UTF@octets@after{#1#2}}
430 \def\FV@UTF@three@octets#1#2#3{%
431   \ifcsname u8:\detokenize{#1#2#3}\endcsname
432   \else
433     #1#2#3%
434   \fi
435   \FV@UTF@octets@after{#1#2#3}}
436 \def\FV@UTF@four@octets#1#2#3#4{%
437   \ifcsname u8:\detokenize{#1#2#3#4}\endcsname
438   \else
439     #1#2#3#4%
440   \fi
441   \FV@UTF@octets@after{#1#2#3#4}}
```

End conditional creation of UTF macros:

```
442 \fi
```

12.4 Reading and processing command arguments

`fextra` provides macros for reading and processing verbatim arguments. These are primarily intended for creating commands that take verbatim arguments but can still be used within other commands (with some limitations). These macros are used in reimplementing `fancyvrb` commands like `\Verb`. They may also be used in other packages; `minted` and `pythontex` use them for handling inline code.

All macros meant for internal use have names of the form `\FV@<Name>`, while all macros meant for use in other packages have names of the form `\FVExtra<Name>`. Only the latter are intended to have a stable interface.

12.4.1 Tokenization and lookahead

`\FVExtra@ifnextcharAny`

A version of `\@ifnextchar` that can detect any character, including catcode 10 spaces. This is an exact copy of the definition from `latex.ltx`, modified with the “`\let\reserved@d= #1%`” (note space!) trick from `amsgen`.

```
443 \long\def\FVExtra@ifnextcharAny#1#2#3{%
444   \let\reserved@d= #1%
445   \def\reserved@a{#2}%
446   \def\reserved@b{#3}%
447   \futurelet\@let@token\FVExtra@ifnchAny}
448 \def\FVExtra@ifnchAny{%
449   \ifx\@let@token\reserved@d
450     \expandafter\reserved@a
451   \else
452     \expandafter\reserved@b
453   \fi}
```

`\FVExtra@ifnextcharVArg`

This is a wrapper for `\@ifnextchar` from `latex.ltx` (`ltxdefns.dtx`) that tokenizes lookaheads under a mostly verbatim catcode regime rather than the current catcode regime. This is important when looking ahead for stars `*` and optional argument delimiters `[`, because if these are not present when looking ahead for a verbatim argument, then the first thing tokenized will be the verbatim argument’s delimiting character. Ideally, the delimiter should be tokenized under a verbatim catcode regime. This is necessary for instance if the delimiter is `\active` and `\outer`.

The catcode of the space is preserved (in the unlikely event it is `\active`) and curly braces are given their normal catcodes for the lookahead. This simplifies space handling in an untokenized context, and allows paired curly braces to be used as verbatim delimiters.

```
454 \long\def\FVExtra@ifnextcharVArg#1#2#3{%
455   \begingroup
456   \edef\FV@TmpSpaceCat{\the\catcode`}%
457   \let\do\@makeother\FVExtraDoSpecials
458   \catcode`\ =\FV@TmpSpaceCat\relax
459   \catcode`\{=1
460   \catcode`\}=2
461   \@ifnextchar#1{\endgroup#2}{\endgroup#3}}
```

`\FVExtra@ifstarVArg`

A starred command behaves differently depending on whether it is followed by an optional star or asterisk `*`. `\@ifstar` from `latex.ltx` is typically used to check for the `*`. In the process, it discards following spaces (catcode 10) and tokenizes the next non-space character under the current catcode regime. While this is fine for normal commands, it is undesirable if the next character turns out to be not a `*` but rather a verbatim argument's delimiter. This reimplementaion prevents such issues for all printable ASCII symbols via `\FVExtra@ifnextcharVArg`.

```
462 \begingroup
463 \catcode`\*=12
464 \gdef\FVExtra@ifstarVArg#1{\FVExtra@ifnextcharVArg*{\@firstoftwo{#1}}}
465 \endgroup
```

12.4.2 Reading arguments

`\FV@Read0ArgContinue`

Read a macro followed by an optional argument, then pass the optional argument to the macro for processing and to continue.

```
466 \def\FV@Read0ArgContinue#1[#2]{#1{#2}}
```

`\FVExtraRead0ArgBeforeVArg`

Read an optional argument that comes before a verbatim argument. The lookahead for the optional argument tokenizes with a verbatim catcode regime in case it encounters the delimiter for the verbatim argument rather than `[`. If the lookahead doesn't find `[`, the optional argument for `\FVExtraRead0ArgBeforeVArg` can be used to supply a default optional argument other than *empty*.

```
467 \newcommand{\FVExtraRead0ArgBeforeVArg}[2][ ]{%
468   \FVExtra@ifnextcharVArg[%
469     {\FV@Read0ArgContinue{#2}}%
470     {\FV@Read0ArgContinue{#2}{#1}}}
```

`\FVExtraRead0ArgBeforeVEnv`

Read an optional argument at the start of a verbatim environment, after the `\begin{environment}` but before the start of the next line where the verbatim content begins. Check for extraneous content after the optional argument and discard the following newline. Note that this is not needed when an environment takes a mandatory argument that follows the optional argument.

The case with only an optional argument is tricky because the default behavior of `\@ifnextchar` is to read into the next line looking for the optional argument. Setting `^^M` as `\active` prevents this. That does mean, though, that the end-of-line token will have to be read and removed later as an `\active ^^M`.

`\@ifnextchar` is used instead of `\FVExtra@ifnextcharVArg` because the latter is not needed since there is an explicit, required delimiter (`^^M`) before the actual start of verbatim content. Lookahead can never tokenize verbatim content under an incorrect catcode regime.

```
471 \newcommand{\FVExtraRead0ArgBeforeVEnv}[2][ ]{%
472   \begingroup
473   \catcode`^^M=\active
474   \@ifnextchar[%
475     {\endgroup\FVExtraRead0ArgBeforeVEnv@i{#2}}%
476     {\endgroup\FVExtraRead0ArgBeforeVEnv@i{#2}{#1}}}{
477 \def\FVExtraRead0ArgBeforeVEnv@i#1[#2]{%
478   \begingroup
```

```

479 \catcode\^^M=\active
480 \FVExtraRead0ArgBeforeVEnv@ii{#1}{#2}}
481 \begingroup
482 \catcode\^^M=\active%
483 \gdef\FVExtraRead0ArgBeforeVEnv@ii#1#2#3^^M{%
484 \endgroup%
485 \FVExtraRead0ArgBeforeVEnv@iii{#1}{#2}{#3}}%
486 \endgroup%
487 \def\FVExtraRead0ArgBeforeVEnv@iii#1#2#3{%
488 \if\relax\detokenize{#3}\relax
489 \else
490 \PackageError{fvextra}%
491 {Discarded invalid text while checking for optional argument of verbatim environment}%
492 {Discarded invalid text while checking for optional argument of verbatim environment}%
493 \fi
494 #1{#2}}

```

`\FVExtraReadVArg`

`\FVExtraReadVArgSingleLine`

Read a verbatim argument that is bounded by two identical characters or by paired curly braces. There are two variants: one reads a multi-line (but not multi-paragraph) argument, while the other restricts the argument to a single line via the `\outer ^^M` trick from `fancyvrb`. An `\outer ^^C` is used to prevent `^^C` from being part of arguments, so that it can be used later as a sentinel if retokenization is needed. `^^B` is handled in the same manner for symmetry with later usage, though technically it is not used as a sentinel so this is not strictly necessary. Alternate UTF macros, defined later, are invoked when under pdfTeX with `inputenc` using UTF-8.

The lookahead for the type of delimiting character is done under a verbatim catcode regime, except that the space catcode is preserved and curly braces are given their normal catcodes. This provides consistency with any `\FVExtra@ifnextcharVArg` or `\FVExtra@ifstarVArg` that may have been used previously, allows characters like `#` and `%` to be used as delimiters when the verbatim argument is read outside any other commands (untokenized), and allows paired curly braces to serve as delimiters. Any additional command-specific catcode modifications should only be applied to the argument after it has been read, since they do not apply to the delimiters.

Once the delimiter lookahead is complete, catcodes revert to full verbatim, and are then modified appropriately given the type of delimiter. The space and tab must be `\active` to be preserved correctly when the verbatim argument is not inside any other commands (otherwise, they collapse into single spaces).

Note that `\FVExtraReadVArg` will interpret a line break as a catcode 10 space, not as an `\active` space. Depending on usage, the argument may need to be processed with `\FVExtraDetokenizeVArg` and `\FVExtraRetokenizeVArg` to fix this.

```

495 \def\FVExtraReadVArg#1{%
496 \begingroup
497 \ifFV@pdfTeXinputenc
498 \ifdefstring{\inputencodingname}{utf8}%
499 {\let\FV@ReadVArg@Char\FV@ReadVArg@Char@UTF}%
500 {}%
501 \fi

```

```

502 \edef\FV@TmpSpaceCat{\the\catcode`}%
503 \let\do\@makeother\FVExtraDoSpecials
504 \catcode`\^^B=\active
505 \FV@OuterDefSTXEmpty
506 \catcode`\^^C=\active
507 \FV@OuterDefETXEmpty
508 \begingroup
509 \catcode`\ =\FV@TmpSpaceCat\relax
510 \catcode`\{=1
511 \catcode`\}=2
512 \@ifnextchar\bgroup
513 {\endgroup
514 \catcode`\{=1
515 \catcode`\}=2
516 \catcode`\ =\active
517 \catcode`\^^I=\active
518 \FV@ReadVArg@Group{#1}}%
519 {\endgroup
520 \catcode`\ =\active
521 \catcode`\^^I=\active
522 \FV@ReadVArg@Char{#1}}}
523 \def\FVExtraReadVArgSingleLine#1{%
524 \begingroup
525 \ifFV@pdfTeXinputenc
526 \ifdefstring{\inputencodingname}{utf8}%
527 {\let\FV@ReadVArg@Char\FV@ReadVArg@Char@UTF}%
528 {}%
529 \fi
530 \edef\FV@TmpSpaceCat{\the\catcode`}%
531 \let\do\@makeother\FVExtraDoSpecials
532 \catcode`\^^B=\active
533 \FV@OuterDefSTXEmpty
534 \catcode`\^^C=\active
535 \FV@OuterDefETXEmpty
536 \catcode`\^^M=\active
537 \FV@OuterDefEOLEmpty
538 \begingroup
539 \catcode`\ =\FV@TmpSpaceCat\relax
540 \catcode`\{=1
541 \catcode`\}=2
542 \@ifnextchar\bgroup
543 {\endgroup
544 \catcode`\{=1
545 \catcode`\}=2
546 \catcode`\ =\active
547 \catcode`\^^I=\active
548 \FV@ReadVArg@Group{#1}}%
549 {\endgroup
550 \catcode`\ =\active
551 \catcode`\^^I=\active
552 \FV@ReadVArg@Char{#1}}}

```

`\FV@ReadVArg@Group`

The argument is read under the verbatim catcode regime already in place from `\FVExtraReadVArg`. The `\endgroup` returns to prior catcodes. Any command-

specific catcodes can be applied later via `\scantokens`. Using them here in reading the argument would have no effect as far as later processing with `\scantokens` is concerned, unless the argument were read outside any other commands and additional characters were given catcodes 1 or 2 (like the curly braces). That scenario is not allowed because it makes reading the argument overly dependent on the argument content. (Technically, reading the argument is already dependent on the argument content in the sense that the argument cannot contain unescaped unpaired curly braces, given that it is delimited by curly braces.)

```
553 \def\FV@ReadVArg@Group#1#2{%
554   \endgroup
555   #1{#2}}
```

`\FV@ReadVArg@Char`

The delimiting character is read under the verbatim catcode regime in place from `\FVExtraReadVArg`. If the command is not inside a normal command, then this means the delimiting character will typically have catcode 12 and that characters like `#` and `%` can be used as delimiters; otherwise, the delimiter may have any catcode that is possible for a single character captured by a macro. If the argument is read inside another command (already tokenized), then it is possible for the delimiter to be a control sequence rather than a single character. An error is raised in this case. The `\endgroup` in `\FV@ReadVArg@Char@i` returns to prior catcodes after the argument is captured.

It would be possible to read the argument using any command-specific catcode settings, but that would result in different behavior depending on whether the argument is already tokenized, and would make reading the argument overly dependent on the argument content.

```
556 \def\FV@ReadVArg@Char#1#2{%
557   \expandafter\expandafter\expandafter
558   \if\expandafter\expandafter\expandafter\relax\expandafter\@gobble\detokenize{#2}\relax
559   \expandafter\@gobble
560   \else
561     \expandafter\@firstofone
562   \fi
563   {\PackageError{fvextra}%
564     {Verbatim delimiters must be single characters, not commands}%
565     {Try a different delimiter}}%
566   \def\FV@ReadVArg@Char@i##1##2#2{%
567     \endgroup
568     ##1{##2}}%
569   \FV@ReadVArg@Char@i{#1}}%
```

Alternate implementation for pdfTeX with inputenc using UTF-8

Start conditional creation of macros:

```
570 \ifFV@pdfTeXinputenc
```

`\FV@ReadVArg@Char@UTF`

This is a variant of `\FV@ReadVArg@Char` that allows non-ASCII codepoints as delimiters under the pdfTeX engine with `inputenc` using UTF-8. Under pdfTeX, non-ASCII codepoints must be handled as a sequence of bytes rather than as a single entity. `\FV@ReadVArg@Char` is automatically `\let` to this version when

appropriate. This uses the `\FV@U8:<byte>` macros for working with inputenc's UTF-8.

```

571 \def\FV@ReadVArg@Char@UTF#1#2{%
572   \expandafter\expandafter\expandafter
573   \if\expandafter\expandafter\expandafter\relax\expandafter\@gobble\detokenize{#2}\relax
574   \expandafter\@gobble
575   \else
576   \expandafter\@firstofone
577   \fi
578   {\PackageError{fvextra}%
579    {Verbatim delimiters must be single characters, not commands}%
580    {Try a different delimiter}}%
581   \ifcsname FV@U8:\detokenize{#2}\endcsname
582   \expandafter\@firstoftwo
583   \else
584   \expandafter\@secondoftwo
585   \fi
586   {\def\FV@UTF@octets@after##1{\FV@ReadVArg@Char@UTF@i{#1}{##1}}%
587    \csname FV@U8:\detokenize{#2}\endcsname#2}%
588   {\FV@ReadVArg@Char@UTF@i{#1}{#2}}}

```

`\FV@ReadVArg@Char@UTF@i`

```

589 \def\FV@ReadVArg@Char@UTF@i#1#2{%
590   \def\FV@ReadVArg@Char@i##1##2#2{%
591     \endgroup
592     ##1{##2}}%
593   \FV@ReadVArg@Char@i{#1}}%

```

End conditional creation of UTF macros:

```
594 \fi
```

`vargsingleline`

This determines whether `\Verb` and `\SaveVerb` use `\FVExtraReadVArg` or `\FVExtraReadVArgSingleLine` to read their arguments. It has no effect on `\EscVerb`, since that does not use special tokenization.

```

595 \newbool{FV@vargsingleline}
596 \define@booleankey{FV}{vargsingleline}%
597 {\booltrue{FV@vargsingleline}}
598 {\boolfalse{FV@vargsingleline}}
599 \fvset{vargsingleline=false}

```

12.4.3 Reading and protecting arguments in expansion-only contexts

The objective here is to make possible commands that can function correctly after being in expansion-only contexts like `\edef`. The general strategy is to allow commands to be defined like this:

```
\def\cmd{\FVExtraRobustCommand\robustcmd\reader}
```

`\robustcmd` is the actual command, including argument reading and processing, and is `\protected`. `\reader` is an expandable macro that reads all of `\robustcmd`'s arguments, then wraps them in `\FVExtraAlwaysUnexpanded`. When `\FVExtraAlwaysUnexpanded{<args>}` is expanded, the result is always `\FVExtraAlwaysUnexpanded{<args>}`. `\FVExtraRobustCommand` is `\protected` and manages everything in a context-sensitive manner.

- In a normal context, `\FVExtraRobustCommand` reads two arguments, which will be `\robustcmd` and `\reader`. It detects that `\reader` has not expanded to `\FVExtraAlwaysUnexpanded{<args>}`, so it discards `\reader` and reinserts `\robustcmd` so that it can operate normally.
- In an expansion-only context, neither `\FVExtraRobustCommand` nor `\robustcmd` will expand, because both are `\protected`. `\reader` will read `\robustcmd`'s arguments and protect them with `\FVExtraAlwaysUnexpanded`. When this is used later in a normal context, `\FVExtraRobustCommand` reads two arguments, which will be `\robustcmd` and `\FVExtraAlwaysUnexpanded`. It detects that `\reader` did expand, so it discards `\FVExtraAlwaysUnexpanded` and reads its argument to discard the wrapping braces. Then it reinserts `\robustcmd<args>` so that everything can proceed as if expansion had not occurred.

`\FVExtrapdfstringdef`

`\FVExtrapdfstringdefDisableCommands`

Conditionally allow alternate definitions for PDF bookmarks when `hyperref` is in use. This is helpful for working with `\protected` or otherwise unexpandable commands.

```
600 \def\FVExtrapdfstringdef#1#2{%
601   \AfterPreamble{%
602     \ifcsname pdfstringdef\endcsname
603     \ifx\pdfstringdef\relax
604     \else
605     \pdfstringdef#1{#2}%
606     \fi\fi}}
607 \def\FVExtrapdfstringdefDisableCommands#1{%
608   \AfterPreamble{%
609     \ifcsname pdfstringdefDisableCommands\endcsname
610     \ifx\pdfstringdefDisableCommands\relax
611     \else
612     \pdfstringdefDisableCommands{#1}%
613     \fi\fi}}
```

`\FVExtraAlwaysUnexpanded`

Always expands to itself, thanks to `\unexpanded`.

```
614 \long\def\FVExtraAlwaysUnexpanded#1{%
615   \unexpanded{\FVExtraAlwaysUnexpanded{#1}}}
616 \FVExtrapdfstringdefDisableCommands{%
617   \long\def\FVExtraAlwaysUnexpanded#1{#1}}
```

`FVExtraRobustCommandExpanded`

Boolean to track whether expansion occurred. Set in `\FVExtraRobustCommand`. Useful in creating commands that behave differently depending on whether expansion occurred.

```
618 \newbool{FVExtraRobustCommandExpanded}
```

`\FVExtraRobustCommand`

```
619 \protected\def\FVExtraRobustCommand#1#2{%
620   \ifx#2\FVExtraAlwaysUnexpanded
621   \expandafter\@firstoftwo
622   \else
623   \expandafter\@secondoftwo
```

```

624 \fi
625 {\booltrue{FVExtraRobustCommandExpanded}\FV@RobustCommand@i{#1}}%
626 {\boolfalse{FVExtraRobustCommandExpanded}#1}}
627 \FVextrapdfstringdefDisableCommands{%
628 \def\FVExtraRobustCommand{}}

```

\FV@RobustCommand@i

#2 will be the argument of \FVExtraAlwaysUnexpanded. Reading this strips the braces. At the beginning of #2 will be the reader macro, which must be \@gobble'd.

```
629 \def\FV@RobustCommand@i#1#2{\expandafter#1\@gobble#2}
```

\FVExtraUnexpandedReadStar0ArgMArg

Read the arguments for a command that may be starred, may have an optional argument, and has a single brace-delimited mandatory argument. Then protect them with \FVExtraAlwaysUnexpanded. The reader macro is itself maintained in the protected result, so that it can be redefined to provide a simple default value for hyperref.

Note the argument signature #1#{. This reads everything up to, but not including, the next brace group.

```
630 \def\FVExtraUnexpandedReadStar0ArgMArg#1#{%
631 \FV@UnexpandedReadStar0ArgMArg@i{#1}}
```

\FV@UnexpandedReadStar0ArgMArg@i

```

632 \def\FV@UnexpandedReadStar0ArgMArg@i#1#2{%
633 \FVExtraAlwaysUnexpanded{\FVExtraUnexpandedReadStar0ArgMArg#1{#2}}}
634 \FVextrapdfstringdefDisableCommands{%
635 \makeatletter
636 \def\FV@UnexpandedReadStar0ArgMArg@i#1#2{#2}%
637 \makeatother}

```

\FVExtraUseVerbUnexpandedReadStar0ArgMArg

This is a variant of \FVExtraUnexpandedReadStar0ArgMArg customized for \UseVerb. It would be tempting to use \pdfstringdef to define a PDF string based on the final tokenization in \UseVerb, rather than applying \FVExtraPDFStringVerbatimDetokenize to the original raw (read) tokenization. Unfortunately, \pdfstringdef apparently can't handle catcode 12 \ and %. Since the final tokenization could contain arbitrary catcodes, that approach might fail even if the \ and % issue were resolved. It may be worth considering more sophisticated approaches in the future.

```
638 \def\FVExtraUseVerbUnexpandedReadStar0ArgMArg#1#{%
639 \FV@UseVerbUnexpandedReadStar0ArgMArg@i{#1}}
```

\FV@UseVerbUnexpandedReadStar0ArgMArg@i

```

640 \def\FV@UseVerbUnexpandedReadStar0ArgMArg@i#1#2{%
641 \FVExtraAlwaysUnexpanded{\FVExtraUseVerbUnexpandedReadStar0ArgMArg#1{#2}}}
642 \FVextrapdfstringdefDisableCommands{%
643 \makeatletter
644 \def\FV@UseVerbUnexpandedReadStar0ArgMArg@i#1#2{%
645 \ifcsname FV@SVRaw@#2\endcsname
646 \expandafter\expandafter\expandafter\FVExtraPDFStringVerbatimDetokenize
647 \expandafter\expandafter\expandafter{\csname FV@SVRaw@#2\endcsname}%
648 \fi}%
649 \makeatother}

```

`\FVExtraUnexpandedReadStar0ArgBVarG`

Same as `\FVExtraUnexpandedReadStar0ArgMArg`, except `BVarG`, brace-delimited verbatim argument.

```
650 \def\FVExtraUnexpandedReadStar0ArgBVarG#1#{%
651   \FV@UnexpandedReadStar0ArgBVarG@i{#1}}
```

`\FV@UnexpandedReadStar0ArgBVarG@i`

```
652 \def\FV@UnexpandedReadStar0ArgBVarG@i#1#2{%
653   \FVExtraAlwaysUnexpanded{\FVExtraUnexpandedReadStar0ArgBVarG#1{#2}}}
654 \FVextrapdfstringdefDisableCommands{%
655   \makeatletter
656   \def\FV@UnexpandedReadStar0ArgBVarG@i#1#2{%
657     \FVExtraPDFStringVerbatimDetokenize{#2}}%
658   \makeatother}
```

`\FVExtraUnexpandedReadStar0ArgBEscVArg`

Same as `\FVExtraUnexpandedReadStar0ArgMArg`, except `BEscVArg`, brace-delimited escaped verbatim argument.

```
659 \def\FVExtraUnexpandedReadStar0ArgBEscVArg#1#{%
660   \FV@UnexpandedReadStar0ArgBEscVArg@i{#1}}
```

`\FV@UnexpandedReadStar0ArgBEscVArg@i`

```
661 \def\FV@UnexpandedReadStar0ArgBEscVArg@i#1#2{%
662   \FVExtraAlwaysUnexpanded{\FVExtraUnexpandedReadStar0ArgBEscVArg#1{#2}}}
663 \FVextrapdfstringdefDisableCommands{%
664   \makeatletter
665   \def\FV@UnexpandedReadStar0ArgBEscVArg@i#1#2{%
666     \FVExtraPDFStringEscapedVerbatimDetokenize{#2}}%
667   \makeatother}
```

`\FVExtraUnexpandedReadStar0ArgMArgBVarG`

Read arguments for a command that has a mandatory argument before a verbatim argument, such as `minted`'s `\mintinline`.

```
668 \def\FVExtraUnexpandedReadStar0ArgMArgBVarG#1#{%
669   \FV@UnexpandedReadStar0ArgMArgBVarG@i{#1}}
670 \def\FV@UnexpandedReadStar0ArgMArgBVarG@i#1#2{%
671   \FV@UnexpandedReadStar0ArgMArgBVarG@ii{#1}{#2}}
672 \def\FV@UnexpandedReadStar0ArgMArgBVarG@ii#1#2#3#{%
673   \FV@UnexpandedReadStar0ArgMArgBVarG@iii{#1}{#2}{#3}}
674 \def\FV@UnexpandedReadStar0ArgMArgBVarG@iii#1#2#3#4{%
675   \FVExtraAlwaysUnexpanded{\FVExtraUnexpandedReadStar0ArgMArgBVarG#1{#2}{#3}{#4}}}
676 \FVextrapdfstringdefDisableCommands{%
677   \makeatletter
678   \def\FV@UnexpandedReadStar0ArgMArgBVarG@iii#1#2#3#4{%
679     \FVExtraPDFStringVerbatimDetokenize{#4}}%
680   \makeatother}
```

12.4.4 Converting detokenized tokens into PDF strings

At times it will be convenient to convert detokenized tokens into PDF strings, such as bookmarks. Define macros to escape such detokenized content so that it is in a suitable form.

`\FVExtraPDFStringEscapeChar`

Note that this does not apply any special treatment to spaces. If there are multiple adjacent spaces, then the octal escape `\040` is needed to prevent them from being merged. In the detokenization macros where `\FVExtraPDFStringEscapeChar` is currently used, spaces are processed separately without `\FVExtraPDFStringEscapeChar`, and literal spaces or `\040` are inserted in a context-dependent manner.

```

681 \def\FVExtraPDFStringEscapeChar#1{%
682   \ifcsname FV@PDFStringEscapeChar@#1\endcsname
683     \csname FV@PDFStringEscapeChar@#1\endcsname
684   \else
685     #1%
686   \fi}
687 \begingroup
688 \catcode`\&=14
689 \catcode`\%=12&
690 \catcode`\(=12&
691 \catcode`\)=12&
692 \catcode`\^^J=12&
693 \catcode`\^^M=12&
694 \catcode`\^^I=12&
695 \catcode`\^^H=12&
696 \catcode`\^^L=12&
697 \catcode`\!=0\relax&
698 !catcode`\=12!relax&
699 !expandafter!gdef!csname FV@PDFStringEscapeChar@!\!endcsname{\&}&
700 !expandafter!gdef!csname FV@PDFStringEscapeChar@%!\!endcsname{\%}&
701 !expandafter!gdef!csname FV@PDFStringEscapeChar@(!\!endcsname{\(!}&
702 !expandafter!gdef!csname FV@PDFStringEscapeChar@)\!endcsname{\)\}&
703 !expandafter!gdef!csname FV@PDFStringEscapeChar@^^J!\!endcsname{\n}&
704 !expandafter!gdef!csname FV@PDFStringEscapeChar@^^M!\!endcsname{\r}&
705 !expandafter!gdef!csname FV@PDFStringEscapeChar@^^I!\!endcsname{\t}&
706 !expandafter!gdef!csname FV@PDFStringEscapeChar@^^H!\!endcsname{\b}&
707 !expandafter!gdef!csname FV@PDFStringEscapeChar@^^L!\!endcsname{\f}&
708 !catcode`\!=0!relax&
709 \endgroup

```

`\FVExtraPDFStringEscapeChars`

```

710 \def\FVExtraPDFStringEscapeChars#1{%
711   \FV@PDFStringEscapeChars#1\FV@Sentinel}

```

`\FV@PDFStringEscapeChars`

```

712 \def\FV@PDFStringEscapeChars#1{%
713   \ifx#1\FV@Sentinel
714   \else
715     \FVExtraPDFStringEscapeChar{#1}%
716     \expandafter\FV@PDFStringEscapeChars
717   \fi}%

```

12.4.5 Detokenizing verbatim arguments

Ensure correct catcodes for this subsection (note `<` and `>` for `\FV@<Sentinel>`):

```

718 \begingroup
719 \catcode`\ =10
720 \catcode`\a=11

```

```

721 \catcode`\<=11
722 \catcode`\>=11
723 \catcode`\^^C=\active

```

Detokenize as if the original source were tokenized verbatim

`\FVExtraVerbatimDetokenize`

Detokenize tokens as if their original source was tokenized verbatim, rather than under any other catcode regime that may actually have been in place. This recovers the original source when tokenization was verbatim. Otherwise, it recovers the closest approximation of the source that is possible given information loss during tokenization (for example, adjacent space characters may be merged into a single space token). This is useful in constructing nearly verbatim commands that can be used inside other commands. It functions in an expansion-only context (“fully expandable,” works in `\edef`).

This yields spaces with catcode 12, *not* spaces with catcode 10 like `\detokenize`. Spaces with catcode 10 require special handling when being read by macros, so detokenizing them to catcode 10 makes further processing difficult. Spaces with catcode 12 may be used just like any other catcode 12 token.

This requires that the `\active` end-of-text (ETX) `^^C` (U+0003) not be defined as `\outer`, since `^^C` is used as a sentinel. Usually, it should not be defined at all, or defined to an error sequence. When in doubt, it may be worth explicitly defining `^^C` before using `\FVExtraVerbatimDetokenize`:

```

\begingroup
\catcode`\^^C=\active
\def^^C{}
...
\FVExtraVerbatimDetokenize{...}
...
\endgroup

```

`\detokenize` inserts a space after each control word (control sequence with a name composed of catcode 11 tokens, ASCII letters [a-zA-Z]). For example,

```
\detokenize{\macroA\macroB{}}\csname name\endcsname123}
```

yields

```
\macroA \macroB {} \csname name\endcsname 123
```

That is the correct behavior when detokenizing text that will later be retokenized for normal use. The space prevents the control word from accidentally merging with any letters that follow it immediately, and will be gobbled by the macro when retokenized. However, the inserted spaces are unwanted in the current context, because

```
\FVExtraVerbatimDetokenize{\macroA\macroB{}}\csname name\endcsname123}
```

should yield

```
\macroA\macroB{ }\csname_name\endcsname123
```

Note that the space is visible since it is catcode 12.

Thus, `\FVExtraVerbatimDetokenize` is essentially a context-sensitive wrapper around `\detokenize` that removes extraneous space introduced by `\detokenize`. It iterates through the tokens, detokenizing them individually and then removing any trailing space inserted by `\detokenize`.

```
724 \gdef\FVExtraVerbatimDetokenize#1{%  
725   \FV@VDetok@Scan{ }#1^^C \FV@<Sentinel>}
```

`\FV@VDetok@Scan`

This scans through a token sequence while performing two tasks:

1. Replace all catcode 10 spaces with catcode 12 spaces.
2. Insert macros that will process groups, after which they will insert yet other macros to process individual tokens.

Usage must *always* have the form

```
\FV@VDetok@Scan{ }<tokens>^^C_\FV@<Sentinel>
```

where `^^C` is `\active`, the catcode 10 space after `^^C` is mandatory, and `\FV@<Sentinel>` is a *single*, undefined control word (this is accomplished via catcodes).

- `\FV@VDetok@Scan` searches for spaces to replace. After any spaces in `<tokens>` have been handled, the space in `^^C_\FV@<Sentinel>` triggers space processing. When `\FV@VDetok@Scan` detects the sentinel macro `\FV@<Sentinel>`, scanning stops.
- The `{ }` protects the beginning of `<tokens>`, so that if `<tokens>` is a group, its braces won't be gobbled. Later, the inserted `{ }` must be stripped so that it does not become part the processed `<tokens>`.
- `^^C` is a convenient separator between `<tokens>` and the rest of the sentinel sequence.
 - Since `\FV@VDetok@Scan` has delimited arguments, a leading catcode 10 space in `<tokens>` will be preserved automatically. Preserving a trailing catcode 10 space is much easier if it is immediately adjacent to a non-space character in the sentinel sequence; two adjacent catcode 10 spaces would be difficult to handle with macro pattern matching. However, the sentinel sequence must contain a catcode 10 space, so the sentinel sequence must contain at least 3 tokens.
 - Since `^^C` is not a control word, it does not gobble following spaces. That makes it much easier to assemble macro arguments that contain a catcode 10 space. This is useful because the sentinel sequence `^^C_\FV@<Sentinel>` may have to be inserted into processing multiple times (for example, in recursive handling of groups).
 - `\FVExtraReadVArg` defines `^^C` as `\outer`, so any verbatim argument read by it is guaranteed not to contain `^^C`. This is in contrast to `\active` ASCII symbols and to two-character sequences `<backslash><symbol>` that should be expected in arbitrary verbatim content. It is a safe sentinel from that perspective.

- A search of a complete TeX Live 2018 installation revealed no other uses of `^^C` that would clash (thanks, `ripgrep`!). As a control character, it should not be in common use except as a sentinel or for similar special purposes.

If `<tokens>` is empty or contains no spaces, then `#1` will contain `{<tokens>^^C` and `#2` will be empty. Otherwise, `#1` will contain `{<tokens_to_space>` and `#2` will contain `<tokens_after_space>^^C`.

This uses the `\if\relax\detokenize{<argument>}\relax` approach to check for an empty argument. If `#2` is empty, then the space that was just removed by `\FV@VDetok@Scan` reading its arguments was the space in the sentinel sequence, in which case scanning should end. `#1` is passed on raw so that `\FV@VDetok@ScanEnd` can strip the `^^C` from the end, which is the only remaining token from the sentinel sequence `^^C\FV@<Sentinel>`. Otherwise, if `#2` is not empty, continue. In that case, the braces in `{#1}{#2}` ensure arguments remain intact.

Note that `\FV@<Sentinel>` is removed during each space search, and thus must be reinserted in `\FV@VDetok@ScanCont`. It would be possible to use the macro signature `#1 #2` instead of `#1 #2\FV@<Sentinel>`, and then do an `\ifx` test on `#2` for `\FV@<Sentinel>`. However, that is problematic, because `#2` may contain an arbitrary sequence of arbitrary tokens, so it cannot be used safely without `\detokenize`.

```
726 \gdef\FV@VDetok@Scan#1 #2\FV@<Sentinel>{%
727   \if\relax\detokenize{#2}\relax
728     \expandafter\@firstoftwo
729   \else
730     \expandafter\@secondoftwo
731   \fi
732   {\FV@VDetok@ScanEnd#1}%
733   {\FV@VDetok@ScanCont{#1}{#2}}}
```

`\FV@VDetok@ScanEnd`

This removes the `^^C` from the sentinel sequence `^^C\FV@<Sentinel>`, so the sentinel sequence is now completely gone. If `#1` is empty, there is nothing to do (`#1` being empty means that `#1` consumed the `{}` that was inserted to protect anything following, because there was nothing after it). Otherwise, `\@gobble` the inserted `{}` before starting a different scan to deal with groups. The group scanner `\FV@VDetok@ScanGroup` has its own sentinel sequence `{\FV@<Sentinel>}`.

```
734 \gdef\FV@VDetok@ScanEnd#1^^C{%
735   \if\relax\detokenize{#1}\relax
736     \expandafter\@gobble
737   \else
738     \expandafter\@firstofone
739   \fi
740   {\expandafter\FV@VDetok@ScanGroup\@gobble#1{\FV@<Sentinel>}}}
```

`\FV@VDetok@ScanCont`

Continue scanning after removing a space in `\FV@VDetok@Scan`.

`#1` is everything before the space. If `#1` is empty, there is nothing to do related to it; `#1` simply consumed an inserted `{}` that preceded nothing (that would be a leading space). Otherwise, start a different scan on `#1` to deal with groups. A non-empty `#1` will start with the `{}` that was inserted to protect groups, hence the `\@gobble` before group scanning.

Then insert a literal catcode 12 space to account for the space removed in `\FV@VDetok@Scan`. Note the catcode, and thus the lack of indentation and the % to avoid unwanted catcode 12 spaces.

#2 is everything after the space, ending with `^^C_` from the sentinel sequence `^^C_\FV@<Sentinel>`. This needs continued scanning to deal with spaces, with `{}` inserted in front to protect a leading group and `\FV@<Sentinel>` after to complete the sentinel sequence.

```

741 \begingroup
742 \catcode`\ =12%
743 \gdef\FV@VDetok@ScanCont#1#2{%
744 \if\relax\detokenize{#1}\relax%
745 \expandafter\@gobble%
746 \else%
747 \expandafter\@firstofone%
748 \fi%
749 {\expandafter\FV@VDetok@ScanGroup\@gobble#1{\FV@<Sentinel>}}%
750 %<-catcode 12 space
751 \FV@VDetok@Scan{}#2\FV@<Sentinel>}%
752 \endgroup

```

`\FV@VDetok@ScanGroup`

The macro argument #1# reads up to the next group. When this macro is invoked, the sentinel sequence `{\FV@<Sentinel>}` is inserted, so there is guaranteed to be at least one group.

Everything in #1 contains no spaces and no groups, and thus is ready for token scanning, with the sentinel `\FV@Sentinel`. Note that `\FV@Sentinel`, which is defined as `\def\FV@Sentinel{\FV@<Sentinel>}`, is used here, *not* `\FV@<Sentinel>`. `\FV@<Sentinel>` is not defined and is thus unsuitable for `\ifx` comparisons with tokens that may have been tokenized under an incorrect catcode regime and thus are undefined. `\FV@Sentinel` is defined, and its definition is resistant against accidental collisions.

```

753 \gdef\FV@VDetok@ScanGroup#1#{%
754 \FV@VDetok@ScanToken#1\FV@Sentinel
755 \FV@VDetok@ScanGroup@i}

```

`\FV@VDetok@ScanGroup@i`

The braces from the group are stripped during reading #1. Proceed based on whether the group is empty. If the group is not empty, `{}` must be inserted to protect #1 in case it is a group, and the new sentinel sequence `\FV@<Sentinel>^^C` is added for the group contents. `\FV@<Sentinel>` cannot be used as a sentinel for the group contents, because if this is the sentinel group `{\FV@<Sentinel>}`, then #1 is `\FV@<Sentinel>`.

```

756 \gdef\FV@VDetok@ScanGroup@i#1{%
757 \if\relax\detokenize{#1}\relax
758 \expandafter\@firstoftwo
759 \else
760 \expandafter\@secondoftwo
761 \fi
762 {\FV@VDetok@ScanEmptyGroup}%
763 {\FV@VDetok@ScanGroup@ii{#1\FV@<Sentinel>^^C}}

```

`\FV@VDetok@ScanEmptyGroup`

Insert `{}` to handle the empty group, then continue group scanning.

```

764 \begingroup
765 \catcode`\(=1
766 \catcode`\)=2
767 \catcode`\{=12
768 \catcode`\}=12
769 \gdef\FV@VDetok@ScanEmptyGroup({}\FV@VDetok@ScanGroup)
770 \endgroup

```

`\FV@VDetok@ScanGroup@ii`

The group is not empty, so determine whether it contains `\FV@<Sentinel>` and thus is the sentinel group. The group contents are followed by the sentinel sequence `\FV@<Sentinel>^^C` inserted in `\FV@VDetok@ScanGroup@i`. This means that if `#2` is empty, the group did not contain `\FV@<Sentinel>` and thus is not the sentinel group. Otherwise, `#2` will be `\FV@<Sentinel>`.

If this is not the sentinel group, then the group contents must be scanned, with surrounding literal braces inserted. `#1` already contains an inserted leading `{}` to protect groups; see `\FV@VDetok@ScanGroup@i`. A sentinel sequence `^^C\FV@<Sentinel>` is needed, though. Then group scanning must continue.

```

771 \begingroup
772 \catcode`\(=1
773 \catcode`\)=2
774 \catcode`\{=12
775 \catcode`\}=12
776 \gdef\FV@VDetok@ScanGroup@ii#1\FV@<Sentinel>#2^^C(%)
777 \if\relax\detokenize(#2)\relax
778 \expandafter\@firstofone
779 \else
780 \expandafter\@gobble
781 \fi
782 ({\FV@VDetok@Scan#1^^C \FV@<Sentinel>}\FV@VDetok@ScanGroup)
783 \endgroup

```

`\FV@VDetok@ScanToken`

Scan individual tokens. At this point, all spaces and groups have been handled, so this will only ever encounter individual tokens that can be iterated with a `#1` argument. The sentinel for token scanning is `\FV@Sentinel`. This is the appropriate sentinel because `\ifx` comparisons are now safe (individual tokens) and `\FV@Sentinel` is defined. Processing individual detokenized tokens requires the same sentinel sequence as handling spaces, since it can produce them.

```

784 \gdef\FV@VDetok@ScanToken#1{%
785 \ifx\FV@Sentinel#1%
786 \expandafter\@gobble
787 \else
788 \expandafter\@firstofone
789 \fi
790 {\expandafter\FV@VDetok@ScanToken@i\detokenize{#1}^^C \FV@<Sentinel>}}

```

`\FV@VDetok@ScanToken@i`

If `#2` is empty, then there are no spaces in the detokenized token, so it is either an `\active` character other than the space, or a two-character sequence of the form `<backslash><symbol>` where the second character is not a space. Thus, `#1` contains `<detokenized>^^C`. Otherwise, `#1` contains `<detokenized_without_space>`, and `#2` may be discarded since it contains `^^C\FV@<Sentinel>`. (If the detokenized token

contains a space, it is always at the end.)

```
791 \gdef\FV@VDetok@ScanToken@i#1 #2\FV@<Sentinel>{%  
792 \if\relax\detokenize{#2}\relax  
793 \expandafter\@firstoftwo  
794 \else  
795 \expandafter\@secondoftwo  
796 \fi  
797 {\FV@VDetok@ScanTokenNoSpace#1}%  
798 {\FV@VDetok@ScanTokenWithSpace{#1}}}
```

`\FV@VDetok@ScanTokenNoSpace`

Strip `^^C` sentinel in reading, then insert character(s) and continue scanning.

```
799 \gdef\FV@VDetok@ScanTokenNoSpace#1^^C{#1\FV@VDetok@ScanToken}
```

`\FV@VDetok@ScanTokenWithSpace`

Handle a token that when detokenized produces a space. If there is nothing left once the space is removed, this is the `\active` space. Otherwise, process further.

```
800 \gdef\FV@VDetok@ScanTokenWithSpace#1{%  
801 \if\relax\detokenize{#1}\relax  
802 \expandafter\@firstoftwo  
803 \else  
804 \expandafter\@secondoftwo  
805 \fi  
806 {\FV@VDetok@ScanTokenActiveSpace}%  
807 {\FV@VDetok@ScanTokenWithSpace@i#1\FV@<Sentinel>}}
```

`\FV@VDetok@ScanTokenActiveSpace`

```
808 \begingroup  
809 \catcode`\ =12%  
810 \gdef\FV@VDetok@ScanTokenActiveSpace{ \FV@VDetok@ScanToken}%  
811 \endgroup
```

`\FV@VDetok@ScanTokenWithSpace@i`

If there is only one character left once the space is removed, this is the escaped space `\.`. Otherwise, this is a command word that needs further processing.

```
812 \gdef\FV@VDetok@ScanTokenWithSpace@i#1#2\FV@<Sentinel>{%  
813 \if\relax\detokenize{#2}\relax  
814 \expandafter\@firstoftwo  
815 \else  
816 \expandafter\@secondoftwo  
817 \fi  
818 {\FV@VDetok@ScanTokenEscSpace{#1}}%  
819 {\FV@VDetok@ScanTokenCW{#1#2}}}
```

`\FV@VDetok@ScanTokenEscSpace`

```
820 \begingroup  
821 \catcode`\ =12%  
822 \gdef\FV@VDetok@ScanTokenEscSpace#1{#1 \FV@VDetok@ScanToken}%  
823 \endgroup
```

`\FV@VDetok@ScanTokenCW`

Process control words in a context-sensitive manner by looking ahead to the next token (`#2`). The lookahead must be reinserted into processing, hence the `\FV@VDetok@ScanToken#2`.

A control word will detokenize to a sequence of characters followed by a space. If the following token has catcode 11, then this space represents one or more space characters that must have been present in the original source, because otherwise the catcode 11 token would have become part of the control word's name. If the following token has another catcode, then it is impossible to determine whether a space was present, so assume that one was not.

```

824 \begingroup
825 \catcode\ =12%
826 \gdef\FV@VDetok@ScanTokenCW#1#2{%
827 \ifcat\noexpand#2a%
828 \expandafter\@firstoftwo%
829 \else%
830 \expandafter\@secondoftwo%
831 \fi%
832 {#1 \FV@VDetok@ScanToken#2}%
833 {#1\FV@VDetok@ScanToken#2}}%
834 \endgroup

```

Detokenize as if the original source were tokenized verbatim, then convert to PDF string

`\FVExtraPDFStringVerbatimDetokenize`

This is identical to `\FVExtraVerbatimDetokenize`, except that the output is converted to a valid PDF string. Some spaces are represented with the octal escape `\040` to prevent adjacent spaces from being merged.

```

835 \gdef\FVExtraPDFStringVerbatimDetokenize#1{%
836 \FV@PDFStrVDetok@Scan{ }#1^C \FV@<Sentinel>}

```

`\FV@PDFStrVDetok@Scan`

```

837 \gdef\FV@PDFStrVDetok@Scan#1 #2\FV@<Sentinel>{%
838 \if\relax\detokenize{#2}\relax
839 \expandafter\@firstoftwo
840 \else
841 \expandafter\@secondoftwo
842 \fi
843 {\FV@PDFStrVDetok@ScanEnd#1}%
844 {\FV@PDFStrVDetok@ScanCont{#1}{#2}}}

```

`\FV@PDFStrVDetok@ScanEnd`

```

845 \gdef\FV@PDFStrVDetok@ScanEnd#1^C{%
846 \if\relax\detokenize{#1}\relax
847 \expandafter\@gobble
848 \else
849 \expandafter\@firstofone
850 \fi
851 {\expandafter\FV@PDFStrVDetok@ScanGroup\@gobble#1{\FV@<Sentinel>}}}

```

`\FV@PDFStrVDetok@ScanCont`

```

852 \begingroup
853 \catcode\ =12%
854 \gdef\FV@PDFStrVDetok@ScanCont#1#2{%
855 \if\relax\detokenize{#1}\relax%
856 \expandafter\@gobble%

```

```

857 \else%
858 \expandafter\@firstofone%
859 \fi%
860 {\expandafter\FV@PDFStrVDetok@ScanGroup\@gobble#1{\FV@<Sentinel>}}%
861 %<-catcode 12 space
862 \FV@PDFStrVDetok@Scan{ }#2\FV@<Sentinel>}%
863 \endgroup

\FV@PDFStrVDetok@ScanGroup
864 \gdef\FV@PDFStrVDetok@ScanGroup#1#{%
865 \FV@PDFStrVDetok@ScanToken#1\FV@Sentinel
866 \FV@PDFStrVDetok@ScanGroup@i}

\FV@PDFStrVDetok@ScanGroup@i
867 \gdef\FV@PDFStrVDetok@ScanGroup@i#1{%
868 \if\relax\detokenize{#1}\relax
869 \expandafter\@firstoftwo
870 \else
871 \expandafter\@secondoftwo
872 \fi
873 {\FV@PDFStrVDetok@ScanEmptyGroup}%
874 {\FV@PDFStrVDetok@ScanGroup@ii{ }#1\FV@<Sentinel>^^C}}

\FV@PDFStrVDetok@ScanEmptyGroup
875 \begingroup
876 \catcode`\(=1
877 \catcode`\)=2
878 \catcode`\{=12
879 \catcode`\}=12
880 \gdef\FV@PDFStrVDetok@ScanEmptyGroup({}\FV@PDFStrVDetok@ScanGroup)
881 \endgroup

\FV@PDFStrVDetok@ScanGroup@ii
882 \begingroup
883 \catcode`\(=1
884 \catcode`\)=2
885 \catcode`\{=12
886 \catcode`\}=12
887 \gdef\FV@PDFStrVDetok@ScanGroup@ii#1\FV@<Sentinel>#2^^C(%
888 \if\relax\detokenize{#2}\relax
889 \expandafter\@firstofone
890 \else
891 \expandafter\@gobble
892 \fi
893 ({\FV@PDFStrVDetok@Scan#1^^C \FV@<Sentinel>}\FV@PDFStrVDetok@ScanGroup))
894 \endgroup

\FV@PDFStrVDetok@ScanToken
895 \gdef\FV@PDFStrVDetok@ScanToken#1{%
896 \ifx\FV@Sentinel#1%
897 \expandafter\@gobble
898 \else
899 \expandafter\@firstofone
900 \fi
901 {\expandafter\FV@PDFStrVDetok@ScanToken@i\detokenize{#1}^^C \FV@<Sentinel>}}

```

`\FV@PDFStrVDetok@ScanToken@i`

```
902 \gdef\FV@PDFStrVDetok@ScanToken@i#1 #2\FV@<Sentinel>{%
903   \if\relax\detokenize{#2}\relax
904     \expandafter\@firstoftwo
905   \else
906     \expandafter\@secondoftwo
907   \fi
908   {\FV@PDFStrVDetok@ScanTokenNoSpace#1}%
909   {\FV@PDFStrVDetok@ScanTokenWithSpace{#1}}}
```

`\FV@PDFStrVDetok@ScanTokenNoSpace`

This is modified to use `\FVExtraPDFStringEscapeChars`.

```
910 \gdef\FV@PDFStrVDetok@ScanTokenNoSpace#1^^C{%
911   \FVExtraPDFStringEscapeChars{#1}\FV@PDFStrVDetok@ScanToken}
```

`\FV@PDFStrVDetok@ScanTokenWithSpace`

```
912 \gdef\FV@PDFStrVDetok@ScanTokenWithSpace#1{%
913   \if\relax\detokenize{#1}\relax
914     \expandafter\@firstoftwo
915   \else
916     \expandafter\@secondoftwo
917   \fi
918   {\FV@PDFStrVDetok@ScanTokenActiveSpace}%
919   {\FV@PDFStrVDetok@ScanTokenWithSpace@i#1\FV@<Sentinel>}}
```

`\FV@PDFStrVDetok@ScanTokenActiveSpace`

This is modified to use `\040` rather than a catcode 12 space.

```
920 \begingroup
921 \catcode`\!=0\relax
922 \catcode`\|=12\relax
923 !gdef!FV@PDFStrVDetok@ScanTokenActiveSpace{\040!FV@PDFStrVDetok@ScanToken}%
924 !catcode`\|=0!relax
925 \endgroup
```

`\FV@PDFStrVDetok@ScanTokenWithSpace@i`

If there is only one character left once the space is removed, this is the escaped space `\.`. Otherwise, this is a command word that needs further processing.

```
926 \gdef\FV@PDFStrVDetok@ScanTokenWithSpace@i#1#2\FV@<Sentinel>{%
927   \if\relax\detokenize{#2}\relax
928     \expandafter\@firstoftwo
929   \else
930     \expandafter\@secondoftwo
931   \fi
932   {\FV@PDFStrVDetok@ScanTokenEscSpace{#1}}%
933   {\FV@PDFStrVDetok@ScanTokenCW{#1#2}}}
```

`\FV@PDFStrVDetok@ScanTokenEscSpace`

This is modified to add `\FVExtraPDFStringEscapeChar` and use `\040` for the space, since a space could follow.

```
934 \begingroup
935 \catcode`\!=0\relax
936 \catcode`\|=12\relax
937 !gdef!FV@PDFStrVDetok@ScanTokenEscSpace#1{%
938   !FVExtraPDFStringEscapeChar{#1}\040!FV@PDFStrVDetok@ScanToken}%
939 !catcode`\|=0!relax
```

```

940 \endgroup
\FV@PDFStrVDetok@ScanTokenCW
    This is modified to add \FVExtraPDFStringEscapeChars.
941 \begingroup
942 \catcode`\< =12%
943 \gdef\FV@PDFStrVDetok@ScanTokenCW#1#2{%
944 \ifcat\noexpand#2a%
945 \expandafter\@firstoftwo%
946 \else%
947 \expandafter\@secondoftwo%
948 \fi%
949 {\FVExtraPDFStringEscapeChars{#1} \FV@PDFStrVDetok@ScanToken#2}%
950 {\FVExtraPDFStringEscapeChars{#1}\FV@PDFStrVDetok@ScanToken#2}}
951 \endgroup

```

Detokenize as if the original source were tokenized verbatim, except for backslash escapes of non-catcode 11 characters

```
\FVExtraEscapedVerbatimDetokenize
```

This is a variant of `\FVExtraVerbatimDetokenize` that treats character sequences of the form `\<char>` as escapes for `<char>`. It is primarily intended for making `\<symbol>` escapes for `<symbol>`, but allowing arbitrary escapes simplifies the default behavior and implementation. This is useful in constructing nearly verbatim commands that can be used inside other commands, because the backslash escapes allow for characters like `#` and `%`, as well as making possible multiple adjacent spaces via `\.`. It should be applied to arguments that are read verbatim insofar as is possible, except that the backslash `\` should have its normal meaning (catcode 0). Most of the implementation is identical to that for `\FVExtraVerbatimDetokenize`. Only the token processing requires modification to handle backslash escapes.

It is possible to restrict escapes to ASCII symbols and punctuation. See `\FVExtraDetokenizerREscVArg`. The disadvantage of restricting escapes is that it prevents functioning in an expansion-only context (unless you want to use undefined macros as a means of raising errors). The advantage is that it eliminates ambiguity introduced by allowing arbitrary escapes. Backslash escapes of characters with catcode 11 (ASCII letters, `[A-Za-z]`) are typically not necessary, and introduce ambiguity because something like `\x` will gobble following spaces since it will be tokenized originally as a control word.

```

952 \gdef\FVExtraEscapedVerbatimDetokenize#1{%
953 \FV@EscVDetok@Scan{#1}~C \FV@<Sentinel>}
\FV@EscVDetok@Scan
954 \gdef\FV@EscVDetok@Scan#1 #2\FV@<Sentinel>{%
955 \if\relax\detokenize{#2}\relax
956 \expandafter\@firstoftwo
957 \else
958 \expandafter\@secondoftwo
959 \fi
960 {\FV@EscVDetok@ScanEnd#1}%
961 {\FV@EscVDetok@ScanCont{#1}{#2}}}
\FV@EscVDetok@ScanEnd

```

```

962 \gdef\FV@EscVDetok@ScanEnd#1^^C{%
963   \if\relax\detokenize{#1}\relax
964     \expandafter@gobble
965   \else
966     \expandafter@firstofone
967   \fi
968   {\expandafter\FV@EscVDetok@ScanGroup@gobble#1{\FV@<Sentinel>}}

```

\FV@EscVDetok@ScanCont

```

969 \begingroup
970 \catcode`\ =12%
971 \gdef\FV@EscVDetok@ScanCont#1#2{%
972   \if\relax\detokenize{#1}\relax%
973   \expandafter@gobble%
974   \else%
975   \expandafter@firstofone%
976   \fi%
977   {\expandafter\FV@EscVDetok@ScanGroup@gobble#1{\FV@<Sentinel>}}%
978   %<-catcode 12 space
979   \FV@EscVDetok@Scan{#2\FV@<Sentinel>}%
980 \endgroup

```

\FV@EscVDetok@ScanGroup

```

981 \gdef\FV@EscVDetok@ScanGroup#1#{%
982   \FV@EscVDetok@ScanToken#1\FV@Sentinel
983   \FV@EscVDetok@ScanGroup@i}

```

\FV@EscVDetok@ScanGroup@i

```

984 \gdef\FV@EscVDetok@ScanGroup@i#1{%
985   \if\relax\detokenize{#1}\relax
986     \expandafter@firstoftwo
987   \else
988     \expandafter@secondoftwo
989   \fi
990   {\FV@EscVDetok@ScanEmptyGroup}%
991   {\FV@EscVDetok@ScanGroup@ii{#1\FV@<Sentinel>^^C}}

```

\FV@EscVDetok@ScanEmptyGroup

```

992 \begingroup
993 \catcode`\ (=1
994 \catcode`\ )=2
995 \catcode`\ {=12
996 \catcode`\ }=12
997 \gdef\FV@EscVDetok@ScanEmptyGroup({}\FV@EscVDetok@ScanGroup)
998 \endgroup

```

\FV@EscVDetok@ScanGroup@ii

```

999 \begingroup
1000 \catcode`\ (=1
1001 \catcode`\ )=2
1002 \catcode`\ {=12
1003 \catcode`\ }=12
1004 \gdef\FV@EscVDetok@ScanGroup@ii#1\FV@<Sentinel>#2^^C(
1005   \if\relax\detokenize{#2}\relax

```

```

1006     \expandafter\@firstofone
1007     \else
1008     \expandafter\@gobble
1009     \fi
1010     ({\FV@EscVDetok@Scan#1^^C \FV@<Sentinel>}\FV@EscVDetok@ScanGroup))
1011 \endgroup
\FV@EscVDetok@ScanToken
1012 \gdef\FV@EscVDetok@ScanToken#1{%
1013     \ifx\FV@Sentinel#1%
1014     \expandafter\@gobble
1015     \else
1016     \expandafter\@firstofone
1017     \fi
1018     {\expandafter\FV@EscVDetok@ScanToken@i\detokenize{#1}^^C \FV@<Sentinel>}}
\FV@EscVDetok@ScanToken@i
1019 \gdef\FV@EscVDetok@ScanToken@i#1 #2\FV@<Sentinel>{%
1020     \if\relax\detokenize{#2}\relax
1021     \expandafter\@firstoftwo
1022     \else
1023     \expandafter\@secondoftwo
1024     \fi
1025     {\FV@EscVDetok@ScanTokenNoSpace#1}%
1026     {\FV@EscVDetok@ScanTokenWithSpace{#1}}}

```

Parallel implementations, with a restricted option Starting here, there are alternate macros for restricting escapes to ASCII punctuation and symbols. These alternates have names of the form `\FV@REscVDetok@<name>`. They are used in `\FVExtraDetokenizeREscVArg`. The alternate `\FV@REscVDetok@<name>` macros replace invalid escape sequences with the undefined `\FV@<InvalidEscape>`, which is later scanned for with a delimited macro.

`\FV@EscVDetok@ScanTokenNoSpace`

This was modified from `\FV@VDetok@ScanTokenNoSpace` to discard the first character of multi-character sequences (that would be the backslash `\`).

```

1027 \gdef\FV@EscVDetok@ScanTokenNoSpace#1#2^^C{%
1028     \if\relax\detokenize{#2}\relax
1029     \expandafter\@firstoftwo
1030     \else
1031     \expandafter\@secondoftwo
1032     \fi
1033     {#1\FV@EscVDetok@ScanToken}%
1034     {#2\FV@EscVDetok@ScanToken}}
\FV@REscVDetok@ScanTokenNoSpace
1035 \gdef\FV@REscVDetok@ScanTokenNoSpace#1#2^^C{%
1036     \if\relax\detokenize{#2}\relax
1037     \expandafter\@firstoftwo
1038     \else
1039     \expandafter\@secondoftwo
1040     \fi
1041     {#1\FV@EscVDetok@ScanToken}%
1042     {\ifcsname FV@Char@Special:\number`#2\endcsname#2\else\noexpand\FV@<InvalidEscape>\fi
1043     \FV@EscVDetok@ScanToken}}

```

`\FV@EscVDetok@ScanTokenWithSpace`

```
1044 \gdef\FV@EscVDetok@ScanTokenWithSpace#1{%
1045   \if\relax\detokenize{#1}\relax
1046     \expandafter\@firstoftwo
1047   \else
1048     \expandafter\@secondoftwo
1049   \fi
1050   {\FV@EscVDetok@ScanTokenActiveSpace}%
1051   {\FV@EscVDetok@ScanTokenWithSpace@i#1\FV@<Sentinel>}}
```

`\FV@EscVDetok@ScanTokenActiveSpace`

```
1052 \begingroup
1053 \catcode`\ =12%
1054 \gdef\FV@EscVDetok@ScanTokenActiveSpace{ \FV@EscVDetok@ScanToken}%
1055 \endgroup
```

`\FV@EscVDetok@ScanTokenWithSpace@i`

If there is only one character left once the space is removed, this is the escaped space `\.`. Otherwise, this is a command word. A command word is passed on so as to keep the backslash and letters separate.

```
1056 \gdef\FV@EscVDetok@ScanTokenWithSpace@i#1#2\FV@<Sentinel>{%
1057   \if\relax\detokenize{#2}\relax
1058     \expandafter\@firstoftwo
1059   \else
1060     \expandafter\@secondoftwo
1061   \fi
1062   {\FV@EscVDetok@ScanTokenEscSpace{#1}}%
1063   {\FV@EscVDetok@ScanTokenCW{#1}{#2}}}
```

`\FV@REscVDetok@ScanTokenWithSpace@i`

```
1064 \gdef\FV@REscVDetok@ScanTokenWithSpace@i#1#2\FV@<Sentinel>{%
1065   \if\relax\detokenize{#2}\relax
1066     \expandafter\@firstoftwo
1067   \else
1068     \expandafter\@secondoftwo
1069   \fi
1070   {\FV@EscVDetok@ScanTokenEscSpace{#1}}%
1071   {\noexpand\FV@<InvalidEscape>\FV@EscVDetok@ScanToken}}
```

`\FV@EscVDetok@ScanTokenEscSpace`

This is modified to drop #1, which will be the backslash.

```
1072 \begingroup
1073 \catcode`\ =12%
1074 \gdef\FV@EscVDetok@ScanTokenEscSpace#1{ \FV@EscVDetok@ScanToken}%
1075 \endgroup
```

`\FV@EscVDetok@ScanTokenCW`

This is modified to accept an additional argument, since the control word is now split into backslash plus letters.

```
1076 \begingroup
1077 \catcode`\ =12%
1078 \gdef\FV@EscVDetok@ScanTokenCW#1#2#3{%
1079   \ifcat\noexpand#2a%
1080     \expandafter\@firstoftwo%
```

```

1081 \else%
1082 \expandafter\@secondoftwo%
1083 \fi%
1084 {#2\FV@EscVDetok@ScanToken#3}%
1085 {#2\FV@EscVDetok@ScanToken#3}}
1086 \endgroup

```

Detokenize as if the original source were tokenized verbatim, except for backslash escapes of non-catcode 11 characters, then convert to PDF string

\FVExtraPDFStringEscapedVerbatimDetokenize

This is identical to \FVExtraEscapedVerbatimDetokenize, except that the output is converted to a valid PDF string. All spaces are represented with the octal escape \040 to prevent adjacent spaces from being merged. There is no alternate implementation for restricting escapes to ASCII symbols and punctuation. Typically, this would be used in an expansion-only context to create something like bookmarks, while \FVExtraEscapedVerbatimDetokenize (potentially with escape restrictions) would be used in parallel to generate whatever is actually typeset. Escape errors can be handled in generating what is typeset.

```

1087 \gdef\FVExtraPDFStringEscapedVerbatimDetokenize#1{%
1088   \FV@PDFStrEscVDetok@Scan{ }#1~^C \FV@<Sentinel>}

```

\FV@PDFStrEscVDetok@Scan

```

1089 \gdef\FV@PDFStrEscVDetok@Scan#1 #2\FV@<Sentinel>{%
1090   \if\relax\detokenize{#2}\relax
1091     \expandafter\@firstoftwo
1092   \else
1093     \expandafter\@secondoftwo
1094   \fi
1095   {\FV@PDFStrEscVDetok@ScanEnd#1}%
1096   {\FV@PDFStrEscVDetok@ScanCont{#1}{#2}}}

```

\FV@PDFStrEscVDetok@ScanEnd

```

1097 \gdef\FV@PDFStrEscVDetok@ScanEnd#1~^C{%
1098   \if\relax\detokenize{#1}\relax
1099     \expandafter\@gobble
1100   \else
1101     \expandafter\@firstofone
1102   \fi
1103   {\expandafter\FV@PDFStrEscVDetok@ScanGroup\@gobble#1{\FV@<Sentinel>}}}

```

\FV@PDFStrEscVDetok@ScanCont

This is modified to use \040 for the space. In the unescaped case, using a normal space here is fine, but in the escaped case, the preceding or following token could be an escaped space.

```

1104 \begingroup
1105 \catcode`\!=0\relax
1106 \catcode`\=12\relax
1107 !gdef!FV@PDFStrEscVDetok@ScanCont#1#2{%
1108   !if!relax!detokenize{#1}!relax
1109     !expandafter!@gobble
1110   !else

```

```

1111     !expandafter!@firstofone
1112     !fi
1113     {!expandafter!FV@PDFStrEscVDetok@ScanGroup!@gobble#1{!FV@<Sentinel>}}%
1114     \O40%<-space
1115     !FV@PDFStrEscVDetok@Scan{ }#2!FV@<Sentinel>}%
1116 !catcode`\=0!relax
1117 \endgroup
\FV@PDFStrEscVDetok@ScanGroup
1118 \gdef\FV@PDFStrEscVDetok@ScanGroup#1#{%
1119   \FV@PDFStrEscVDetok@ScanToken#1\FV@Sentinel
1120   \FV@PDFStrEscVDetok@ScanGroup@i}
\FV@PDFStrEscVDetok@ScanGroup@i
1121 \gdef\FV@PDFStrEscVDetok@ScanGroup@i#1{%
1122   \if\relax\detokenize{#1}\relax
1123     \expandafter\@firstoftwo
1124   \else
1125     \expandafter\@secondoftwo
1126   \fi
1127   {\FV@PDFStrEscVDetok@ScanEmptyGroup}%
1128   {\FV@PDFStrEscVDetok@ScanGroup@ii{ }#1\FV@<Sentinel>^^C}}
\FV@PDFStrEscVDetok@ScanEmptyGroup
1129 \begingroup
1130 \catcode`\(=1
1131 \catcode`\)=2
1132 \catcode`\{=12
1133 \catcode`\}=12
1134 \gdef\FV@PDFStrEscVDetok@ScanEmptyGroup({}\FV@PDFStrEscVDetok@ScanGroup)
1135 \endgroup
\FV@PDFStrEscVDetok@ScanGroup@ii
1136 \begingroup
1137 \catcode`\(=1
1138 \catcode`\)=2
1139 \catcode`\{=12
1140 \catcode`\}=12
1141 \gdef\FV@PDFStrEscVDetok@ScanGroup@ii#1\FV@<Sentinel>#2^^C(%
1142   \if\relax\detokenize{#2}\relax
1143     \expandafter\@firstofone
1144   \else
1145     \expandafter\@gobble
1146   \fi
1147   ({\FV@PDFStrEscVDetok@Scan#1^^C \FV@<Sentinel>}\FV@PDFStrEscVDetok@ScanGroup))
1148 \endgroup
\FV@PDFStrEscVDetok@ScanToken
1149 \gdef\FV@PDFStrEscVDetok@ScanToken#1{%
1150   \ifx\FV@Sentinel#1%
1151     \expandafter\@gobble
1152   \else
1153     \expandafter\@firstofone
1154   \fi
1155   {\expandafter\FV@PDFStrEscVDetok@ScanToken@i\detokenize{#1}^^C \FV@<Sentinel>}}

```

`\FV@PDFStrEscVDetok@ScanToken@i`

```
1156 \gdef\FV@PDFStrEscVDetok@ScanToken@i#1 #2\FV@<Sentinel>{%  
1157 \if\relax\detokenize{#2}\relax  
1158 \expandafter\@firstoftwo  
1159 \else  
1160 \expandafter\@secondoftwo  
1161 \fi  
1162 {\FV@PDFStrEscVDetok@ScanTokenNoSpace#1}%  
1163 {\FV@PDFStrEscVDetok@ScanTokenWithSpace{#1}}}
```

`\FV@PDFStrEscVDetok@ScanTokenNoSpace`

This was modified to add `\FVExtraPDFStringEscapeChar`

```
1164 \gdef\FV@PDFStrEscVDetok@ScanTokenNoSpace#1#2^^C{%  
1165 \if\relax\detokenize{#2}\relax  
1166 \expandafter\@firstoftwo  
1167 \else  
1168 \expandafter\@secondoftwo  
1169 \fi  
1170 {\FVExtraPDFStringEscapeChar{#1}\FV@PDFStrEscVDetok@ScanToken}%  
1171 {\FVExtraPDFStringEscapeChar{#2}\FV@PDFStrEscVDetok@ScanToken}}
```

`\FV@PDFStrEscVDetok@ScanTokenWithSpace`

```
1172 \gdef\FV@PDFStrEscVDetok@ScanTokenWithSpace#1{%  
1173 \if\relax\detokenize{#1}\relax  
1174 \expandafter\@firstoftwo  
1175 \else  
1176 \expandafter\@secondoftwo  
1177 \fi  
1178 {\FV@PDFStrEscVDetok@ScanTokenActiveSpace}%  
1179 {\FV@PDFStrEscVDetok@ScanTokenWithSpace@i#1\FV@<Sentinel>}}
```

`\FV@PDFStrEscVDetok@ScanTokenActiveSpace`

This is modified to use `\040` for the space.

```
1180 \begingroup  
1181 \catcode`\!=0\relax  
1182 \catcode`\=12\relax  
1183 !gdef!\FV@PDFStrEscVDetok@ScanTokenActiveSpace{\040!\FV@PDFStrEscVDetok@ScanToken}%  
1184 !catcode`\!=0\relax  
1185 \endgroup
```

`\FV@PDFStrEscVDetok@ScanTokenWithSpace@i`

```
1186 \gdef\FV@PDFStrEscVDetok@ScanTokenWithSpace@i#1#2\FV@<Sentinel>{%  
1187 \if\relax\detokenize{#2}\relax  
1188 \expandafter\@firstoftwo  
1189 \else  
1190 \expandafter\@secondoftwo  
1191 \fi  
1192 {\FV@PDFStrEscVDetok@ScanTokenEscSpace{#1}}%  
1193 {\FV@PDFStrEscVDetok@ScanTokenCW{#1}{#2}}}
```

`\FV@PDFStrEscVDetok@ScanTokenEscSpace`

This is modified to drop `#1`, which will be the backslash, and use `\040` for the space.

```
1194 \begingroup
```

```

1195 \catcode`\!=0\relax
1196 \catcode`\|=12\relax
1197 !gdef\FV@PDFStrEscVDetok@ScanTokenEscSpace#1{\040\FV@PDFStrEscVDetok@ScanToken}
1198 !catcode`\|=0\relax
1199 \endgroup
\FV@PDFStrEscVDetok@ScanTokenCW
    This is modified to use \FVExtraPDFStringEscapeChars.
1200 \begingroup
1201 \catcode`\ =12%
1202 \gdef\FV@PDFStrEscVDetok@ScanTokenCW#1#2#3{%
1203 \ifcat\noexpand#2a%
1204 \expandafter\@firstoftwo%
1205 \else%
1206 \expandafter\@secondoftwo%
1207 \fi%
1208 {\FVExtraPDFStringEscapeChars{#2} \FV@PDFStrEscVDetok@ScanToken#3}%
1209 {\FVExtraPDFStringEscapeChars{#2}\FV@PDFStrEscVDetok@ScanToken#3}}
1210 \endgroup

```

Detokenization wrappers

\FVExtraDetokenizeVArg

Detokenize a verbatim argument read by \FVExtraReadVArg. This is a wrapper around \FVExtraVerbatimDetokenize that adds some additional safety by ensuring \^C is \active with an appropriate definition, at the cost of not working in an expansion-only context. This tradeoff isn't an issue when working with \FVExtraReadVArg, because it has the same expansion limitations.

```

1211 \gdef\FVExtraDetokenizeVArg#1#2{%
1212 \begingroup
1213 \catcode`\^C=\active
1214 \let\^C\FV@Sentinel
1215 \edef\FV@Tmp{\FVExtraVerbatimDetokenize{#2}}%
1216 \expandafter\FV@DetokenizeVArg@i\expandafter{\FV@Tmp}{#1}}
1217 \gdef\FV@DetokenizeVArg@i#1#2{%
1218 \endgroup
1219 #2{#1}}

```

\FVExtraDetokenizeEscVArg

This is the same as \FVExtraDetokenizeVArg, except it is intended to work with \FVExtraReadEscVArg by using \FVExtraEscapedVerbatimDetokenize.

```

1220 \gdef\FVExtraDetokenizeEscVArg#1#2{%
1221 \begingroup
1222 \catcode`\^C=\active
1223 \let\^C\FV@Sentinel
1224 \edef\FV@Tmp{\FVExtraEscapedVerbatimDetokenize{#2}}%
1225 \expandafter\FV@DetokenizeVArg@i\expandafter{\FV@Tmp}{#1}}

```

\FVExtraDetokenizeREscVArg

```

1226 \gdef\FVExtraDetokenizeREscVArg#1#2{%
1227 \begingroup
1228 \catcode`\^C=\active
1229 \let\^C\FV@Sentinel
1230 \let\FV@EscVDetok@ScanTokenNoSpace\FV@REscVDetok@ScanTokenNoSpace

```

```

1231 \let\FV@EscVDetok@ScanTokenWithSpace@i\FV@REscVDetok@ScanTokenWithSpace@i
1232 \edef\FV@Tmp{\FVExtraEscapedVerbatimDetokenize{#2}}%
1233 \expandafter\FV@DetokenizeREscVArg@InvalidEscapeCheck\FV@Tmp\FV@<InvalidEscape>\FV@<Sentinel>
1234 \expandafter\FV@DetokenizeVArg@i\expandafter{\FV@Tmp}{#1}}
1235 \gdef\FV@DetokenizeREscVArg@InvalidEscapeCheck#1\FV@<InvalidEscape>#2\FV@<Sentinel>{%
1236 \if\relax\detokenize{#2}\relax
1237 \expandafter\@gobble
1238 \else
1239 \expandafter\@firstofone
1240 \fi
1241 {\PackageError{fvextra}%
1242 {Invalid backslash escape; only escape ASCII symbols and punctuation}%
1243 {Only use \@backslashchar <char> for ASCII symbols and punctuation}}

```

End catcodes for this subsection:

```

1244 \endgroup

```

12.4.6 Retokenizing detokenized arguments

`\FV@RetokVArg@Read`

Read all tokens up to `\active ^^C^^M`, then save them in a macro for further use. This is used to read tokens inside `\scantokens` during retokenization. The `\endgroup` disables catcode modifications that will have been put in place for the reading process, including making `^^C` and `^^M` `\active`.

```

1245 \begingroup
1246 \catcode`^^C=\active%
1247 \catcode`^^M=\active%
1248 \gdef\FV@RetokVArg@Read#1^^C^^M{%
1249 \endgroup%
1250 \def\FV@TmpRetoked{#1}}%
1251 \endgroup

```

`\FVExtraRetokenizeVArg`

This retokenizes the detokenized output of something like `\FVExtraVerbatimDetokenize` or `\FVExtraDetokenizeVArg`. `#1` is a macro that receives the output, `#2` sets catcodes but includes no `\begingroup` or `\endgroup`, and `#3` is the detokenized characters. `\FV@RetokVArg@Read` contains an `\endgroup` that returns catcodes to their prior state.

This is a somewhat atypical use of `\scantokens`. There is no `\everyeof{\noexpand}` to handle the end-of-file marker, and no `\endlinechar=-1` to ignore the end-of-line token so that it does not become a space. Rather, the end-of-line `^^M` is made `\active` and used as a delimiter by `\FV@RetokVArg@Read`, which reads characters under the new catcode regime, then stores them unexpanded in `\FV@TmpRetoked`.

Inside `\scantokens` is `^^B#3^^C`. This becomes `^^B#3^^C^^M` once `\scantokens` inserts the end-of-line token. `^^B` is `\let` to `\FV@RetokVArg@Read`, rather than using `\FV@RetokVArg@Read` directly, because `\scantokens` acts as a `\write` followed by `\input`. That means that a command word like `\FV@RetokVArg@Read` will have a space inserted after it, while an `\active` character like `^^B` will not. Using `^^B` is a way to avoid needing to remove this space; it is simpler not to handle the scenario where `\FV@RetokVArg@Read` introduces a space and the detokenized characters also start with a space. The `^^C` is needed because trailing spaces on

a line are automatically stripped, so a non-space character must be part of the delimiting token sequence.

```

1252 \begingroup
1253 \catcode\^^B=\active
1254 \catcode\^^C=\active
1255 \gdef\FVExtraRetokenizeVArg#1#2#3{%
1256   \begingroup
1257   #2%
1258   \catcode\^^B=\active
1259   \catcode\^^C=\active
1260   \catcode\^^M=\active
1261   \let^^B\FV@RetokVArg@Read
1262   \let^^C\@empty
1263   \FV@DefEOLEmpty
1264   \scantokens{\^^B#3^^C}%
1265   \expandafter\FV@RetokenizeVArg@i\expandafter{\FV@TmpRetoked}{#1}}%
1266 \gdef\FV@RetokenizeVArg@i#1#2{%
1267   #2{#1}}
1268 \endgroup

```

12.5 Hooks

`\FV@UseKeyValues@Hook`

This hook is useful for tasks that must be accomplished immediately after the beginning of a command or environment, just after `\begingroup`, before any catcode or similar changes are made. Hooking into `\FV@CatCodes` is not a straightforward alternative, because it may be invoked multiple times in the original `fancyvrb` code, plus additional times in `fvextra` code during retokenization. Hooking into `\FV@FormattingPrep` is not a reliable alternative, because it may be invoked before or after `\FV@CatCodes`.

```

1269 \let\FV@UseKeyValues@Hook\@empty
1270 \expandafter\def\expandafter\FV@UseKeyValues\expandafter{%
1271   \FV@UseKeyValues\FV@UseKeyValues@Hook}

```

`\FV@FormattingPrep@PreHook`

`\FV@FormattingPrep@PostHook`

These are hooks for extending `\FV@FormattingPrep`. `\FV@FormattingPrep` is inside a group, before the beginning of processing, so it is a good place to add extension code. These hooks are used for such things as tweaking math mode behavior and preparing for `breakbefore` and `breakafter`. The `PreHook` should typically be used, unless `fancyvrb`'s font settings, whitespace setup, and active character definitions are needed for extension code.

```

1272 \let\FV@FormattingPrep@PreHook\@empty
1273 \let\FV@FormattingPrep@PostHook\@empty
1274 \expandafter\def\expandafter\FV@FormattingPrep\expandafter{%
1275   \expandafter\FV@FormattingPrep@PreHook\FV@FormattingPrep\FV@FormattingPrep@PostHook}

```

`\FV@PygmentsHook`

This is a hook for turning on Pygments-related features for packages like `minted` and `pythontex` (section 12.13). It needs to be the first thing in `\FV@FormattingPrep@PreHook`, since it will potentially affect some of the later things in the hook. It is activated by `\VerbatimPygments`.

```

1276 \def\FV@PygmentsHook{}
1277 \g@addto@macro\FV@FormattingPrep@PreHook{\FV@PygmentsHook}

```

12.6 Escaped characters

\FV@EscChars

Define versions of common escaped characters that reduce to raw characters. This is useful, for example, when working with text that is almost verbatim, but was captured in such a way that some escapes were unavoidable.

```

1278 \edef\FV@hashchar{\string#}
1279 \edef\FV@dollarchar{\string$}
1280 \edef\FV@ampchar{\string&}
1281 \edef\FV@underscorechar{\string_}
1282 \edef\FV@caretchar{\string^}
1283 \edef\FV@tildechar{\string~}
1284 \edef\FV@leftsquarebracket{\string[]}
1285 \edef\FV@rightsquarebracket{\string]}
1286 \edef\FV@commachar{\string,}
1287 \newcommand{\FV@EscChars}{%
1288   \let#\FV@hashchar
1289   \let%\FV@percentchar
1290   \let{\FV@charlb
1291   \let}\FV@charrb
1292   \let$\FV@dollarchar
1293   \let&\FV@ampchar
1294   \let_\FV@underscorechar
1295   \let^\FV@caretchar
1296   \let\\\FV@backslashchar
1297   \let~\FV@tildechar
1298   \let~\FV@tildechar
1299   \let[\FV@leftsquarebracket
1300   \let]\FV@rightsquarebracket
1301   \let,\FV@commachar
1302 } %$ <- highlighting

```

12.7 Inline-only options

Create `\fvinline` for inline-only options. Note that this only applies to new or reimplemented inline commands that use `\FV@UseInlineKeyValues`.

\FV@InlineKeyValues

```

1303 \def\FV@InlineKeyValues{}

```

\fvinline

```

1304 \def\fvinline#1{%
1305   \expandafter\def\expandafter\FV@InlineKeyValues\expandafter{%
1306     \FV@InlineKeyValues#1,}}

```

\FV@UseInlineKeyValues

```

1307 \def\FV@UseInlineKeyValues{%
1308   \expandafter\fvset\expandafter{\FV@InlineKeyValues}%
1309   \FV@ApplyBreakAnywhereInlineStretch}

```

12.8 Reimplementations

`fvextra` reimplements some `fancyvrb` internals. The patches in section 12.10 fix bugs, handle edge cases, and extend existing functionality in logical ways, while leaving default `fancyvrb` behavior largely unchanged. In contrast, reimplementations add features by changing existing behavior in significant ways. As a result, there is a boolean option `extra` that allows them to be disabled.

12.8.1 `extra` option

Boolean option that governs whether reimplemented commands and environments should be used, rather than the original definitions.

`FV@extra`

```
1310 \newbool{FV@extra}
```

`extra`

```
1311 \define@booleankey{FV}{extra}%  
1312 {\booltrue{FV@extra}}%  
1313 {\boolfalse{FV@extra}}  
1314 \fvset{extra=true}
```

12.8.2 `\FancyVerbFormatInline`

This allows customization of inline verbatim material. It is the inline equivalent of `\FancyVerbFormatLine` and `\FancyVerbFormatText`.

`\FancyVerbFormatInline`

```
1315 \def\FancyVerbFormatInline#1{#1}
```

12.8.3 `\Verb`

`\Verb` is reimplemented so that it functions as well as possible when used within other commands.

`\verb` cannot be used inside other commands. The original `fancyvrb` implementation of `\Verb` does work inside other commands, but being inside other commands reduces its functionality since there is no attempt at retokenization. When used inside other commands, it essentially reduces to `\texttt`. `\Verb` also fails when the delimiting characters are active, since it assumes that the closing delimiting character will have catcode 12.

`fvextra`'s re-implemented `\Verb` uses `\scantokens` and careful consideration of catcodes to (mostly) remedy this. It also adds support for paired curly braces `{...}` as the delimiters for the verbatim argument, since this is often convenient when `\Verb` is used within another command. The original `\Verb` implementation is completely incompatible with curly braces being used as delimiters, so this doesn't affect backward compatibility.

The re-implemented `\Verb` is constructed with `\FVExtraRobustCommand` so that it will function correctly after being in an expansion-only context, so long as the argument is delimited with curly braces.

`\Verb`

```
1316 \def\Verb{%  
1317 \FVExtraRobustCommand\RobustVerb\FVExtraUnexpandedReadStar0ArgBVar}
```

```

\RobustVerb
1318 \protected\def\RobustVerb{\FV@Command}{Verb}}
1319 \FVExtrapdfstringdefDisableCommands{%
1320 \def\RobustVerb{}}

\FVC@Verb@FV
Save the original fancyvrb definition of \FVC@Verb, so that the extra option
can switch back to it.
1321 \let\FVC@Verb@FV\FVC@Verb

\FVC@Verb
Redefine \FVC@Verb so that it will adjust based on extra.
1322 \def\FVC@Verb{%
1323 \begingroup
1324 \FV@UseInlineKeyValues\FV@UseKeyValues
1325 \ifFV@extra
1326 \expandafter\endgroup\expandafter\FVC@Verb@Extra
1327 \else
1328 \expandafter\endgroup\expandafter\FVC@Verb@FV
1329 \fi}

\FVC@Verb@Extra
fvextra reimplementaion of \FVC@Verb.
When used after expansion, there is a check for valid delimiters, curly braces.
If incorrect delimiters are used, and there are no following curly braces, then the
reader macro \FVExtraUnexpandedReadStar0ArgBVarArg will give an error about
unmatched braces. However, if incorrect delimiters are used, and there are following
braces in a subsequent command, then this error will be triggered, preventing
interference with the following command by the reader macro.
1330 \def\FVC@Verb@Extra{%
1331 \ifbool{FVExtraRobustCommandExpanded}%
1332 {\ifnextchar\bgroup
1333 {\FVC@Verb@Extra@i}%
1334 {\PackageError{fvextra}%
1335 {\string\Verb\space delimiters must be paired curly braces in this context}%
1336 {Use curly braces as delimiters}}}%
1337 {\FVC@Verb@Extra@i}}

\FVC@Verb@Extra@i
1338 \def\FVC@Verb@Extra@i{%
1339 \begingroup
1340 \ifbool{FV@vargsingleline}%
1341 {\let\FV@Reader\FVExtraReadVArgSingleLine}%
1342 {\let\FV@Reader\FVExtraReadVArg}%
1343 \FV@Reader{%
1344 \FV@UseInlineKeyValues\FV@UseKeyValues\FV@FormattingPrep
1345 \FVExtraDetokenizeVArg}%
1346 \FVExtraRetokenizeVArg{\FVC@Verb@Extra@ii}{\FV@CatCodes}}}}

\FVC@Verb@Extra@ii
breaklines is only applied when there is no background color, since \colorbox
prevents line breaks.
1347 \def\FVC@Verb@Extra@ii#1{%
1348 \ifx\FancyVerbBackgroundColor\relax

```

```

1349 \expandafter\@firstoftwo
1350 \else
1351 \expandafter\@secondoftwo
1352 \fi
1353 {\ifbool{FV@breaklines}%
1354  {\FV@InsertBreaks{\FancyVerbFormatInline}{#1}}%
1355  {\mbox{\FancyVerbFormatInline{#1}}}%
1356  {\setlength{\FV@TmpLength}{\fboxsep}%
1357   \ifx\FancyVerbBackgroundColorPadding\relax
1358    \setlength{\fboxsep}{Opt}%
1359   \else
1360    \setlength{\fboxsep}{\FancyVerbBackgroundColorPadding}%
1361   \fi
1362   \colorbox{\FancyVerbBackgroundColor}{%
1363    \setlength{\fboxsep}{\FV@TmpLength}%
1364    \FancyVerbBackgroundColorVPhantom\FancyVerbFormatInline{#1}}}%
1365 \endgroup}

```

12.8.4 \SaveVerb

This is reimplemented, following \Verb as a template, so that both \Verb and \SaveVerb are using the same reading and tokenization macros. This also adds support for \fvinlineset. Since the definition in fancyvrb is

```
\def\SaveVerb{\FV@Command}{\SaveVerb}
```

only the internal macros need to be reimplemented.

\FVC@SaveVerb@FV

```
1366 \let\FVC@SaveVerb@FV\FVC@SaveVerb
```

\FVC@SaveVerb

```

1367 \def\FVC@SaveVerb{%
1368 \begingroup
1369 \FV@UseInlineKeyValues\FV@UseKeyValues
1370 \ifFV@extra
1371 \expandafter\endgroup\expandafter\FVC@SaveVerb@Extra
1372 \else
1373 \expandafter\endgroup\expandafter\FVC@SaveVerb@FV
1374 \fi}

```

\FVC@SaveVerb@Extra

In addition to following the \Verb implementation, this saves a raw version of the text to allow retokenize with \UseVerb. The raw version is also used for conversion to a PDF string if that is needed.

```

1375 \def\FVC@SaveVerb@Extra#1{%
1376 \@namedef{FV@SV@#1}{}%
1377 \@namedef{FV@SVRaw@#1}{}%
1378 \begingroup
1379 \ifbool{FV@vargsingleline}%
1380 {\let\FV@Reader\FVExtraReadVArgSingleLine}%
1381 {\let\FV@Reader\FVExtraReadVArg}%
1382 \FV@Reader{%
1383 \FVC@SaveVerb@Extra@i{#1}}

```

```

\FVC@SaveVerb@Extra@i
1384 \def\FVC@SaveVerb@Extra@i#1#2{%
1385 \FV@UseInlineKeyValues\FV@UseKeyValues\FV@FormattingPrep
1386 \FVExtraDetokenizeVArg{%
1387 \FVExtraRetokenizeVArg{\FVC@SaveVerb@Extra@i#1}{#2}}{\FV@CatCodes}}{#2}}

```

```

\FVC@SaveVerb@Extra@ii
1388 \def\FVC@SaveVerb@Extra@ii#1#2#3{%
1389 \global\let\FV@AfterSave\FancyVerbAfterSave
1390 \endgroup
1391 \@namedef{FV@SV@#1}{#3}%
1392 \@namedef{FV@SVRaw@#1}{#2}%
1393 \FV@AfterSave}%

```

12.8.5 \UseVerb

This adds support for `\fvinline` and line breaking. It also adds movable argument and PDF string support. A new option `retokenize` is defined that determines whether the typeset output is based on the `commandchars` and `codes` in place when `\SaveVerb` was used (default), or is retokenized under current `commandchars` and `codes`.

FV@retokenize

retokenize

Whether `\UseVerb` uses saved verbatim with its original tokenization, or retokenizes under current `commandchars` and `codes`.

```

1394 \newbool{FV@retokenize}
1395 \define@booleankey{FV}{retokenize}%
1396 {\booltrue{FV@retokenize}}{\boolfalse{FV@retokenize}}

```

\UseVerb

```

1397 \def\UseVerb{%
1398 \FVExtraRobustCommand\RobustUseVerb\FVExtraUseVerbUnexpandedReadStarOArgMArg}

```

\RobustUseVerb

```

1399 \protected\def\RobustUseVerb{\FV@Command}{\UseVerb}}
1400 \FVExtrapdfstringdefDisableCommands{%
1401 \def\RobustUseVerb{}}

```

\FVC@UseVerb@FV

```

1402 \let\FVC@UseVerb@FV\FVC@UseVerb

```

\FVC@UseVerb

```

1403 \def\FVC@UseVerb{%
1404 \begingroup
1405 \FV@UseInlineKeyValues\FV@UseKeyValues
1406 \ifFV@extra
1407 \expandafter\endgroup\expandafter\FVC@UseVerb@Extra
1408 \else
1409 \expandafter\endgroup\expandafter\FVC@UseVerb@FV
1410 \fi}

```

`\FVC@UseVerb@Extra`

```
1411 \def\FVC@UseVerb@Extra#1{%
1412   \@ifundefined{FV@SV@#1}%
1413   {\FV@Error{Short verbatim text never saved to name `#1'}\FV@eha}%
1414   {\begingroup
1415     \FV@UseInlineKeyValues\FV@UseKeyValues\FV@FormattingPrep
1416     \ifbool{FV@retokenize}%
1417     {\expandafter\let\expandafter\FV@Tmp\csname FV@SVRaw@#1\endcsname
1418      \expandafter\FV@UseVerb@Extra@Retok\expandafter{\FV@Tmp}}%
1419     {\expandafter\let\expandafter\FV@Tmp\csname FV@SV@#1\endcsname
1420      \expandafter\FV@UseVerb@Extra\expandafter{\FV@Tmp}}}
```

`\FV@UseVerb@Extra@Retok`

```
1421 \def\FV@UseVerb@Extra@Retok#1{%
1422   \FVExtraDetokenizeVArg{%
1423     \FVExtraRetokenizeVArg{\FV@UseVerb@Extra}{\FV@CatCodes}}{#1}}
```

`\FV@UseVerb@Extra`

```
1424 \let\FV@UseVerb@Extra\FVC@Verb@Extra@ii
```

12.9 New commands and environments

12.9.1 `\EscVerb`

This is a variant of `\Verb` in which backslash escapes of the form `\<char>` are used for `<char>`. Backslash escapes are *only* permitted for printable, non-alphanumeric ASCII characters. The argument is read under a normal catcode regime, so any characters that cannot be read under normal catcodes must always be escaped, and the argument must always be delimited by curly braces. This ensures that `\EscVerb` behaves identically whether or not it is used inside another command.

`\EscVerb` is constructed with `\FVExtraRobustCommand` so that it will function correctly after being in an expansion-only context.

`\EscVerb`

Note that while the typeset mandatory argument will be read under normal catcodes, the reader macro for expansion is `\FVExtraUnexpandedReadStar0ArgBescVArg`. This reflects how the argument will be typeset.

```
1425 \def\EscVerb{%
1426   \FVExtraRobustCommand\RobustEscVerb\FVExtraUnexpandedReadStar0ArgBescVArg}
```

`\RobustEscVerb`

```
1427 \protected\def\RobustEscVerb{\FV@Command}{\EscVerb}}
1428 \FVExtrapdfstringdefDisableCommands{%
1429   \def\RobustEscVerb{}}
```

`\FVC@EscVerb`

Delimiting with curly braces is required, so that the command will always behave the same whether or not it has been through expansion.

```
1430 \def\FVC@EscVerb{%
1431   \@ifnextchar\bgroup
1432   {\FVC@EscVerb@i}%
1433   {\PackageError{fvextra}%
1434    {Invalid argument; argument must be delimited by paired curly braces}%
1435    {Delimit argument with curly braces}}}
```

```

\FVC@EscVerb@i
1436 \def\FVC@EscVerb@i#1{%
1437 \begingroup
1438 \FV@UseInlineKeyValues\FV@UseKeyValues\FV@FormattingPrep
1439 \FVExtraDetokenizeREscVArg{%
1440 \FVExtraRetokenizeVArg{\FVC@EscVerb@ii}{\FV@CatCodes}}{#1}}

```

```

\FVC@EscVerb@ii
1441 \let\FVC@EscVerb@ii\FVC@Verb@Extra@ii

```

12.9.2 VerbEnv

Environment variant of `\Verb`. Depending on how this is used in the future, it may be worth improving error message and error recovery functionality, using techniques from `fancyvrb`.

```

\VerbEnv
1442 \def\VerbEnv{%
1443 \ifcsname @currenvir\endcsname
1444 \ifx@currenvir@empty
1445 \PackageError{fvextra}{VerbEnv is an environment}{VerbEnv is an environment}%
1446 \else
1447 \ifx@currenvir\relax
1448 \PackageError{fvextra}{VerbEnv is an environment}{VerbEnv is an environment}%
1449 \fi
1450 \fi
1451 \else
1452 \PackageError{fvextra}{VerbEnv is an environment}{VerbEnv is an environment}%
1453 \fi
1454 \VerbatimEnvironment
1455 \FVExtraRead0ArgBeforeVEnv{\expandafter\VerbEnv@i\expandafter{\FV@EnvironName}}
1456 \def\VerbEnv@i#1#2{%
1457 \begingroup
1458 \let\do\@makeother\FVExtraDoSpecials
1459 \catcode`\ =\active
1460 \catcode`\^I=\active
1461 \catcode`\^M=\active
1462 \VerbEnv@ii{#1}{#2}}
1463 \begingroup
1464 \catcode`\!=0
1465 \catcode`\<=1
1466 \catcode`\>=2
1467 !catcode`\=12
1468 !catcode`\{=12
1469 !catcode`\}=12
1470 !catcode`\^M=!active%
1471 !gdef!VerbEnv@ii#1#2#3^M<%
1472 !endgroup%
1473 !def!VerbEnv@CheckLine##1\end{#1}##2!FV@Sentinel<%
1474 !if!relax!detokenize<##2>!relax%
1475 !else%
1476 !PackageError{fvextra}<Missing environment contents><Missing environment contents>%
1477 !let!VerbEnv@iii!VerbEnv@iii@Error%
1478 !fi>%

```

```

1479 !VerbEnv@CheckLine#3\end{#1}!FV@Sentinel%
1480 !VerbEnv@iii<#1><#2><#3>>%
1481 !endgroup%
1482 \def\VerbEnv@iii@Error#1#2#3{}
1483 \def\VerbEnv@iii#1#2#3{%
1484 \begingroup
1485 \let\do\@makeother\FVExtraDoSpecials
1486 \catcode`\ =10\relax
1487 \catcode`\^M=\active
1488 \VerbEnv@iv{#1}{#2}{#3}}
1489 \begingroup
1490 \catcode`\ !=0
1491 \catcode`\ <=1
1492 \catcode`\ >=2
1493 !catcode`\ =12
1494 !catcode`\ !=12
1495 !catcode`\ !=12
1496 !catcode`\ ^M=\active%
1497 !gdef!VerbEnv@iv#1#2#3#4^M<%
1498 !endgroup%
1499 !def!VerbEnv@CheckEndDelim##1\end{#1}##2!FV@Sentinel<%
1500 !if!relax!detokenize<##2>!relax%
1501 !PackageError<fvextra><Missing end for environment !FV@EnvironName><Add environment en
1502 !let!VerbEnv@v!VerbEnv@v@Error%
1503 !else%
1504 !VerbEnv@CheckEndLeading##1!FV@Sentinel%
1505 !VerbEnv@CheckEndTrailing##2!FV@Sentinel%
1506 !fi>%
1507 !def!VerbEnv@CheckEndTrailing##1\end{#1}!FV@Sentinel<%
1508 !if!relax!detokenize<##1>!relax%
1509 !else%
1510 !PackageError<fvextra>%
1511 <Discarded text after end of environment !FV@EnvironName>%
1512 <Discarded text after end of environment !FV@EnvironName>%
1513 !let!VerbEnv@v!VerbEnv@v@Error%
1514 !fi>%
1515 !VerbEnv@CheckEndDelim#4\end{#1}!FV@Sentinel%
1516 !VerbEnv@v<#2><#3>>%
1517 !endgroup
1518 \def\VerbEnv@CheckEndLeading{%
1519 \FVExtra@ifnextcharAny\@sptoken%
1520 {\VerbEnv@CheckEndLeading@Continue}%
1521 {\ifx\@let@token\FV@Sentinel
1522 \expandafter\VerbEnv@CheckEndLeading@End
1523 \else
1524 \expandafter\VerbEnv@CheckEndLeading@EndError
1525 \fi}}
1526 \def\VerbEnv@CheckEndLeading@Continue#1{%
1527 \VerbEnv@CheckEndLeading}
1528 \def\VerbEnv@CheckEndLeading@End#1\FV@Sentinel{}
1529 \def\VerbEnv@CheckEndLeading@EndError{%
1530 \PackageError{fvextra}%
1531 {Discarded text before end of environment \FV@EnvironName}%
1532 {Discarded text before end of environment \FV@EnvironName}%

```

```

1533 \let\VerbEnv@v\VerbEnv@v@Error}
1534 \def\VerbEnv@v@Error#1#2{}
1535 \def\VerbEnv@v#1#2{%
1536 \Verb[#1]{#2}%
1537 \expandafter\end\expandafter{\FV@EnvironName}}

```

`\endVerbEnv`

```

1538 \def\endVerbEnv{\global\let\FV@EnvironName\relax}

```

12.9.3 VerbatimWrite

This environment writes its contents to a file verbatim. Differences from `fancyvrb`'s `VerbatimOut`:

- Multiple `VerbatimWrite` environments can write to the same file. The file is set via the `writefilehandle` option. This does mean that the user is responsible for creating a new file handle via `\newwrite` and then ideally invoking `\closeout` at the appropriate time.
- By default, text is really written verbatim. This is accomplished by a combination of setting catcodes to 12 (other) and `\detokenize`. This can be customized using the new `writer` option, which defines a macro that performs any processing on each line before writing it to file. By default, all `fancyvrb` options except for `VerbatimWrite`-specific options are ignored. This can be customized on a per-environment basis via environment optional arguments.

`writefilehandle`

`\FancyVerbWriteFileHandle`

Set file handle for `VerbatimWrite`.

```

1539 \define@key{FV}{writefilehandle}{%
1540 \FV@SetWrite#1\FV@Sentinel}
1541 \def\FV@SetWrite#1#2\FV@Sentinel{%
1542 \let\FancyVerbWriteFileHandle\relax
1543 \if\relax\detokenize{#2}\relax
1544 \let\FancyVerbWriteFileHandle#1\relax
1545 \fi
1546 \ifx\FancyVerbWriteFileHandle\relax
1547 \PackageError{fvextra}%
1548 {Missing or invalid file handle for write}%
1549 {Need file handle from \string\newwrite}%
1550 \fi}
1551 \let\FancyVerbWriteFileHandle\relax

```

`writer`

`\FV@Writer`

Define `writer` macro that processes each line before writing.

```

1552 \define@key{FV}{writer}{%
1553 \let\FV@Writer#1\relax}
1554 \def\FancyVerbDefaultWriter#1{%
1555 \immediate\write\FancyVerbWriteFileHandle{\detokenize{#1}}}
1556 \fvset{writer=\FancyVerbDefaultWriter}

```

VerbatimWrite

The environment implementation follows standard `fancyvrb` environment style.

A special write counter is used to track line numbers while avoiding incrementing the regular counter that is used for typeset code. Some macros do nothing with the default `writer`, but are needed to enable `fancyvrb` options when a custom `writer` is used in conjunction with optional environment arguments. These include `\FancyVerbDefineActive`, `\FancyVerbFormatCom`, and `\FV@DefineTabOut`.

```
1557 \newcounter{FancyVerbWriteLine}
1558 \def\VerbatimWrite{%
1559   \FV@Environment
1560   {codes=,commandchars=none,commentchar=none,defineactive,%,
1561     gobble=0,formatcom=,firstline,lastline}%
1562   {VerbatimWrite}}
1563 \def\FVB@VerbatimWrite{%
1564   \@bsphack
1565   \begingroup
1566   \setcounter{FancyVerbWriteLine}{0}%
1567   \let\c@FancyVerbLine\c@FancyVerbWriteLine
1568   \FV@UseKeyValues
1569   \FV@DefineWhiteSpace
1570   \def\FV@Space{\space}%
1571   \FV@DefineTabOut
1572   \let\FV@ProcessLine\FV@Writer
1573   \let\FV@FontScanPrep\relax
1574   \let\@noligs\relax
1575   \FancyVerbDefineActive
1576   \FancyVerbFormatCom
1577   \FV@Scan}
1578 \def\FVE@VerbatimWrite{%
1579   \endgroup
1580   \@esphack}
1581 \def\endVerbatimWrite{\FVE@VerbatimWrite}
```

12.9.4 VerbatimBuffer

This environment stores its contents verbatim in a “buffer,” a sequence of numbered macros each of which contains one line of the environment. The “buffered” lines can then be looped over for further processing or later use.

By default, all `fancyvrb` options except for `VerbatimBuffer`-specific options are ignored. This can be customized on a per-environment basis via environment optional arguments.

afterbuffer

\FV@afterbuffer

Macro that is inserted after the last line of the environment is buffered, immediately before the environment ends.

```
1582 \define@key{FV}{afterbuffer}{%
1583   \def\FV@afterbuffer{#1}}
1584 \fvset{afterbuffer=}
```

\FancyVerbBufferIndex

Current index in buffer during buffering. This is given a `FancyVerb*` macro name since it may be accessed by the user in defining custom `bufferer`.

```
1585 \def\FancyVerbBufferIndex{0}
```

bufferer

\FV@Bufferer

\FancyVerbDefaultBufferer

This is the macro that adds lines to the buffer. The default is designed to create a truly verbatim buffer via `\detokenize`.

```
1586 \define@key{FV}{bufferer}{%
1587   \let\FV@Bufferer=#1\relax}
1588 \def\FancyVerbDefaultBufferer#1{%
1589   \expandafter\xdef\csname\FancyVerbBufferLineName\FancyVerbBufferIndex\endcsname{%
1590     \detokenize{#1}}
1591 \fvset{bufferer=\FancyVerbDefaultBufferer}
```

bufferlengthname

\FancyVerbBufferLengthName

Name of macro storing the length of the buffer.

```
1592 \define@key{FV}{bufferlengthname}{%
1593   \ifcsname#1\endcsname
1594   \else
1595     \expandafter\xdef\csname#1\endcsname{0}%
1596   \fi
1597 \def\FancyVerbBufferLengthName#1{%
1598   \expandafter\def\expandafter\FV@bufferlengthmacro\expandafter{%
1599     \csname#1\endcsname}}
1600 \fvset{bufferlengthname=FancyVerbBufferLength}
```

bufferlinename

\FancyVerbBufferLineName

Base name of buffer line macros. This is given a `\FancyVerb*` macro name since it may be accessed by the user in defining custom `bufferer`.

```
1601 \define@key{FV}{bufferlinename}{%
1602   \def\FancyVerbBufferLineName{#1}}
1603 \fvset{bufferlinename=FancyVerbBufferLine}
```

buffername

Shortcut for setting `bufferlengthname` and `bufferlinename`.

```
1604 \define@key{FV}{buffername}{%
1605   \fvset{bufferlengthname=#1length,bufferlinename=#1line}}
```

globalbuffer

FV@globalbuffer

Whether buffer line macros and the buffer length macro are defined globally.

```
1606 \newbool{FV@globalbuffer}
1607 \define@booleankey{FV}{globalbuffer}%
1608   {\booltrue{FV@globalbuffer}}%
1609   {\boolfalse{FV@globalbuffer}}
1610 \fvset{globalbuffer=false}
```

VerbatimBuffer

The environment implementation follows standard `fancyvrb` environment style.

A special buffer counter is used to track line numbers while avoiding incrementing the regular counter that is used for typeset code. Some macros do nothing with the default `bufferer`, but are needed to enable `fancyvrb` options when a custom `bufferer` is used in conjunction with optional environment arguments.

These include `\FancyVerbDefineActive` and `\FancyVerbFormatCom`. Since counters are global, the exact location of the `\setcounter` commands at the end of the environment relative to `\begingroup... \endgroup` is not important.

```

1611 \newcounter{FancyVerbBufferLine}
1612 \def\FancyVerbBufferDepth{0}
1613 \def\VerbatimBuffer{%
1614   \FV@Environment
1615   {codes=,commandchars=none,commentchar=none,defineactive,%,
1616     gobble=0,formatcom=,firstline,lastline}%
1617   {VerbatimBuffer}}
1618 \def\FVB@VerbatimBuffer{%
1619   \@bsphack
1620   \xdef\FancyVerbBufferDepth{\the\numexpr\FancyVerbBufferDepth+1\relax}%
1621   \begingroup
1622   \FV@UseKeyValues
1623   \setcounter{FancyVerbBufferLine}{\FV@bufferlengthmacro}%
1624   \let\c@FancyVerbLine\c@FancyVerbBufferLine
1625   \xdef\FancyVerbBufferIndex{\FV@bufferlengthmacro}%
1626   \ifbool{FV@globalbuffer}%
1627     {}%
1628     {\expandafter\xdef\csname FV@setbufferlocalscopevars\FancyVerbBufferDepth\endcsname{%
1629       \unexpanded{\def\FV@oldbufferlength}%
1630         {\FV@bufferlengthmacro}%
1631       \unexpanded{\def\FV@bufferlengthmacro}%
1632         {\unexpanded\expandafter{\FV@bufferlengthmacro}}}%
1633       \unexpanded{\def\FancyVerbBufferLineName}%
1634         {\unexpanded\expandafter{\FancyVerbBufferLineName}}}}}%
1635   \ifx\FV@afterbuffer\@empty
1636   \else
1637     \ifx\FV@afterbuffer\relax
1638     \else
1639       \expandafter\global\expandafter
1640       \let\csname FV@afterbuffer\FancyVerbBufferDepth\endcsname\FV@afterbuffer
1641     \fi
1642   \fi
1643   \FV@DefineWhiteSpace
1644   \def\FV@ProcessLine{%
1645     \xdef\FancyVerbBufferIndex{\the\numexpr\FancyVerbBufferIndex+1\relax}%
1646     \FV@Bufferer}%
1647   \let\FV@FontScanPrep\relax
1648   \let\@noligs\relax
1649   \FancyVerbDefineActive
1650   \FancyVerbFormatCom
1651   \FV@Scan}
1652 \def\FVE@VerbatimBuffer{%
1653   \expandafter\xdef\FV@bufferlengthmacro{\FancyVerbBufferIndex}%
1654   \gdef\FancyVerbBufferIndex{0}%
1655   \endgroup
1656   \@esphack
1657   \ifcsname FV@afterbuffer\FancyVerbBufferDepth\endcsname
1658     \begingroup
1659     \csname FV@afterbuffer\FancyVerbBufferDepth\endcsname
1660   \endgroup
1661   \expandafter\global\expandafter

```

```

1662     \let\csname FV@afterbuffer\FancyVerbBufferDepth\endcsname\FV@Undefined
1663 \fi
1664 \ifcsname FV@setbufferlocalscopevars\FancyVerbBufferDepth\endcsname
1665   \begingroup
1666   \csname FV@setbufferlocalscopevars\FancyVerbBufferDepth\endcsname
1667   \loop\unless\ifnum\FV@bufferlengthmacro=\FV@oldbufferlength\relax
1668     \expandafter\global\expandafter
1669     \let\csname\FancyVerbBufferLineName\FV@bufferlengthmacro\endcsname\FV@Undefined
1670     \expandafter\xdef\FV@bufferlengthmacro{%
1671       \the\numexpr\FV@bufferlengthmacro-1\relax}%
1672   \repeat
1673 \endgroup
1674 \expandafter\global\expandafter
1675   \let\csname FV@setbufferlocalscopevars\FancyVerbBufferDepth\endcsname\FV@Undefined
1676 \fi
1677 \xdef\FancyVerbBufferDepth{\the\numexpr\FancyVerbBufferDepth-1\relax}}
1678 \def\endVerbatimBuffer{\FVE@VerbatimBuffer}

```

12.9.5 \VerbatimInsertBuffer

\VerbatimInsertBuffer

insertenvname

This inserts an existing buffer created with `VerbatimBuffer` as a verbatim environment. By default, the inserted environment is `Verbatim`; this can be modified with the option `insertenvname` to any `Verbatim`- or `BVerbatim`-based environment, or any environment with a compatible implementation. The `Verbatim` and `BVerbatim` internals are customized to function with a buffer in a command context.

Notes on the implementation of `\VerbatimInsertBuffer@i`:

- The active \sim M allows a verbatim environment to read optional arguments in the usual way, without requiring modifications to argument-reading macros.
- The `\begingroup\fvset{#1}\global\let\FV@CurrentVerbatimInsertEnvName...` is used to extract any `insertenvname` setting from optional arguments. Most optional arguments apply to the verbatim environment or to the customized verbatim internals that are invoked within it. However, `insertenvname` is needed earlier to determine which verbatim environment is in use. It is not possible simply to use `\fvset{#1}` before the verbatim environment to apply all settings, because that would conflict with the precedence of option processing in `\FV@Environment`.

```

1679 \define@key{FV}{insertenvname}{%
1680   \def\FV@VerbatimInsertEnvName{#1}}
1681 \fvset{insertenvname=Verbatim}
1682 \def\FV@Environment@InsertBuffer#1#2{%
1683   \def\FV@KeyValues{#1}%
1684   \FV@GetKeyValues{\@nameuse{FVB@#2}}}}
1685 \def\FV@Scan@InsertBuffer{%
1686   \FV@CatCodes
1687   \xdef\FV@EnvironName{\FV@VerbatimInsertEnvName}%
1688   \ifnum\FV@bufferlengthmacro=\z@ \relax
1689     \PackageError{fvextra}%

```

```

1690     {Buffer length macro \expandafter\string\FV@bufferlengthmacro\space
1691     is invalid or zero}%
1692     {}%
1693     \let\FV@GetLine\relax
1694     \fi
1695     \FV@BeginScanning}%
1696 \def\VerbatimInsertBuffer@def@FV@Line#1{%
1697   \FV@ExtraRetokenizeVArg{\def\FV@Line}{-}{#1}}
1698 \def\FancyVerbGetLine@VerbatimInsertBuffer{%
1699   \ifnum\FancyVerbBufferIndex>\FV@bufferlengthmacro\relax
1700     \global\let\FV@Environment\relax
1701     \let\next\relax
1702   \else
1703     \ifcsname\FancyVerbBufferLineName\FancyVerbBufferIndex\endcsname
1704       \expandafter\let\expandafter\FV@Line@Buffer
1705       \csname\FancyVerbBufferLineName\FancyVerbBufferIndex\endcsname
1706       \expandafter\VerbatimInsertBuffer@def@FV@Line\expandafter{\FV@Line@Buffer}%
1707       \def\next{\FV@PreProcessLine\FV@GetLine}%
1708       \xdef\FancyVerbBufferIndex{\the\numexpr\FancyVerbBufferIndex+1\relax}%
1709     \else
1710       \def\next{%
1711         \PackageError{fvextra}%
1712         {Buffer with line macro named
1713          "\FancyVerbBufferLineName\FancyVerbBufferIndex" does not exist}%
1714         {Check bufferlinename, bufferlengthname, and globalbuffer settings}%
1715       }%
1716     \fi
1717   \fi
1718   \next}
1719 \newcommand{\VerbatimInsertBuffer}[1] [] {%
1720   \begingroup
1721   \let\FV@Scan\FV@Scan@InsertBuffer
1722   \let\FV@CheckScan\relax
1723   \let\FV@Environment\FV@Environment@InsertBuffer
1724   \let\FancyVerbGetLine\FancyVerbGetLine@VerbatimInsertBuffer
1725   \gdef\FancyVerbBufferIndex{1}%
1726   \VerbatimInsertBuffer@i{#1}%
1727   \gdef\FancyVerbBufferIndex{0}%
1728   \endgroup
1729   \@doendpe}
1730 \begingroup
1731 \catcode`\^^M=\active
1732 \gdef\VerbatimInsertBuffer@i#1{%
1733   \begingroup%
1734   \fvset{#1}%
1735   \global\let\FV@CurrentVerbatimInsertEnvName\FV@VerbatimInsertEnvName%
1736   \endgroup%
1737   \csname\FV@CurrentVerbatimInsertEnvName\endcsname[#1]^^M%
1738   \csname end\FV@CurrentVerbatimInsertEnvName\endcsname%
1739   \global\let\FV@CurrentVerbatimInsertEnvName\FV@Undefined}%
1740 \endgroup

```

12.9.6 `\VerbatimClearBuffer`

`\VerbatimClearBuffer`

Clear an existing buffer.

```
1741 \newcommand{\VerbatimClearBuffer}[1] [] {%
1742   \begingroup
1743   \def\FV@KeyValues{#1}%
1744   \FV@UseKeyValues
1745   \xdef\FancyVerbBufferIndex{\FV@bufferlengthmacro}%
1746   \expandafter\xdef\FV@bufferlengthmacro{0}%
1747   \loop\unless\ifnum\FancyVerbBufferIndex<1\relax
1748     \expandafter\global\expandafter\let
1749     \csname\FancyVerbBufferLineName\FancyVerbBufferIndex\endcsname
1750     \FV@Undefined
1751     \xdef\FancyVerbBufferIndex{\the\numexpr\FancyVerbBufferIndex-1\relax}%
1752   \repeat
1753   \gdef\FancyVerbBufferIndex{0}%
1754   \endgroup}
```

12.9.7 `\InsertBuffer`

`\InsertBuffer`

`wrapperenvname`

`wrapperenvopt`

`wrapperenvarg`

This inserts an existing buffer created with `VerbatimBuffer` so that it is interpreted as \LaTeX . The result is essentially the same as if the buffered text had been included literally at the insertion point.

```
1755 \define@key{FV}{wrapperenvname}{%
1756   \def\FV@WrapperEnvName{#1}%
1757   \ifx\FV@WrapperEnvName\@empty
1758     \let\FV@WrapperEnvName\relax
1759   \fi}
1760 \fvset{wrapperenvname=}
1761 \define@key{FV}{wrapperenvopt}{%
1762   \def\FV@WrapperEnvOpt{#1}%
1763   \ifx\FV@WrapperEnvOpt\@empty
1764     \let\FV@WrapperEnvOpt\relax
1765   \fi}
1766 \fvset{wrapperenvopt=}
1767 \define@key{FV}{wrapperenvarg}{%
1768   \def\FV@WrapperEnvArg{#1}%
1769   \ifx\FV@WrapperEnvArg\@empty
1770     \let\FV@WrapperEnvArg\relax
1771   \fi}
1772 \fvset{wrapperenvarg=}
1773 \newcommand{\InsertBuffer}[1] [] {%
1774   \begingroup
1775   \def\FV@KeyValues{#1}%
1776   \FV@UseKeyValues
1777   \ifnum\FV@bufferlengthmacro<1
1778     \expandafter\endgroup\expandafter\@gobble
1779   \else
```

```

1780     \expandafter\@firstofone
1781     \fi
1782     \InsertBuffer@i}
1783 \def\InsertBuffer@i{%
1784   \InsertBuffer@expandbuffer
1785   \expandafter\endgroup\expandafter\scantokens\expandafter{%
1786     \FV@expandedbuffer\noexpand}\relax}
1787 \def\InsertBuffer@expandbuffer{%
1788   \edef\FV@expandedbuffer{%
1789     \ifx\FV@WrapperEnvName\relax
1790     \else
1791       \unexpanded\expandafter\expandafter\expandafter{%
1792         \expandafter\string\expandafter\begin\expandafter{\FV@WrapperEnvName}}%
1793       \ifx\FV@WrapperEnvOpt\relax
1794       \else
1795         \unexpanded\expandafter{\expandafter[\FV@WrapperEnvOpt]}%
1796       \fi
1797       \ifx\FV@WrapperEnvArg\relax
1798       \else
1799         \unexpanded\expandafter{\expandafter{\FV@WrapperEnvArg}}%
1800       \fi
1801       \unexpanded{^^J}%
1802     \fi
1803     \InsertBuffer@expandbufferlines{1}%
1804     \ifx\FV@WrapperEnvName\relax
1805       \unskip
1806     \else
1807       \unexpanded\expandafter\expandafter\expandafter{%
1808         \expandafter\string\expandafter\end\expandafter{\FV@WrapperEnvName}^^J}%
1809     \fi}}
1810 \def\InsertBuffer@expandbufferlines#1{%
1811   \unexpanded\expandafter\expandafter\expandafter{%
1812     \csname\FancyVerbBufferLineName#1\endcsname^^J}%
1813   \ifnum\FV@bufferlengthmacro=#1
1814     \expandafter\@gobble
1815   \else
1816     \expandafter\@firstofone
1817   \fi
1818   {\expandafter\InsertBuffer@expandbufferlines\expandafter{\the\numexpr#1+1\relax}}}

```

12.9.8 \ClearBuffer

\ClearBuffer

Clear an existing buffer. Alias for \VerbatimClearBuffer.

```
1819 \let\ClearBuffer\VerbatimClearBuffer
```

12.9.9 \BufferMdfivesum

\BufferMdfivesum

Calculate the MD5 sum of the current buffer.

```

1820 \def\BufferMdfivesum{%
1821   \csname str_mdfive_hash:e\endcsname{%
1822     \ifnum\FV@bufferlengthmacro<1

```

```

1823     \expandafter\@gobble
1824     \else
1825     \expandafter\@firstofone
1826     \fi
1827     {\BufferMdfivesum@i{1}}}}
1828 \def\BufferMdfivesum@i#1{%
1829   \csname\FancyVerbBufferLineName#1\endcsname^^J%
1830   \ifnum\FV@bufferlengthmacro=#1
1831     \expandafter\@gobble
1832   \else
1833     \expandafter\@firstofone
1834   \fi
1835   {\expandafter\BufferMdfivesum@i\expandafter{\the\numexpr#1+1\relax}}}}

```

12.9.10 \IterateBuffer, \IterateBufferBreak

\IterateBuffer

\IterateBufferBreak

Loop over buffer, applying a macro to each line.

```

1836 \newcommand{\IterateBuffer}[2] [] {%
1837   \if\relax\detokenize{#1}\relax
1838   \else
1839     \let\FancyVerbBufferLengthName@beforeiter\FancyVerbBufferLengthName
1840     \let\FV@bufferlengthmacro@beforeiter\FV@bufferlengthmacro
1841     \let\FancyVerbBufferLineName@beforeiter\FancyVerbBufferLineName
1842     \begingroup
1843     \def\FV@KeyValues{#1}%
1844     \FV@UseKeyValues
1845     \global\let\FancyVerbBufferLengthName@iter\FancyVerbBufferLengthName
1846     \global\let\FV@bufferlengthmacro@iter\FV@bufferlengthmacro
1847     \global\let\FancyVerbBufferLineName@iter\FancyVerbBufferLineName
1848     \endgroup
1849     \let\FancyVerbBufferLengthName\FancyVerbBufferLengthName@iter
1850     \let\FV@bufferlengthmacro\FV@bufferlengthmacro@iter
1851     \let\FancyVerbBufferLineName\FancyVerbBufferLineName@iter
1852     \global\let\FancyVerbBufferLengthName@iter\FV@Undefined
1853     \global\let\FV@bufferlengthmacro@iter\FV@Undefined
1854     \global\let\FancyVerbBufferLineName@iter\FV@Undefined
1855   \fi
1856   \gdef\FancyVerbBufferIndex{1}%
1857   \def\FV@IterateBuffer@cmd{#2}%
1858   \def\IterateBufferBreak{\xdef\FancyVerbBufferIndex{\FV@bufferlengthmacro}}%
1859   \loop\unless\ifnum\FancyVerbBufferIndex>\FV@bufferlengthmacro\relax
1860     \expandafter\let\expandafter\FV@IterateBuffer@line
1861     \csname\FancyVerbBufferLineName\FancyVerbBufferIndex\endcsname
1862     \expandafter\FV@IterateBuffer@cmd\expandafter{\FV@IterateBuffer@line}%
1863     \xdef\FancyVerbBufferIndex{\the\numexpr\FancyVerbBufferIndex+1\relax}%
1864   \repeat
1865   \gdef\FancyVerbBufferIndex{0}%
1866   \let\FV@IterateBuffer@cmd\FV@Undefined
1867   \let\IterateBufferBreak\FV@Undefined
1868   \let\FV@IterateBuffer@line\FV@Undefined
1869   \if\relax\detokenize{#1}\relax
1870   \else

```

```

1871 \let\FancyVerbBufferLengthName\FancyVerbBufferLengthName@beforeiter
1872 \let\FV@bufferlengthmacro\FV@bufferlengthmacro@beforeiter
1873 \let\FancyVerbBufferLineName\FancyVerbBufferLineName@beforeiter
1874 \let\FancyVerbBufferLengthName@beforeiter\FV@Undefined
1875 \let\FV@bufferlengthmacro@beforeiter\FV@Undefined
1876 \let\FancyVerbBufferLineName@beforeiter\FV@Undefined
1877 \fi}

```

`\WriteBuffer`

Buffer equivalent of `VerbatimWrite`.

```

1878 \def\WriteBuffer{%
1879   \FV@Command{}{WriteBuffer}}
1880 \def\FVC@WriteBuffer{%
1881   \@bsphack
1882   \begingroup
1883   \setcounter{FancyVerbWriteLine}{0}%
1884   \let\c@FancyVerbLine\c@FancyVerbWriteLine
1885   \FV@UseKeyValues
1886   \FV@DefineWhiteSpace
1887   \def\FV@Space{\space}%
1888   \FV@DefineTabOut
1889   \gdef\FancyVerbBufferIndex{1}%
1890   \loop\unless\ifnum\FancyVerbBufferIndex>\FV@bufferlengthmacro\relax
1891     \stepcounter{FancyVerbWriteLine}%
1892     \expandafter\let\expandafter\FV@WriteBuffer@line
1893     \csname\FancyVerbBufferLineName\FancyVerbBufferIndex\endcsname
1894     \expandafter\FV@Writer\expandafter{\FV@WriteBuffer@line}%
1895     \xdef\FancyVerbBufferIndex{\the\numexpr\FancyVerbBufferIndex+1\relax}%
1896   \repeat
1897   \gdef\FancyVerbBufferIndex{0}%
1898   \endgroup
1899   \@esphack}

```

12.10 Patches

12.10.1 Delimiting characters for verbatim commands

Unlike `\verb`, `fancyvrb`'s commands like `\Verb` cannot take arguments delimited by characters like `#` and `%` due to the way that starred commands and optional arguments are implemented. The relevant macros are redefined to make this possible.

`fancyvrb`'s `\Verb` is actually implemented in `\FVC@Verb`. This is invoked by a helper macro `\FV@Command` which allows versions of commands with customized options:

$$\FV@Command\{*customized_options*\}\{*base_command_name*\}$$

`\Verb` is then defined as `\def\Verb{\FV@Command{}{Verb}}`. The definition of `\FV@Command` (and `\FV@@Command` which it uses internally) involves looking ahead for a star `*` (`\@ifstar`) and for a left square bracket `[` that delimits an optional argument (`\@ifnextchar`). As a result, the next character is tokenized under the current, normal catcode regime. This prevents `\Verb` from being able to use delimiting characters like `#` and `%` that work with `\verb`.

`\FV@Command` and `\FV@@Command` are redefined so that this lookahead tokenizes under a typical verbatim catcode regime (with one exception that is explained below). This enables `\verb`-style delimiters. This does not account for any custom catcode changes introduced by `\fvset`, customized commands, or optional arguments. However, delimiting characters should never need custom catcodes, and both the `fancyvrb` definition of `\Verb` (when not used inside another macro) as well as the `fvextra` reimplementations (in all cases) handle the possibility of delimiters with valid but non-typical catcodes. Other, non-verbatim commands that use `\FV@Command`, such as `\UseVerb`, are not affected by the patch.

The catcode regime for lookahead has one exception to a typical verbatim catcode regime: The curly braces `{}` retain their normal codes. This allows the `fvextra` reimplementations of `\Verb` to use a pair of curly braces as delimiters, which can be convenient when `\Verb` is used within another command. Since the original `fancyvrb` implementation of `\Verb` with unpatched `\FV@Command` is incompatible with curly braces being used as delimiters in any form, this does not affect any pre-existing `fancyvrb` functionality.

`\FV@Command`

```
1900 \def\FV@Command#1#2{%
1901   \FVExtra@ifstarVArg
1902   {\def\FV@KeyValues{#1,showspaces,showtabs}\FV@@Command{#2}}%
1903   {\def\FV@KeyValues{#1}\FV@@Command{#2}}}
```

`\FV@@Command`

```
1904 \def\FV@@Command#1{%
1905   \FVExtra@ifnextcharVArg[%
1906     {\FV@GetKeyValues{\@nameuse{FVC@#1}}}%
1907     {\@nameuse{FVC@#1}}}
```

12.10.2 `\CustomVerbatimCommand` compatibility with `\FVExtraRobustCommand`

`\@CustomVerbatimCommand`

#1 is `\newcommand` or `\renewcommand`, #2 is the (re)new command, #3 is the base `fancyvrb` command, #4 is options.

```
1908 \def\@CustomVerbatimCommand#1#2#3#4{%
1909   \begingroup\fvset{#4}\endgroup
1910   \@ifundefined{FVC@#3}%
1911     {\FV@Error{Command `'\string#3' is not a FancyVerb command.}\@eha}%
1912     {\ifcsname Robust#3\endcsname
1913       \expandafter\@firstoftwo
1914       \else
1915         \expandafter\@secondoftwo
1916         \fi
1917     {\expandafter\let\expandafter\@tempa\csname #3\endcsname
1918       \def\@tempb##1##2##3{%
1919         \expandafter\def\expandafter\@tempc\expandafter{%
1920           \csname Robust\expandafter\@gobble\string#2\endcsname}%
1921         \def\@tempd###1{%
1922           #1{#2}{##1###1##3}}%
1923         \expandafter\@tempd\@tempc
1924         \expandafter\protected\expandafter\def\@tempc{\FV@Command{#4}{#3}}}%
1925       \expandafter\@tempb\@tempa}%
1926     {#1{#2}{\FV@Command{#4}{#3}}}}
```

12.10.3 Visible spaces

`\FancyVerbSpace`

The default definition of visible spaces (`showspaces=true`) could allow font commands to escape under some circumstances, depending on how it is used:

```
{\catcode`\ =12 \gdef\FancyVerbSpace{\tt }}
```

`\textvisiblespace` is not an alternative because it does not have the correct width. The redefinition follows <https://tex.stackexchange.com/a/120231/10742>.

```
1927 \def\FancyVerbSpace{%
1928   \makebox[0.5em]{%
1929     \kern.07em
1930     \vrule height.3ex
1931     \hrulefill
1932     \vrule height.3ex
1933     \kern.07em}}
```

12.10.4 obeytabs with visible tabs and with tabs inside macro arguments

`\FV@TrueTab` governs tab appearance when `obeytabs=true` and `showtabs=true`. It is redefined so that symbols with flexible width, such as `\rightarrowfill`, will work as expected. In the original `fancyvrb` definition, `\kern\@tempdima\hbox to\z@{...}`. The `\kern` is removed and instead the `\hbox` is given the width `\@tempdima`.

`\FV@TrueTab` and related macros are also modified so that they function for tabs inside macro arguments when `obeytabs=true` (inside curly braces `{}` with their normal meaning, when using `commandchars`, etc.). The `fancyvrb` implementation of tab expansion assumes that tabs are never inside a group; when a group that contains a tab is present, the entire line typically vanishes. The new implementation keeps the `fancyvrb` behavior exactly for tabs outside groups; they are perfectly expanded to tab stops. Tabs inside groups cannot be perfectly expanded to tab stops, at least not using the `fancyvrb` approach. Instead, when `fvextra` encounters a run of whitespace characters (tabs and possibly spaces), it makes the assumption that the nearest tab stop was at the beginning of the run. This gives the correct behavior if the whitespace characters are leading indentation that happens to be within a macro. Otherwise, it will typically not give correct tab expansion—but at least the entire line will not be discarded, and the run of whitespace will be represented, even if imperfectly.

A general solution to tab expansion may be possible, but will almost certainly require multiple compiles, perhaps even one compile (or more) per tab. The `zref` package provides a `\zsaveposx` macro that stores the current x position on the page for subsequent compiles. This macro, or a similar macro from another package, could be used to establish a reference point at the beginning of each line. Then each run of whitespace that contains a tab could have a reference point established at its start, and tabs could be expanded based on the distance between the start of the run and the start of the line. Such an approach would allow the first run of whitespace to measure its distance from the start of the line on the 2nd compile (once both reference points were established), so it would be able expand the first run of whitespace correctly on the 3rd compile. That would allow a second run of whitespace to definitely establish its starting point on the 3rd compile, which would allow it to expand correctly on the 4th compile. And so on. Thus, while it should

be possible to perform completely correct tab expansion with such an approach, it will in general require at least 4 compiles to do better than the current approach. Furthermore, the sketch of the algorithm provided so far does not include any complications introduced by line breaking. In the current approach, it is necessary to determine how each tab would be expanded in the absence of line breaking, save all tab widths, and then expand using saved widths during the actual typesetting with line breaking.

`FV@TrueTabGroupLevel`

Counter for keeping track of the group level (`\currentgrouplevel`) at the very beginning of a line, inside `\FancyVerbFormatLine` but outside `\FancyVerbFormatText`, which is where the tab expansion macro is invoked. This allows us to determine whether we are in a group, and expand tabs accordingly.

```
1934 \newcounter{FV@TrueTabGroupLevel}
```

`\FV@@ObeyTabs`

The `fancyvrb` macro responsible for tab expansion is modified so that it can handle tabs inside groups, even if imperfectly. We need to use a special version of the space, `\FV@Space@ObeyTabs`, that within a group will capture all following spaces or tabs and then insert them with tab expansion based on the beginning of the run of whitespace. We need to record the current group level, but then increment it by 1 because all comparisons will be performed within the `\hbox{...}`. The `\FV@TmpCurrentGroupLevel` is needed for compatibility with the `calc` package, which redefines `\setcounter`.

```
1935 \def\FV@@ObeyTabs#1{%
1936   \let\FV@Space@Orig\FV@Space
1937   \let\FV@Space\FV@Space@ObeyTabs
1938   \edef\FV@TmpCurrentGroupLevel{\the\currentgrouplevel}%
1939   \setcounter{FV@TrueTabGroupLevel}{\FV@TmpCurrentGroupLevel}%
1940   \addtocounter{FV@TrueTabGroupLevel}{1}%
1941   \setbox\FV@TabBox=\hbox{#1}\box\FV@TabBox
1942   \let\FV@Space\FV@Space@Orig}
```

`\FV@TrueTab`

Version that follows `fancyvrb` if not in a group and takes another approach otherwise.

```
1943 \def\FV@TrueTab{%
1944   \ifnum\value{FV@TrueTabGroupLevel}=\the\currentgrouplevel\relax
1945     \expandafter\FV@TrueTab@NoGroup
1946   \else
1947     \expandafter\FV@TrueTab@Group
1948   \fi}
```

`\FV@TrueTabSaveWidth`

When linebreaking is in use, the `fancyvrb` tab expansion algorithm cannot be used directly, since it involves `\hbox`, which doesn't allow for line breaks. In those cases, tab widths will be calculated for the case without breaks and saved, and then saved widths will be used in the actual typesetting. This macro is `\let` to width-saving code in those cases.

```
1949 \let\FV@TrueTabSaveWidth\relax
```

`FV@TrueTabCounter`

Counter for tracking saved tabs.

```
1950 \newcounter{FV@TrueTabCounter}
```

`\FV@TrueTabSaveWidth@Save`

Save the current tab width, then increment the tab counter. `\@tempdima` will hold the current tab width.

```
1951 \def\FV@TrueTabSaveWidth@Save{%
1952   \expandafter\xdef\csname FV@TrueTab:Width\arabic{FV@TrueTabCounter}\endcsname{%
1953     \number\@tempdima}%
1954   \stepcounter{FV@TrueTabCounter}}
```

`\FV@TrueTab@NoGroup`

This follows the `fancyvrb` approach exactly, except for the `\hbox` to `\@tempdima` adjustment and the addition of `\FV@TrueTabSaveWidth`.

```
1955 \def\FV@TrueTab@NoGroup{%
1956   \egroup
1957   \@tempdima=\FV@ObeyTabSize sp\relax
1958   \@tempcnta=\wd\FV@TabBox
1959   \advance\@tempcnta\FV@ObeyTabSize\relax
1960   \divide\@tempcnta\@tempdima
1961   \multiply\@tempdima\@tempcnta
1962   \advance\@tempdima-\wd\FV@TabBox
1963   \FV@TrueTabSaveWidth
1964   \setbox\FV@TabBox=\hbox\bgroup
1965   \unhbox\FV@TabBox\hbox to\@tempdima{\hss\FV@TabChar}}
```

`FV@ObeyTabs@Whitespaces@Tab`

In a group where runs of whitespace characters are collected, we need to keep track of whether a tab has been found, so we can avoid expansion and the associated `\hbox` for spaces without tabs.

```
1966 \newbool{FV@ObeyTabs@Whitespaces@Tab}
```

`\FV@TrueTab@Group`

If in a group, a tab should start collecting whitespace characters for later tab expansion, beginning with itself. The collected whitespace will use `\FV@FVTabToken` and `\FV@FVSpaceToken` so that any `\ifx` comparisons performed later will behave as expected. This shouldn't be strictly necessary, because `\FancyVerbBreakStart` operates with saved tab widths rather than using the tab expansion code directly. But it is safer in case any other unanticipated scanning is going on.

```
1967 \def\FV@TrueTab@Group{%
1968   \booltrue{FV@ObeyTabs@Whitespaces@Tab}%
1969   \gdef\FV@TmpWhitespaces{\FV@FVTabToken}%
1970   \FV@ObeyTabs@ScanWhitespaces}
```

`\FV@Space@ObeyTabs`

Space treatment, like tab treatment, now depends on whether we are in a group, because in a group we want to collect all runs of whitespace and then expand any tabs.

```
1971 \def\FV@Space@ObeyTabs{%
1972   \ifnum\value{FV@TrueTabGroupLevel}=\the\currentgrouplevel\relax
1973     \expandafter\FV@Space@ObeyTabs@NoGroup
1974   \else
1975     \expandafter\FV@Space@ObeyTabs@Group
1976   \fi}
```

`\FV@Space@ObeyTabs@NoGroup`

Fall back to normal space.

```
1977 \def\FV@Space@ObeyTabs@NoGroup{\FV@Space@Orig}
```

`\FV@Space@ObeyTabs@Group`

Make a note that no tabs have yet been encountered, store the current space, then scan for following whitespace.

```
1978 \def\FV@Space@ObeyTabs@Group{%
1979   \boolfalse\FV@ObeyTabs@Whitespace@Tab}%
1980   \gdef\FV@TmpWhitespace{\FV@FVSpaceToken}%
1981   \FV@ObeyTabs@ScanWhitespace}
```

`\FV@ObeyTabs@ScanWhitespace`

Collect whitespace until the end of the run, then process it. Proper lookahead comparison requires `\FV@FVSpaceToken` and `\FV@FVTabToken`.

```
1982 \def\FV@ObeyTabs@ScanWhitespace{%
1983   \ifnextchar\FV@FVSpaceToken%
1984     {\FV@TrueTab@CaptureWhitespace@Space}%
1985     {\ifx\@let@token\FV@FVTabToken
1986       \expandafter\FV@TrueTab@CaptureWhitespace@Tab
1987       \else
1988         \expandafter\FV@ObeyTabs@ResolveWhitespace
1989         \fi}}
1990 \def\FV@TrueTab@CaptureWhitespace@Space#1{%
1991   \g@addto@macro\FV@TmpWhitespace{\FV@FVSpaceToken}%
1992   \FV@ObeyTabs@ScanWhitespace}
1993 \def\FV@TrueTab@CaptureWhitespace@Tab#1{%
1994   \booltrue\FV@ObeyTabs@Whitespace@Tab}%
1995   \g@addto@macro\FV@TmpWhitespace{\FV@FVTabToken}%
1996   \FV@ObeyTabs@ScanWhitespace}
```

`\FV@TrueTab@Group@Expand`

Yet another tab definition, this one for use in the actual expansion of tabs in whitespace. This uses the fancyvrb algorithm, but only over a restricted region known to contain no groups.

```
1997 \newbox\FV@TabBox@Group
1998 \def\FV@TrueTab@Group@Expand{%
1999   \egroup
2000   \@tempdima=\FV@ObeyTabSize sp\relax
2001   \@tempcnta=\wd\FV@TabBox@Group
2002   \advance\@tempcnta\FV@ObeyTabSize\relax
2003   \divide\@tempcnta\@tempdima
2004   \multiply\@tempdima\@tempcnta
2005   \advance\@tempdima-\wd\FV@TabBox@Group
2006   \FV@TrueTabSaveWidth
2007   \setbox\FV@TabBox@Group=\hbox\bgroup
2008   \unhbox\FV@TabBox@Group\hbox to\@tempdima{\hss\FV@TabChar}}
```

`\FV@ObeyTabs@ResolveWhitespace`

Need to make sure the right definitions of the space and tab are in play here. Only do tab expansion, with the associated `\hbox`, if a tab is indeed present.

```
2009 \def\FV@ObeyTabs@ResolveWhitespace{%
2010   \let\FV@Space\FV@Space@Orig
2011   \let\FV@Tab\FV@TrueTab@Group@Expand
2012   \expandafter\FV@ObeyTabs@ResolveWhitespace@i\expandafter{\FV@TmpWhitespace}%
2013   \let\FV@Space\FV@Space@ObeyTabs
2014   \let\FV@Tab\FV@TrueTab}
2015 \def\FV@ObeyTabs@ResolveWhitespace@i#1{%
```

```

2016 \ifbool{FV@ObeyTabs@Whitespace@Tab}%
2017   {\setbox\FV@TabBox@Group=\hbox{#1}\box\FV@TabBox@Group}%
2018   {#1}}

```

12.10.5 Fonts and symbols in math mode

The single quote (') does not become \prime when typeset math is included within verbatim content, due to the definition of the character in `\@noligs`. This patch adds a new definition of the character in math mode, inspired by <http://tex.stackexchange.com/q/223876/10742>. It also redefines other characters in `\@noligs` to behave normally within math mode and switches the default font within math mode, so that `amsmath`'s `\text` will work as expected.

`\FV@pr@m@s`

Define a version of `\pr@m@s` from `latex.ltx` that works with active '. In verbatim contexts, ' is made active by `\@noligs`.

```

2019 \begingroup
2020 \catcode`\'=\active
2021 \catcode`\^=7
2022 \gdef\FV@pr@m@s{%
2023   \ifx'\@let@token
2024     \expandafter\pr@@@s
2025   \else
2026     \ifx^\@let@token
2027       \expandafter\expandafter\expandafter\pr@@@t
2028     \else
2029       \egroup
2030     \fi
2031   \fi}
2032 \endgroup

```

`\FV@SetupMathFont`

Set the font back to default from the verbatim font.

```

2033 \def\FV@SetupMathFont{%
2034   \everymath\expandafter{\the\everymath\fontfamily{\familydefault}\selectfont}}
2035 \g@addto@macro\FV@FormattingPrep@PreHook{\FV@SetupMathFont}

```

`\FV@SetupMathActive`

Make all characters in `\FVExtraDoSpecials` behave more normally within math. This is for `mathscape` or when $\$$ has its normal catcode via `codes`. This does not retokenize, so it can only provide a better approximation of regular math.

At minimum, the characters in `\@noligs` will typically be made `\active` within verbatim contexts to produce literal versions of themselves. The relevant definition from `latex.ltx`:

```
\def\verbatim@nolig@list{\do\` \do\<\do\>\do\, \do\' \do\~}
```

It is also possible that additional characters will be made `\active` to produce literal versions of themselves or for other purposes. These `\active` characters can interfere with math.

The strategy here has three components:

- For a character in `\FVExtraDoSpecials` that is active before the verbatim context begins, save its definition. Then restore this within math via `\everymath`.

- For a character in `\FVExtraDoSpecials` that is not active, but does have a `\mathcode` of "8000, save the active definition. Then via `\everymath` define the active version of this character to give the saved active definition within math mode and a detokenized character otherwise.
- For a character in `\FVExtraDoSpecials` that is not active and does not have a `\mathcode` of "8000, use `\everymath` to define the active version of the character to give a detokenized character.

Detecting a `\mathcode` of "8000 must be done in an engine-dependent manner. Partial reference: <https://tex.stackexchange.com/a/520122/10742>.

Also switch to `\FV@pr@m@s` so that math prime ' behaves as expected.

```

2036 \begingroup
2037 \expandafter\ifx\csname directlua\endcsname\relax
2038 \expandafter\ifx\csname XeTeXrevision\endcsname\relax
2039 \global\let\FV@mathcodenum\mathcode
2040 \gdef\FV@mathcodenumactive{32768}%
2041 \else
2042 \global\let\FV@mathcodenum\Umathcodenum
2043 \gdef\FV@mathcodenumactive{2097151}%
2044 \fi
2045 \else
2046 \global\let\FV@mathcodenum\Umathcodenum
2047 \gdef\FV@mathcodenumactive{16777216}%
2048 \fi
2049 \endgroup
2050 \def\FV@SetupMathActive{%
2051 \def\do##1{%
2052 \ifnum\catcode`##1=\active
2053 \expandafter\expandafter\expandafter\let\expandafter\expandafter\expandafter\FV@Tmp
2054 \csname FV@Char@CatActive:\number`##1\endcsname
2055 \expandafter\let
2056 \csname FV@Char@Math:\number`##1\endcsname\FV@Tmp
2057 \else
2058 \ifnum\FV@mathcodenum`##1=\FV@mathcodenumactive\relax
2059 \expandafter\expandafter\expandafter\let\expandafter\expandafter\expandafter\FV@Tmp
2060 \csname FV@Char@CatActive:\number`##1\endcsname
2061 \expandafter\let
2062 \csname FV@Char@MathActive:\number`##1\endcsname\FV@Tmp
2063 \expandafter
2064 \def\csname FV@Char@Math:\number`##1\endcsname{%
2065 \expandafter\ifmode\expandafter\expandafter
2066 \csname FV@Char@MathActive:\number`##1\endcsname
2067 \else
2068 \expandafter\expandafter
2069 \csname FV@Char@CatDetok:\number`##1\endcsname
2070 \fi}%
2071 \else
2072 \expandafter\let\expandafter\FV@Tmp
2073 \csname FV@Char@CatDetok:\number`##1\endcsname
2074 \expandafter\let
2075 \csname FV@Char@Math:\number`##1\endcsname\FV@Tmp
2076 \fi
2077 \fi}%

```

```

2078 \FVExtraDoSpecials
2079 \everymath\expandafter{%
2080   \the\everymath
2081   \FV@ApplyMathActive}}
2082 \def\FV@ApplyMathActive{%
2083   \let\pr@m@s\FV@pr@m@s
2084   \def\do##1{%
2085     \expandafter\let\expandafter\FV@Tmp
2086       \csname FV@Char@CatActive:\number`##1\endcsname
2087     \expandafter\expandafter\expandafter\let\expandafter\FV@Tmp
2088       \csname FV@Char@Math:\number`##1\endcsname}%
2089   \FVExtraDoSpecials}
2090 \FV@AddToHook\FV@UseKeyValues@Hook{\FV@SetupMathActive}

```

12.10.6 Orphaned label

`\FV@BeginListFrame@Lines`

When `frame=lines` is used with a label, the label can be orphaned. This overwrites the default definition to add `\penalty\@M`. The fix is attributed to <http://tex.stackexchange.com/a/168021/10742>.

```

2091 \def\FV@BeginListFrame@Lines{%
2092   \begingroup
2093   \lineskip\z@skip
2094   \FV@SingleFrameLine{\z@}%
2095   \kern-0.5\baselineskip\relax
2096   \baselineskip\z@skip
2097   \kern\FV@FrameSep\relax
2098   \penalty\@M
2099   \endgroup}

```

12.10.7 `rulecolor` and `fillcolor`

The `rulecolor` and `fillcolor` options are redefined so that they accept color names directly, rather than requiring `\color{<color_name>}`. The definitions still allow the old usage.

`rulecolor`

```

2100 \define@key{FV}{rulecolor}{%
2101   \ifstrempy{#1}%
2102   {\let\FancyVerbRuleColor\relax}%
2103   {\ifstrequal{#1}{none}%
2104     {\let\FancyVerbRuleColor\relax}%
2105     {\def@tempa{#1}%
2106       \FV@KVProcess@RuleColor#1\FV@Undefined}}}
2107 \def\FV@KVProcess@RuleColor#1#2\FV@Undefined{%
2108   \ifx#1\color
2109   \else
2110     \expandafter\def\expandafter@tempa\expandafter{%
2111       \expandafter\color\expandafter{\@tempa}}%
2112   \fi
2113   \let\FancyVerbRuleColor@tempa}
2114 \fvset{rulecolor=none}

```

`fillcolor`

```

2115 \define@key{FV}{fillcolor}{%
2116   \ifstrempy{#1}%
2117   {\let\FancyVerbFillColor\relax}%
2118   {\ifstrequal{#1}{none}%
2119     {\let\FancyVerbFillColor\relax}%
2120     {\def@tempa{#1}%
2121       \FVKVProcess@FillColor#1\FV@Undefined}}}
2122 \def\FVKVProcess@FillColor#1#2\FV@Undefined{%
2123   \ifx#1\color
2124   \else
2125     \expandafter\def\expandafter@tempa\expandafter{%
2126       \expandafter\color\expandafter{\@tempa}}%
2127   \fi
2128   \let\FancyVerbFillColor@tempa}
2129 \fvset{fillcolor=none}

```

12.11 Extensions

12.11.1 New options requiring minimal implementation

linenos

`fancyvrb` allows line numbers via the options `numbers=left` and `numbers=right`. This creates a `linenos` key that is essentially an alias for `numbers=left`.

```

2130 \define@booleankey{FV}{linenos}%
2131   {\@nameuse{FV@Numbers@left}}{\@nameuse{FV@Numbers@none}}

```

tab

Redefine `\FancyVerbTab`.

```

2132 \define@key{FV}{tab}{\def\FancyVerbTab{#1}}

```

tabcolor

Set tab color, or allow it to adjust to surroundings (the default `fancyvrb` behavior). This involves re-creating the `showtabs` option to add `\FV@TabColor`.

```

2133 \define@key{FV}{tabcolor}%
2134   {\ifstrempy{#1}%
2135     {\let\FV@TabColor\relax}%
2136     {\ifstrequal{#1}{none}%
2137       {\let\FV@TabColor\relax}%
2138       {\def\FV@TabColor{\textcolor{#1}}}}}
2139 \define@booleankey{FV}{showtabs}%
2140   {\def\FV@TabChar{\FV@TabColor{\FancyVerbTab}}}%
2141   {\let\FV@TabChar\relax}
2142 \fvset{tabcolor=none, showtabs=false}

```

showspaces

FV@showspaces

Reimplement `showspaces` with a bool to work with new space options.

```

2143 \newbool{FV@showspaces}
2144 \define@booleankey{FV}{showspaces}%
2145   {\booltrue{FV@showspaces}}%
2146   {\boolfalse{FV@showspaces}}
2147 \fvset{showspaces=false}

```

space

Redefine `\FancyVerbSpace`, which is the visible space.

```

2148 \define@key{FV}{space}{\def\FancyVerbSpace{#1}}
spacecolor
    Set space color, or allow it to adjust to surroundings (the default fancyvrb behavior). This involves re-creating the showspaces option to add \FV@SpaceColor.
2149 \define@key{FV}{spacecolor}%
2150 {\ifstrepty{#1}%
2151   {\let\FV@SpaceColor\relax}%
2152   {\ifstrequal{#1}{none}%
2153     {\let\FV@SpaceColor\relax}%
2154     {\def\FV@SpaceColor{\textcolor{#1}}}}}}
2155 \fvset{spacecolor=none}
spacebreak
\FancyVerbSpaceBreak
    Line break for spaces that is inserted when spaces are visible (showspaces=true) or when breaks around spaces are handled specially (breakcollapsespaces=false). Not used for regular spaces under default conditions.
2156 \define@key{FV}{spacebreak}{%
2157   \def\FancyVerbSpaceBreak{#1}}
2158 \fvset{spacebreak=\discretionary{}{}{}}
breakcollapsespaces
FV@breakcollapsespaces
    When a line break occurs within a sequence of regular space characters (showspaces=false), collapse the spaces into a single space and then replace it with the break. When this is true, a sequence of spaces will cause at most a single line break, and the first character on the wrapped line after the break will be a non-space character. When this is false, a sequence of spaces may result in multiple line breaks. Each wrapped line besides the last will contain only spaces. The final wrapped line may contain leading spaces before any non-space character(s).
2159 \newbool{FV@breakcollapsespaces}
2160 \define@booleankey{FV}{breakcollapsespaces}%
2161 {\booltrue{FV@breakcollapsespaces}}%
2162 {\boolfalse{FV@breakcollapsespaces}}%
2163 \fvset{breakcollapsespaces=true}
\FV@DefFVSpace
    Redefine \FV@Space based on fvextra options that affect spaces.
    This must be added to \FV@FormattingPrep@PreHook, but only after breakbefore and breakafter macros are defined. Hence the \AtEndOfPackage.
2164 \def\FV@DefFVSpace{%
2165   \ifbool{FV@showspaces}%
2166     {\ifbool{FV@breaklines}%
2167       {\ifcsname FV@BreakBefore@Token\FV@SpaceCatTen\endcsname
2168         \def\FV@Space{\FV@SpaceColor{\FancyVerbSpace}}%
2169       \else\ifcsname FV@BreakAfter@Token\FV@SpaceCatTen\endcsname
2170         \def\FV@Space{\FV@SpaceColor{\FancyVerbSpace}}%
2171       \else
2172         \def\FV@Space{\FV@SpaceColor{\FancyVerbSpace}\FancyVerbSpaceBreak}%
2173       \fi\fi}%
2174     {\def\FV@Space{\FV@SpaceColor{\FancyVerbSpace}}}%
2175   {\ifbool{FV@breaklines}%

```

```

2176 {\ifcsname FV@BreakBefore@Token\FV@SpaceCatTen\endcsname
2177   \def\FV@Space{\mbox{\FV@SpaceCatTen}}}%
2178 \else\ifcsname FV@BreakAfter@Token\FV@SpaceCatTen\endcsname
2179   \def\FV@Space{\mbox{\FV@SpaceCatTen}}}%
2180 \else
2181   \ifbool{FV@breakcollapsespaces}%
2182     {\def\FV@Space{\FV@SpaceCatTen}}}%
2183     {\def\FV@Space{\mbox{\FV@SpaceCatTen}\FancyVerbSpaceBreak}}}%
2184   \fi}%
2185 {\def\FV@Space{\FV@SpaceCatTen}}}}}%
2186 \AtEndOfPackage{%
2187   \g@addto@macro\FV@FormattingPrep@PreHook{\FV@DefFVSpace}}

```

mathescape

Give \$, &, ^, and _ their normal catcodes to allow normal typeset math.

```

2188 \define@booleankey{FV}{mathescape}%
2189 {\let\FancyVerbMathEscape\FV@MathEscape}%
2190 {\let\FancyVerbMathEscape\relax}
2191 \def\FV@MathEscape{\catcode`\$=3\catcode`\&=4\catcode`\^=7\catcode`\_ =8\relax}
2192 \FV@AddToHook\FV@CatCodesHook\FancyVerbMathEscape
2193 \fvset{mathescape=false}

```

beameroverlays

Give < and > their normal catcodes (not \active), so that beamer overlays will work. This modifies \@noligs because that is the only way to prevent the settings from being overwritten later. This could have used \FV@CatCodesHook, but then it would have had to compare \@noligs to \relax to avoid issues when \let\@noligs\relax in VerbatimOut.

```

2194 \define@booleankey{FV}{beameroverlays}%
2195 {\let\FancyVerbBeamerOverlays\FV@BeamerOverlays}%
2196 {\let\FancyVerbBeamerOverlays\relax}
2197 \def\FV@BeamerOverlays{%
2198   \expandafter\def\expandafter\@noligs\expandafter{\@noligs
2199     \catcode`\<=12\catcode`\>=12\relax}}
2200 \FV@AddToHook\FV@FormattingPrep@PreHook\FancyVerbBeamerOverlays
2201 \fvset{beameroverlays=false}

```

curlyquotes

Let ` and ' produce curly quotation marks ‘ and ’ rather than the backtick and typewriter single quotation mark produced by default via upquote.

```

2202 \newbool{FV@CurlyQuotes}
2203 \define@booleankey{FV}{curlyquotes}%
2204 {\booltrue{FV@CurlyQuotes}}%
2205 {\boolfalse{FV@CurlyQuotes}}
2206 \def\FancyVerbCurlyQuotes{%
2207   \ifbool{FV@CurlyQuotes}%
2208     {\expandafter\def\expandafter\@noligs\expandafter{\@noligs
2209       \begingroup\lccode`\~=`\lowercase{\endgroup\def~}{`}}%
2210       \begingroup\lccode`\~=`'\lowercase{\endgroup\def~}{'}}}%
2211   {}}
2212 \g@addto@macro\FV@FormattingPrep@PreHook{\FancyVerbCurlyQuotes}
2213 \fvset{curlyquotes=false}

```

fontencoding

Add option for font encoding.

```

2214 \define@key{FV}{fontencoding}%
2215   {\ifstrempy{#1}%
2216     {\let\FV@FontEncoding\relax}%
2217     {\ifstrequal{#1}{none}%
2218       {\let\FV@FontEncoding\relax}%
2219       {\def\FV@FontEncoding{\fontencoding{#1}}}}
2220 \expandafter\def\expandafter\FV@SetupFont\expandafter{%
2221   \expandafter\FV@FontEncoding\FV@SetupFont}
2222 \fvset{fontencoding=none}

```

12.11.2 Formatting with `\FancyVerbFormatLine`, `\FancyVerbFormatText`, and `\FancyVerbHighlightLine`

`fancyvrb` defines `\FancyVerbFormatLine`, which defines the formatting for each line. The introduction of line breaks introduces an issue for `\FancyVerbFormatLine`. Does it format the entire line, including any whitespace in the margins or behind line break symbols (that is, is it outside the `\parbox` in which the entire line is wrapped when breaking is active)? Or does it only format the text part of the line, only affecting the actual characters (inside the `\parbox`)? Since both might be desirable, `\FancyVerbFormatLine` is assigned to the entire line, and a new macro `\FancyVerbFormatText` is assigned to the text, within the `\parbox`.

An additional complication is that the `fancyvrb` documentation says that the default value is `\def\FancyVerbFormatLine#1{#1}`. But the actual default is `\def\FancyVerbFormatLine#1{\FV@ObeyTabs{#1}}`. That is, `\FV@ObeyTabs` needs to operate directly on the line to handle tabs. As a result, *all* `fancyvrb` commands that involve `\FancyVerbFormatLine` are patched, so that `\def\FancyVerbFormatLine#1{#1}`.

An additional macro `\FancyVerbHighlightLine` is added between `\FancyVerbFormatLine` and `\FancyVerbFormatText`. This is used to highlight selected lines (section 12.11.5). It is inside `\FancyVerbHighlightLine` so that if `\FancyVerbHighlightLine` is used to provide a background color, `\FancyVerbHighlightLine` can override it.

`\FancyVerbFormatLine`

Format the entire line, following the definition given in the `fancyvrb` documentation. Because this is formatting the entire line, using boxes works with line breaking.

```
2223 \def\FancyVerbFormatLine#1{#1}
```

`\FancyVerbFormatText`

Format only the text part of the line. Because this is inside all of the line breaking commands, using boxes here can conflict with line breaking.

```
2224 \def\FancyVerbFormatText#1{#1}
```

`\FV@ListProcessLine@NoBreak`

Redefined `\FV@ListProcessLine` in which `bgcolor` support is added, `\FancyVerbFormatText` is added, and tab handling is explicit. The `@NoBreak` suffix is added because `\FV@ListProcessLine` will be `\let` to either this macro or to `\FV@ListProcessLine@Break` depending on whether line breaking is enabled.

```

2225 \def\FV@ListProcessLine@NoBreak#1{%
2226   \hbox to \hsize{%
2227     \kern\leftmargin
2228     \hbox to \linewidth{%
2229       \FV@LeftListNumber

```

```

2230 \FV@LeftListFrame
2231 \FV@BGColor@List{%
2232 \FancyVerbFormatLine{%
2233 \FancyVerbHighlightLine{%
2234 \FV@ObeyTabs{\FancyVerbFormatText{#1}}}}\hss
2235 \FV@RightListFrame
2236 \FV@RightListNumber}%
2237 \hss}\FV@bgcoloroverlap}

```

`\FV@BProcessLine`

Redefined `\FV@BProcessLine` in which `\FancyVerbFormatText` is added and tab handling is explicit.

```

2238 \def\FV@BProcessLine#1{%
2239 \hbox{\FancyVerbFormatLine{%
2240 \ifx\FancyVerbBackgroundColor\relax
2241 \else
2242 \expandafter\FancyVerbBackgroundColorVPhantom
2243 \fi
2244 \FancyVerbHighlightLine{%
2245 \FV@ObeyTabs{\FancyVerbFormatText{#1}}}}}}

```

12.11.3 Line numbering

Add several new line numbering options. `numberfirstline` always numbers the first line, regardless of `stepnumber`. `stepnumberfromfirst` numbers the first line, and then every line that differs from its number by a multiple of `stepnumber`. `stepnumberoffsetvalues` determines whether line numbers are always an exact multiple of `stepnumber` (the new default behavior) or whether there is an offset when `firstnumber` \neq 1 (the old default behavior). A new option `numbers=both` is created to allow line numbers on both left and right simultaneously.

`FV@NumberFirstLine`

```
2246 \newbool{FV@NumberFirstLine}
```

`numberfirstline`

```

2247 \define@booleankey{FV}{numberfirstline}%
2248 {\booltrue{FV@NumberFirstLine}}%
2249 {\boolfalse{FV@NumberFirstLine}}
2250 \fvset{numberfirstline=false}

```

`FV@StepNumberFromFirst`

```
2251 \newbool{FV@StepNumberFromFirst}
```

`stepnumberfromfirst`

```

2252 \define@booleankey{FV}{stepnumberfromfirst}%
2253 {\booltrue{FV@StepNumberFromFirst}}%
2254 {\boolfalse{FV@StepNumberFromFirst}}
2255 \fvset{stepnumberfromfirst=false}

```

`FV@StepNumberOffsetValues`

```
2256 \newbool{FV@StepNumberOffsetValues}
```

`stepnumberoffsetvalues`

```
2257 \define@booleankey{FV}{stepnumberoffsetvalues}%

```

```

2258 {\booltrue{FV@StepNumberOffsetValues}}%
2259 {\boolfalse{FV@StepNumberOffsetValues}}
2260 \fvset{stepnumberoffsetvalues=false}

```

\FV@Numbers@left

Redefine fancyvrb macro to account for numberfirstline, stepnumberfromfirst, and stepnumberoffsetvalues. The \let\FancyVerbStartNum\@ne is needed to account for the case where firstline is never set, and defaults to zero (\z@).

```

2261 \def\FV@Numbers@left{%
2262   \let\FV@RightListNumber\relax
2263   \def\FV@LeftListNumber{%
2264     \ifx\FancyVerbStartNum\z@
2265       \let\FancyVerbStartNum\@ne
2266     \fi
2267     \ifbool{FV@StepNumberFromFirst}%
2268       {@tempcnta=\FV@CodeLineNo
2269        \@tempcntb=\FancyVerbStartNum
2270        \advance\@tempcntb\FV@StepNumber
2271        \divide\@tempcntb\FV@StepNumber
2272        \multiply\@tempcntb\FV@StepNumber
2273        \advance\@tempcnta\@tempcntb
2274        \advance\@tempcnta-\FancyVerbStartNum
2275        \@tempcntb=\@tempcnta}%
2276       {\ifbool{FV@StepNumberOffsetValues}%
2277        {@tempcnta=\FV@CodeLineNo
2278         \@tempcntb=\FV@CodeLineNo}%
2279        {@tempcnta=\c@FancyVerbLine
2280         \@tempcntb=\c@FancyVerbLine}}%
2281       \divide\@tempcntb\FV@StepNumber
2282       \multiply\@tempcntb\FV@StepNumber
2283       \ifnum\@tempcnta=\@tempcntb
2284         \if@FV@NumberBlankLines
2285           \hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}%
2286         \else
2287           \ifx\FV@Line\empty
2288             \else
2289               \hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}%
2290             \fi
2291           \fi
2292         \else
2293           \ifbool{FV@NumberFirstLine}{%
2294             \ifnum\FV@CodeLineNo=\FancyVerbStartNum
2295               \hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}%
2296             \fi}{%
2297           \fi}%
2298 }

```

\FV@Numbers@right

Redefine fancyvrb macro to account for numberfirstline, stepnumberfromfirst, and stepnumberoffsetvalues.

```

2299 \def\FV@Numbers@right{%
2300   \let\FV@LeftListNumber\relax
2301   \def\FV@RightListNumber{%
2302     \ifx\FancyVerbStartNum\z@

```

```

2303     \let\FancyVerbStartNum\@ne
2304   \fi
2305   \ifbool{FV@StepNumberFromFirst}%
2306     {\@tempcnta=FV@CodeLineNo
2307     \@tempcntb=FancyVerbStartNum
2308     \advance\@tempcntb\FV@StepNumber
2309     \divide\@tempcntb\FV@StepNumber
2310     \multiply\@tempcntb\FV@StepNumber
2311     \advance\@tempcnta\@tempcntb
2312     \advance\@tempcnta-FancyVerbStartNum
2313     \@tempcntb=\@tempcnta}%
2314   {\ifbool{FV@StepNumberOffsetValues}%
2315     {\@tempcnta=FV@CodeLineNo
2316     \@tempcntb=FV@CodeLineNo}%
2317     {\@tempcnta=c@FancyVerbLine
2318     \@tempcntb=c@FancyVerbLine}}%
2319   \divide\@tempcntb\FV@StepNumber
2320   \multiply\@tempcntb\FV@StepNumber
2321   \ifnum\@tempcnta=\@tempcntb
2322     \ifFV@NumberBlankLines
2323       \hbox to\z@{\kern\FV@NumberSep\theFancyVerbLine\hss}%
2324     \else
2325       \ifx\FV@Line\empty
2326         \else
2327           \hbox to\z@{\kern\FV@NumberSep\theFancyVerbLine\hss}%
2328         \fi
2329       \fi
2330     \else
2331       \ifbool{FV@NumberFirstLine}{%
2332         \ifnum\FV@CodeLineNo=FancyVerbStartNum
2333           \hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}%
2334         \fi}{%
2335       \fi}%
2336 }

```

\FV@Numbers@both

Define a new macro to allow numbers=both. This copies the definitions of \FV@LeftListNumber and \FV@RightListNumber from \FV@Numbers@left and \FV@Numbers@right, without the \relax's.

```

2337 \def\FV@Numbers@both{%
2338   \def\FV@LeftListNumber{%
2339     \ifx\FancyVerbStartNum\z@
2340       \let\FancyVerbStartNum\@ne
2341     \fi
2342     \ifbool{FV@StepNumberFromFirst}%
2343       {\@tempcnta=FV@CodeLineNo
2344       \@tempcntb=FancyVerbStartNum
2345       \advance\@tempcntb\FV@StepNumber
2346       \divide\@tempcntb\FV@StepNumber
2347       \multiply\@tempcntb\FV@StepNumber
2348       \advance\@tempcnta\@tempcntb
2349       \advance\@tempcnta-FancyVerbStartNum
2350       \@tempcntb=\@tempcnta}%
2351     {\ifbool{FV@StepNumberOffsetValues}%

```

```

2352     {\@tempcnta=\FV@CodeLineNo
2353      \@tempcntb=\FV@CodeLineNo}%
2354     {\@tempcnta=\c@FancyVerbLine
2355      \@tempcntb=\c@FancyVerbLine}}%
2356 \divide\@tempcntb\FV@StepNumber
2357 \multiply\@tempcntb\FV@StepNumber
2358 \ifnum\@tempcnta=\@tempcntb
2359   \if@FV@NumberBlankLines
2360     \hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}%
2361   \else
2362     \ifx\FV@Line\empty
2363     \else
2364       \hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}%
2365     \fi
2366   \fi
2367 \else
2368   \ifbool{FV@NumberFirstLine}{%
2369     \ifnum\FV@CodeLineNo=\FancyVerbStartNum
2370       \hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}%
2371     \fi}{}%
2372 \fi}%
2373 \def\FV@RightListNumber{%
2374   \ifx\FancyVerbStartNum\z@
2375     \let\FancyVerbStartNum\@ne
2376   \fi
2377   \ifbool{FV@StepNumberFromFirst}%
2378     {\@tempcnta=\FV@CodeLineNo
2379      \@tempcntb=\FancyVerbStartNum
2380      \advance\@tempcntb\FV@StepNumber
2381      \divide\@tempcntb\FV@StepNumber
2382      \multiply\@tempcntb\FV@StepNumber
2383      \advance\@tempcnta\@tempcntb
2384      \advance\@tempcnta-\FancyVerbStartNum
2385      \@tempcntb=\@tempcnta}%
2386     {\ifbool{FV@StepNumberOffsetValues}%
2387       {\@tempcnta=\FV@CodeLineNo
2388        \@tempcntb=\FV@CodeLineNo}%
2389       {\@tempcnta=\c@FancyVerbLine
2390        \@tempcntb=\c@FancyVerbLine}}%
2391   \divide\@tempcntb\FV@StepNumber
2392   \multiply\@tempcntb\FV@StepNumber
2393   \ifnum\@tempcnta=\@tempcntb
2394     \if@FV@NumberBlankLines
2395       \hbox to\z@{\kern\FV@NumberSep\theFancyVerbLine\hss}%
2396     \else
2397       \ifx\FV@Line\empty
2398       \else
2399         \hbox to\z@{\kern\FV@NumberSep\theFancyVerbLine\hss}%
2400       \fi
2401     \fi
2402   \else
2403     \ifbool{FV@NumberFirstLine}{%
2404       \ifnum\FV@CodeLineNo=\FancyVerbStartNum
2405         \hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}%

```

```

2406     \fi}{}%
2407     \fi}%
2408 }

```

12.11.4 Background color

Define an option `backgroundcolor` that provides a basic implementation of a background color behind commands and environments. `tcolorbox` or a similar package should be used for more sophisticated background colors.

The patch to `\FV@List` prevents narrow horizontal gaps in the background color between lines of text under some circumstances. The `\ExplSyntax*` is for compatibility with patches from the L^AT_EX Tagged PDF project.

```

backgroundcolor
bgcolor
\FancyVerbBackgroundColor

2409 \define@key{FV}{backgroundcolor}{%
2410   \def\FancyVerbBackgroundColor{#1}%
2411   \ifx\FancyVerbBackgroundColor\FV@None
2412     \let\FancyVerbBackgroundColor\relax
2413   \else\ifx\FancyVerbBackgroundColor\@empty
2414     \let\FancyVerbBackgroundColor\relax
2415   \fi\fi}%
2416 \fvset{backgroundcolor=none}
2417 \define@key{FV}{bgcolor}{%
2418   \fvset{backgroundcolor=#1}}
2419 \ExplSyntaxOn
2420 \patchcmd{\FV@List}{%
2421   {\FV@ObeyTabsInit}%
2422   {\FV@ObeyTabsInit
2423     \ifx\FancyVerbBackgroundColor\relax
2424     \else
2425       \lineskip\z@
2426     \fi}%
2427   }{}%
2428   {\PackageError{fvextra}{
2429     {Failed-to-patch-\detokenize{\FV@List}for-backgroundcolor}%
2430     {Failed-to-patch-\detokenize{\FV@List}for-backgroundcolor}}
2431   \ExplSyntaxOff

```

```

backgroundcolorboxoverlap
bgcolorboxoverlap
\FV@backgroundcolorboxoverlap
\FV@bgcolorstrut
\FV@bgcoloroverlap

2432 \define@key{FV}{backgroundcolorboxoverlap}{%
2433   \ifdim#1=0pt\relax
2434     \let\FV@backgroundcolorboxoverlap\relax
2435   \else
2436     \def\FV@backgroundcolorboxoverlap{#1}%
2437     \fi}
2438 \fvset{backgroundcolorboxoverlap=0.25pt}
2439 \define@key{FV}{bgcolorboxoverlap}{%
2440   \fvset{backgroundcolorboxoverlap=#1}}

```

```

2441 \newsavebox{\FV@bgcolorstructbox}
2442 \def\FV@bgcolorstrut{%
2443   \ifx\FancyVerbBackgroundColor\relax
2444     \FancyVerbBackgroundColorVPhantom\strut
2445   \else\ifx\FV@backgroundcolorboxoverlap\relax
2446     \FancyVerbBackgroundColorVPhantom\strut
2447   \else
2448     \savebox{\FV@bgcolorstructbox}{\hbox{\FancyVerbBackgroundColorVPhantom\strut}}%
2449     \vrule height \ht\FV@bgcolorstructbox
2450             depth \dimexpr\dp\FV@bgcolorstructbox+\FV@backgroundcolorboxoverlap\relax
2451             width 0pt\relax
2452   \fi\fi}
2453 \def\FV@bgcoloroverlap{%
2454   \ifx\FV@backgroundcolorboxoverlap\relax
2455   \else
2456     \vspace{-\FV@backgroundcolorboxoverlap}%
2457   \fi}

```

backgroundcolorvphantom

bgcolorvphantom

\FancyVerbBackgroundColorVPhantom

```

2458 \define@key{FV}{backgroundcolorvphantom}{%
2459   \def\FancyVerbBackgroundColorVPhantom{#1}%
2460   \ifx\FancyVerbBackgroundColorVPhantom\FV@None
2461     \let\FancyVerbBackgroundColorVPhantom\relax
2462   \else\ifx\FancyVerbBackgroundColorVPhantom@empty
2463     \let\FancyVerbBackgroundColorVPhantom\relax
2464   \fi\fi}
2465 \fvset{backgroundcolorvphantom=\vphantom{"Apgjy}}
2466 \define@key{FV}{bgcolorvphantom}{%
2467   \fvset{backgroundcolorvphantom=#1}}

```

backgroundcolorpadding

bgcolorpadding

\FancyVerbBackgroundColorPadding

```

2468 \let\FancyVerbBackgroundColorPadding\relax
2469 \def\FV@backgroundcolorpadding@none@framenotsingle{%
2470   \fvset{frame=none,framerule,rulecolor=none}}
2471 \def\FV@backgroundcolorpadding@dim@framenotsingle{%
2472   \fvset{frame=single,framerule=Opt,rulecolor=\FancyVerbBackgroundColor}}
2473 \define@key{FV}{backgroundcolorpadding}{%
2474   \def\FancyVerbBackgroundColorPadding{#1}%
2475   \ifx\FancyVerbBackgroundColorPadding\FV@None
2476     \let\FancyVerbBackgroundColorPadding\relax
2477   \else\ifx\FancyVerbBackgroundColorPadding@empty
2478     \let\FancyVerbBackgroundColorPadding\relax
2479   \fi\fi
2480   \let\FV@Next\relax
2481   \ifx\FancyVerbBackgroundColorPadding\relax
2482     \ifx\FV@BeginListFrame\FV@BeginListFrame@Single
2483     \else
2484       \let\FV@Next\FV@backgroundcolorpadding@none@framenotsingle
2485     \fi
2486     \ifx\FV@LeftListFrame\FV@LeftListFrame@Single

```

```

2487 \else
2488 \let\FV@Next\FV@backgroundcolorpadding@none@framenotsingle
2489 \fi
2490 \ifx\FV@RightListFrame\FV@RightListFrame@Single
2491 \else
2492 \let\FV@Next\FV@backgroundcolorpadding@none@framenotsingle
2493 \fi
2494 \ifx\FV@endListFrame\FV@endListFrame@Single
2495 \else
2496 \let\FV@Next\FV@backgroundcolorpadding@none@framenotsingle
2497 \fi
2498 \FV@Next
2499 \fvset{framesep,fillcolor=none}%
2500 \else
2501 \ifx\FV@BeginListFrame\FV@BeginListFrame@Single
2502 \else
2503 \let\FV@Next\FV@backgroundcolorpadding@dim@framenotsingle
2504 \fi
2505 \ifx\FV@LeftListFrame\FV@LeftListFrame@Single
2506 \else
2507 \let\FV@Next\FV@backgroundcolorpadding@dim@framenotsingle
2508 \fi
2509 \ifx\FV@RightListFrame\FV@RightListFrame@Single
2510 \else
2511 \let\FV@Next\FV@backgroundcolorpadding@dim@framenotsingle
2512 \fi
2513 \ifx\FV@endListFrame\FV@endListFrame@Single
2514 \else
2515 \let\FV@Next\FV@backgroundcolorpadding@dim@framenotsingle
2516 \fi
2517 \FV@Next
2518 \fvset{framesep=#1,fillcolor=\FancyVerbBackgroundColor}%
2519 \fi}
2520 \define@key{FV}{bgcolorpadding}{\fvset{backgroundcolorpadding=#1}}

```

`\FV@BGColor@List`

Background color for environments based on Verbatim. Puts each line in a colorbox.

```

2521 \def\FV@BGColor@List#1{%
2522 \ifx\FancyVerbBackgroundColor\relax
2523 \expandafter\@firstoftwo
2524 \else
2525 \expandafter\@secondoftwo
2526 \fi
2527 {#1}%
2528 {\setlength{\FV@TmpLength}{\fboxsep}}%
2529 \setlength{\fboxsep}{0pt}%
2530 \colorbox{\FancyVerbBackgroundColor}{%
2531 \setlength{\fboxsep}{\FV@TmpLength}}%
2532 \rlap{\FV@bgcolorstrut#1}%
2533 \hspace{\linewidth}}%
2534 \ifx\FV@RightListFrame\relax\else
2535 \hspace{-\FV@FrameSep}}%
2536 \hspace{-\FV@FrameRule}}%

```

```

2537     \fi
2538     \ifx\FV@LeftListFrame\relax\else
2539         \hspace{-\FV@FrameSep}%
2540         \hspace{-\FV@FrameRule}%
2541     \fi}%
2542 \hss}}
\FV@BVerbatimBegin
\FV@BVerbatimEnd

```

Reimplementation of BVerbatim macros to support bgcolor. Much of this follows the implementation of SaveVerbatim and \UseVerbatim.

Key values must be configured immediately for the bgcolor case, so that the background color and other settings are available. \FV@UseKeyValues will be invoked again within the original fancyvrb implementation (now \FV@BVerbatimBegin@NoBGColor), but that doesn't cause any issues since \FV@UseKeyValues applies keys and then redefines \FV@KeyValues to empty. \FV@FormattingPrep doesn't appear explicitly, because it is in \FV@BVerbatimBegin@NoBGColor. The \FV@BVerbatim@*@NoBGColor macros are used regardless of whether there is a background color; they are wrapped in additional macros in the background color case.

The definition of \FV@BProcessLine already accounts for \FancyVerbBackgroundColorVPhantom.

```

2543 \let\FV@BVerbatimBegin@NoBGColor\FV@BVerbatimBegin
2544 \let\FV@BVerbatimEnd@NoBGColor\FV@BVerbatimEnd
2545 \def\FV@BVerbatimBegin{%
2546   \begingroup
2547   \FV@UseKeyValues
2548   \ifx\FancyVerbBackgroundColor\relax
2549     \expandafter\FV@BVerbatimBegin@NoBGColor
2550   \else
2551     \expandafter\FV@BVerbatimBegin@BGColor
2552   \fi}
2553 \def\FV@BVerbatimEnd{%
2554   \ifx\FancyVerbBackgroundColor\relax
2555     \expandafter\FV@BVerbatimEnd@NoBGColor
2556   \else
2557     \expandafter\FV@BVerbatimEnd@BGColor
2558   \fi
2559 \endgroup}
2560 \def\FV@BVerbatimBegin@BGColor{%
2561   \gdef\FV@TheVerbatim{}%
2562   \ifx\FV@boxwidth\relax
2563     \gdef\FV@boxwidth@tmp{0pt}%
2564     \def\FV@ProcessLine##1{%
2565       \sbox{\FV@LineBox}{\FV@BProcessLine{##1}}%
2566       \ifdim\wd\FV@LineBox>\FV@boxwidth@tmp\relax
2567         \xdef\FV@boxwidth@tmp{\the\wd\FV@LineBox}%
2568       \fi
2569       \expandafter\gdef\expandafter\FV@TheVerbatim\expandafter{%
2570         \FV@TheVerbatim\FV@ProcessLine{##1}}}%
2571   \else
2572     \def\FV@ProcessLine##1{%
2573       \expandafter\gdef\expandafter\FV@TheVerbatim\expandafter{%
2574         \FV@TheVerbatim\FV@ProcessLine{##1}}}%
2575   \fi}

```

```

2576 \def\FV@BVerbatimEnd@BGColor{%
2577   \ifx\FV@boxwidth\relax
2578     \let\FV@boxwidth\FV@boxwidth@tmp
2579     \global\let\FV@boxwidth@tmp\FV@Undefined
2580   \fi
2581   \setlength{\FV@TmpLength}{\fboxsep}%
2582   \ifx\FancyVerbBackgroundColorPadding\relax
2583     \setlength{\fboxsep}{0pt}%
2584   \else
2585     \setlength{\fboxsep}{\FancyVerbBackgroundColorPadding}%
2586   \fi
2587   \colorbox{\FancyVerbBackgroundColor}{%
2588     \setlength{\fboxsep}{\FV@TmpLength}%
2589     \FV@BVerbatimBegin@NoBGColor\FV@TheVerbatim\FV@BVerbatimEnd@NoBGColor}%
2590   \gdef\FV@TheVerbatim{}}

```

12.11.5 Line highlighting or emphasis

This adds an option `highlightlines` that allows specific lines, or lines within a range, to be highlighted or otherwise emphasized.

`highlightlines`

`\FV@HighlightLinesList`

```

2591 \define@key{FV}{highlightlines}{\def\FV@HighlightLinesList{#1}}%
2592 \fvset{highlightlines=}

```

`highlightcolor`

`\FV@HighlightColor`

Define color for highlighting. The default is LightCyan. A good alternative for a brighter color would be LemonChiffon.

```

2593 \define@key{FV}{highlightcolor}{\def\FancyVerbHighlightColor{#1}}%
2594 \let\FancyVerbHighlightColor\@empty
2595 \ifcsname definecolor\endcsname
2596 \ifx\definecolor\relax
2597 \else
2598   \definecolor{FancyVerbHighlightColor}{rgb}{0.878, 1, 1}
2599   \fvset{highlightcolor=FancyVerbHighlightColor}
2600 \fi\fi
2601 \AtBeginDocument{%
2602   \ifx\FancyVerbHighlightColor\@empty
2603     \ifcsname definecolor\endcsname
2604     \ifx\definecolor\relax
2605       \else
2606         \definecolor{FancyVerbHighlightColor}{rgb}{0.878, 1, 1}
2607         \fvset{highlightcolor=FancyVerbHighlightColor}
2608       \fi\fi
2609     \fi}

```

`\FancyVerbHighlightLine`

This is the entry macro into line highlighting. By default it should do nothing. It is always invoked between `\FancyVerbFormatLine` and `\FancyVerbFormatText`, so that it can provide a background color (won't interfere with line breaking) and can override any formatting provided by `\FancyVerbFormatLine`. It is `\let` to `\FV@HighlightLine` when highlighting is active.

```

2610 \def\FancyVerbHighlightLine#1{#1}

```

`\FV@HighlightLine`

This determines whether highlighting should be performed, and if so, which macro should be invoked.

```
2611 \def\FV@HighlightLine#1{%
2612   \@tempcnta=\c@FancyVerbLine
2613   \@tempcntb=\c@FancyVerbLine
2614   \ifcsname FV@HighlightLine:\number\@tempcnta\endcsname
2615     \advance\@tempcntb\m@ne
2616     \ifcsname FV@HighlightLine:\number\@tempcntb\endcsname
2617       \advance\@tempcntb\tw@
2618       \ifcsname FV@HighlightLine:\number\@tempcntb\endcsname
2619         \let\FV@HighlightLine@Next\FancyVerbHighlightLineMiddle
2620       \else
2621         \let\FV@HighlightLine@Next\FancyVerbHighlightLineLast
2622       \fi
2623     \else
2624       \advance\@tempcntb\tw@
2625       \ifcsname FV@HighlightLine:\number\@tempcntb\endcsname
2626         \let\FV@HighlightLine@Next\FancyVerbHighlightLineFirst
2627       \else
2628         \let\FV@HighlightLine@Next\FancyVerbHighlightLineSingle
2629       \fi
2630     \fi
2631   \else
2632     \let\FV@HighlightLine@Next\FancyVerbHighlightLineNormal
2633   \fi
2634   \FV@HighlightLine@Next{#1}%
2635 }
```

`\FancyVerbHighlightLineNormal`

A normal line that is not highlighted or otherwise emphasized. This could be redefined to de-emphasize the line.

```
2636 \def\FancyVerbHighlightLineNormal#1{#1}
```

`\FV@TmpLength`

```
2637 \newlength{\FV@TmpLength}
```

`\FancyVerbHighlightLineFirst`

The first line in a multi-line range.

`\fboxsep` is set to zero so as to avoid indenting the line or changing inter-line spacing. It is restored to its original value inside to prevent any undesired effects. The `\strut` is needed to get the highlighting to be the appropriate height. The `\rlap` and `\hspace` make the `\colorbox` expand to the full `\linewidth`. Note that if `\fboxsep` \neq 0, then we would want to use `\dimexpr\linewidth-2\fboxsep` or add `\hspace{-2\fboxsep}` at the end.

If this macro is customized so that the text cannot take up the full `\linewidth`, then adjustments may need to be made here or in the line breaking code to make sure that line breaking takes place at the appropriate location.

```
2638 \def\FancyVerbHighlightLineFirst#1{%
2639   \setlength{\FV@TmpLength}{\fboxsep}%
2640   \setlength{\fboxsep}{0pt}%
2641   \colorbox{\FancyVerbHighlightColor}{%
2642     \setlength{\fboxsep}{\FV@TmpLength}%
```

```

2643 \rlap{\strut#1}%
2644 \hspace{\linewidth}%
2645 \ifx\FV@RightListFrame\relax\else
2646 \hspace{-\FV@FrameSep}%
2647 \hspace{-\FV@FrameRule}%
2648 \fi
2649 \ifx\FV@LeftListFrame\relax\else
2650 \hspace{-\FV@FrameSep}%
2651 \hspace{-\FV@FrameRule}%
2652 \fi
2653 }%
2654 \hss
2655 }

```

`\FancyVerbHighlightLineMiddle`

A middle line in a multi-line range.

```
2656 \let\FancyVerbHighlightLineMiddle\FancyVerbHighlightLineFirst
```

`\FancyVerbHighlightLineLast`

The last line in a multi-line range.

```
2657 \let\FancyVerbHighlightLineLast\FancyVerbHighlightLineFirst
```

`\FancyVerbHighlightLineSingle`

A single line not in a multi-line range.

```
2658 \let\FancyVerbHighlightLineSingle\FancyVerbHighlightLineFirst
```

`\FV@HighlightLinesPrep`

Process the list of lines to highlight (if any). A macro is created for each line to be highlighted. During highlighting, a line is highlighted if the corresponding macro exists. All of the macro creating is ultimately within the current environment group so it stays local. `\FancyVerbHighlightLine` is `\let` to a version that will invoke the necessary logic.

```

2659 \def\FV@HighlightLinesPrep{%
2660 \ifx\FV@HighlightLinesList\@empty
2661 \else
2662 \let\FancyVerbHighlightLine\FV@HighlightLine
2663 \expandafter\FV@HighlightLinesPrep@i
2664 \fi}
2665 \def\FV@HighlightLinesPrep@i{%
2666 \renewcommand{\do}[1]{%
2667 \ifstrempy{##1}{}\FV@HighlightLinesParse##1-\FV@Undefined}}%
2668 \expandafter\docsvlist\expandafter{\FV@HighlightLinesList}}
2669 \def\FV@HighlightLinesParse#1-#2\FV@Undefined{%
2670 \ifstrempy{#2}%
2671 {\FV@HighlightLinesParse@Single{#1}}%
2672 {\FV@HighlightLinesParse@Range{#1}#2\relax}}
2673 \def\FV@HighlightLinesParse@Single#1{%
2674 \expandafter\let\csname FV@HighlightLine:\detokenize{#1}\endcsname\relax}
2675 \newcounter{FV@HighlightLinesStart}
2676 \newcounter{FV@HighlightLinesStop}
2677 \def\FV@HighlightLinesParse@Range#1#2-{%
2678 \setcounter{FV@HighlightLinesStart}{#1}%
2679 \setcounter{FV@HighlightLinesStop}{#2}%
2680 \stepcounter{FV@HighlightLinesStop}%
2681 \FV@HighlightLinesParse@Range@Loop}

```

```

2682 \def\FV@HighlightLinesParse@Range@Loop{%
2683   \ifnum\value{FV@HighlightLinesStart}<\value{FV@HighlightLinesStop}\relax
2684     \expandafter\let\csname FV@HighlightLine:\arabic{FV@HighlightLinesStart}\endcsname\relax
2685     \stepcounter{FV@HighlightLinesStart}%
2686     \expandafter\FV@HighlightLinesParse@Range@Loop
2687   \fi}
2688 \g@addto@macro\FV@FormattingPrep@PreHook{\FV@HighlightLinesPrep}
\FV@StepLineNo@Patch@HighlightLine
Patch \FV@StepLineNo so that when numberblanklines=false, blank lines
won't be highlighted. If the previous line is at the end of a highlighted range, then
\let \FV@HighlightLine:<n> to \FV@Undefined to prevent further highlighting.
Otherwise, leave everything as-is since the blank line(s) are within a highlighted
range.
2689 \def\FV@StepLineNo@Patch@HighlightLine{%
2690   \ifcsname FV@HighlightLine:\number\c@FancyVerbLine\endcsname
2691     \@tempcnta=\c@FancyVerbLine
2692     \advance\@tempcnta\@ne
2693     \ifcsname FV@HighlightLine:\number\@tempcnta\endcsname
2694     \else
2695       \expandafter\let
2696         \csname FV@HighlightLine:\number\c@FancyVerbLine\endcsname\FV@Undefined
2697     \fi
2698   \fi}
2699 \patchcmd{\FV@StepLineNo}%
2700   {\ifx\FV@Line\empty}%
2701   {\ifx\FV@Line\empty\FV@StepLineNo@Patch@HighlightLine}%
2702   {}%
2703   {\PackageError{fvextra}%
2704     {Failed to patch \string\FV@StepLineNo\ to make highlightlines
2705     compatible with numberblanklines}%
2706     {Failed to patch \string\FV@StepLineNo\ to make highlightlines
2707     compatible with numberblanklines}}

```

12.12 Line breaking

The following code adds automatic line breaking functionality to `fancyvrb`'s `Verbatim` environment. Automatic breaks may be inserted after spaces, or before or after specified characters. Breaking before or after specified characters involves scanning each line token by token to insert `\discretionary` at all potential break locations.

12.12.1 Options and associated macros

Begin by defining keys, with associated macros, booleans, and dimensions.

`\FV@SetToWidthNChars`

Set a dimension to the width of a given number of characters. This is used in setting several indentation-related dimensions.

```

2708 \newcount\FV@LoopCount
2709 \newbox\FV@NCharsBox
2710 \def\FV@SetToWidthNChars#1#2{%
2711   \FV@LoopCount=#2\relax
2712   \ifnum\FV@LoopCount>0

```

```

2713 \def\FV@NChars{%
2714 \loop
2715 \ifnum\FV@LoopCount>0
2716 \expandafter\def\expandafter\FV@NChars\expandafter{\FV@NChars x}%
2717 \fi
2718 \advance\FV@LoopCount by -1
2719 \ifnum\FV@LoopCount>0
2720 \repeat
2721 \setbox\FV@NCharsBox\hbox{\FV@NChars}%
2722 #1=\wd\FV@NCharsBox
2723 \else
2724 #1=0pt\relax
2725 \fi
2726 }

```

FV@breaklines

Turn line breaking on or off. The `\FV@ListProcessLine` from `fancyvrb` is `\let` to a (patched) version of the original or a version that supports line breaks.

```

2727 \newbool{FV@breaklines}
2728 \define@booleankey{FV}{breaklines}%
2729 {\booltrue{FV@breaklines}}%
2730 \let\FV@ListProcessLine\FV@ListProcessLine@Break}%
2731 {\boolfalse{FV@breaklines}}%
2732 \let\FV@ListProcessLine\FV@ListProcessLine@NoBreak}
2733 \AtEndOfPackage{\fvset{breaklines=false}}

```

\FV@BreakLinesLuaTeXHook

Fix hyphen handling under LuaTeX. `\automatichyphenmode=2` would work for environments, but doesn't seem to work inline. Instead, the active hyphen is redefined to `\mbox{-}`.

This is needed before `\@noligs` is ever used, so it is placed in `\FV@FormattingPrep@PreHook`.

```

2734 \def\FV@BreakLinesLuaTeXHook{%
2735 \expandafter\def\expandafter\@noligs\expandafter{\@noligs
2736 \begingroup\lccode`~=\- \lowercase{\endgroup\def~}{\leavevmode\kern\z@\mbox{-}}}}
2737 \ifcsname directlua\endcsname
2738 \ifx\directlua\relax
2739 \else
2740 \FV@AddToHook\FV@FormattingPrep@PreHook\FV@BreakLinesLuaTeXHook
2741 \fi
2742 \fi

```

\FV@BreakLinesIndentationHook

A hook for performing on-the-fly indentation calculations when `breaklines=true`. This is used for all `*NChars` related indentation. It is important to use `\FV@FormattingPrep@PostHook` because it is always invoked *after* any font-related settings.

```

2743 \def\FV@BreakLinesIndentationHook{}
2744 \g@addto@macro\FV@FormattingPrep@PostHook{%
2745 \ifFV@breaklines
2746 \FV@BreakLinesIndentationHook
2747 \fi}

```

\FV@BreakIndent

\FV@BreakIndentNChars

Indentation of continuation lines.

```

2748 \newdimen\FV@BreakIndent
2749 \newcount\FV@BreakIndentNChars
2750 \define@key{FV}{breakindent}{%
2751   \FV@BreakIndent=#1\relax
2752   \FV@BreakIndentNChars=0\relax}
2753 \define@key{FV}{breakindentnchars}{\FV@BreakIndentNChars=#1\relax}
2754 \g@addto@macro\FV@BreakLinesIndentationHook{%
2755   \ifnum\FV@BreakIndentNChars>0
2756     \FV@SetToWidthNChars{\FV@BreakIndent}{\FV@BreakIndentNChars}%
2757   \fi}
2758 \fvset{breakindentnchars=0}

```

FV@breakautoindent

Auto indentation of continuation lines to indentation of original line. Adds to `\FV@BreakIndent`.

```

2759 \newbool{FV@breakautoindent}
2760 \define@booleankey{FV}{breakautoindent}{%
2761   {\booltrue{FV@breakautoindent}}{\boolfalse{FV@breakautoindent}}}
2762 \fvset{breakautoindent=true}

```

\FancyVerbBreakSymbolLeft

The left-hand symbol indicating a break. Since breaking is done in such a way that a left-hand symbol will often be desired while a right-hand symbol may not be, a shorthand option `breaksymbol` is supplied. This shorthand convention is continued with other options applying to the left-hand symbol.

```

2763 \define@key{FV}{breaksymbolleft}{\def\FancyVerbBreakSymbolLeft{#1}}
2764 \define@key{FV}{breaksymbol}{\fvset{breaksymbolleft=#1}}
2765 \fvset{breaksymbolleft=\tiny\ensuremath{\hookrightarrow}}

```

\FancyVerbBreakSymbolRight

The right-hand symbol indicating a break.

```

2766 \define@key{FV}{breaksymbolright}{\def\FancyVerbBreakSymbolRight{#1}}
2767 \fvset{breaksymbolright={}}

```

\FV@BreakSymbolSepLeft

\FV@BreakSymbolSepLeftNChars

Separation of left break symbol from the text.

```

2768 \newdimen\FV@BreakSymbolSepLeft
2769 \newcount\FV@BreakSymbolSepLeftNChars
2770 \define@key{FV}{breaksymbolsepleft}{%
2771   \FV@BreakSymbolSepLeft=#1\relax
2772   \FV@BreakSymbolSepLeftNChars=0\relax}
2773 \define@key{FV}{breaksymbolsep}{\fvset{breaksymbolsepleft=#1}}
2774 \define@key{FV}{breaksymbolsepleftnchars}{\FV@BreakSymbolSepLeftNChars=#1\relax}
2775 \define@key{FV}{breaksymbolsepnchars}{\fvset{breaksymbolsepleftnchars=#1}}
2776 \g@addto@macro\FV@BreakLinesIndentationHook{%
2777   \ifnum\FV@BreakSymbolSepLeftNChars>0
2778     \FV@SetToWidthNChars{\FV@BreakSymbolSepLeft}{\FV@BreakSymbolSepLeftNChars}%
2779   \fi}
2780 \fvset{breaksymbolsepleftnchars=2}

```

\FV@BreakSymbolSepRight

\FV@BreakSymbolSepRightNChars

Separation of right break symbol from the text.

```

2781 \newdimen\FV@BreakSymbolSepRight

```

```

2782 \newcount\FV@BreakSymbolSepRightNChars
2783 \define@key{FV}{breaksymbolsepright}{%
2784   \FV@BreakSymbolSepRight=#1\relax
2785   \FV@BreakSymbolSepRightNChars=0\relax}
2786 \define@key{FV}{breaksymbolseprightnchars}{\FV@BreakSymbolSepRightNChars=#1\relax}
2787 \g@addto@macro\FV@BreakLinesIndentationHook{%
2788   \ifnum\FV@BreakSymbolSepRightNChars>0
2789     \FV@SetToWidthNChars{\FV@BreakSymbolSepRight}{\FV@BreakSymbolSepRightNChars}%
2790   \fi}
2791 \fvset{breaksymbolseprightnchars=2}

```

\FV@BreakSymbolIndentLeft

\FV@BreakSymbolIndentLeftNChars

Additional left indentation to make room for the left break symbol.

```

2792 \newdimen\FV@BreakSymbolIndentLeft
2793 \newcount\FV@BreakSymbolIndentLeftNChars
2794 \define@key{FV}{breaksymbolindentleft}{%
2795   \FV@BreakSymbolIndentLeft=#1\relax
2796   \FV@BreakSymbolIndentLeftNChars=0\relax}
2797 \define@key{FV}{breaksymbolindent}{\fvset{breaksymbolindentleft=#1}}
2798 \define@key{FV}{breaksymbolindentleftnchars}{\FV@BreakSymbolIndentLeftNChars=#1\relax}
2799 \define@key{FV}{breaksymbolindentnchars}{\fvset{breaksymbolindentleftnchars=#1}}
2800 \g@addto@macro\FV@BreakLinesIndentationHook{%
2801   \ifnum\FV@BreakSymbolIndentLeftNChars>0
2802     \FV@SetToWidthNChars{\FV@BreakSymbolIndentLeft}{\FV@BreakSymbolIndentLeftNChars}%
2803   \fi}
2804 \fvset{breaksymbolindentleftnchars=4}

```

\FV@BreakSymbolIndentRight

\FV@BreakSymbolIndentRightNChars

Additional right indentation to make room for the right break symbol.

```

2805 \newdimen\FV@BreakSymbolIndentRight
2806 \newcount\FV@BreakSymbolIndentRightNChars
2807 \define@key{FV}{breaksymbolindentright}{%
2808   \FV@BreakSymbolIndentRight=#1\relax
2809   \FV@BreakSymbolIndentRightNChars=0\relax}
2810 \define@key{FV}{breaksymbolindentrightnchars}{\FV@BreakSymbolIndentRightNChars=#1\relax}
2811 \g@addto@macro\FV@BreakLinesIndentationHook{%
2812   \ifnum\FV@BreakSymbolIndentRightNChars>0
2813     \FV@SetToWidthNChars{\FV@BreakSymbolIndentRight}{\FV@BreakSymbolIndentRightNChars}%
2814   \fi}
2815 \fvset{breaksymbolindentrightnchars=4}

```

We need macros that contain the logic for typesetting the break symbols. By default, the symbol macros contain everything regarding the symbol and its typesetting, while these macros contain pure logic. The symbols should be wrapped in braces so that formatting commands (for example, `\tiny`) don't escape.

\FancyVerbBreakSymbolLeftLogic

The left break symbol should only appear with continuation lines. Note that `linenumber` here refers to local line numbering for the broken line, *not* line numbering for all lines in the environment being typeset.

```

2816 \newcommand{\FancyVerbBreakSymbolLeftLogic}[1]{%
2817   \ifnum\value{linenumber}=1\relax\else{#1}\fi}

```

FancyVerbLineBreakLast

We need a counter for keeping track of the local line number for the last segment of a broken line, so that we can avoid putting a right continuation symbol there. A line that is broken will ultimately be processed twice when there is a right continuation symbol, once to determine the local line numbering, and then again for actual insertion into the document.

```

2818 \newcounter{FancyVerbLineBreakLast}
\FV@SetLineBreakLast
    Store the local line number for the last continuation line.
2819 \newcommand{\FV@SetLineBreakLast}{%
2820   \setcounter{FancyVerbLineBreakLast}{\value{linenumber}}}
\FancyVerbBreakSymbolRightLogic
    Only insert a right break symbol if not on the last continuation line.
2821 \newcommand{\FancyVerbBreakSymbolRightLogic}[1]{%
2822   \ifnum\value{linenumber}=\value{FancyVerbLineBreakLast}\relax\else{#1}\fi}
\FancyVerbBreakStart
    Macro that starts fine-tuned breaking (breakanywhere, breakbefore, breakafter)
    by examining a line token-by-token. Initially \let to \relax; later \let to
    \FV@Break as appropriate.
2823 \let\FancyVerbBreakStart\relax
\FancyVerbBreakStop
    Macro that stops the fine-tuned breaking region started by \FancyVerbBreakStart.
    Initially \let to \relax; later \let to \FV@EndBreak as appropriate.
2824 \let\FancyVerbBreakStop\relax
\FV@Break@DefaultToken
    Macro that controls default token handling between \FancyVerbBreakStart
    and \FancyVerbBreakStop. Initially \let to \FV@Break@NBToken, which does not
    insert breaks. Later \let to \FV@Break@AnyToken or \FV@Break@BeforeAfterToken
    if breakanywhere or breakbefore/breakafter are in use.
2825 \let\FV@Break@DefaultToken\FV@Break@NBToken
FV@breakanywhere
    Allow line breaking (almost) anywhere. Set \FV@Break and \FV@EndBreak to
    be used, and \let \FV@Break@DefaultToken to the appropriate macro.
2826 \newbool{FV@breakanywhere}
2827 \define@booleankey{FV}{breakanywhere}%
2828   {\booltrue{FV@breakanywhere}%
2829     \let\FancyVerbBreakStart\FV@Break
2830     \let\FancyVerbBreakStop\FV@EndBreak
2831     \let\FV@Break@DefaultToken\FV@Break@AnyToken}%
2832   {\boolfalse{FV@breakanywhere}%
2833     \let\FancyVerbBreakStart\relax
2834     \let\FancyVerbBreakStop\relax
2835     \let\FV@Break@DefaultToken\FV@Break@NBToken}
2836 \fvset{breakanywhere=false}
breakanywhereinlinestretch
\FV@breakanywhereinlinestretch
\FV@ApplyBreakAnywhereInlineStretch
    Stretch glue to insert at potential breakanywhere break locations in inline
    contexts, to give better line widths and avoid overfull \hbox.

```

`\FV@UseInlineKeyValues` invokes `\FV@ApplyBreakAnywhereInlineStretch` to redefine `\FancyVerbBreakAnywhereBreak` locally.

```

2837 \define@key{FV}{breakanywhereinlinestretch}{%
2838   \def\FV@breakanywhereinlinestretch{#1}%
2839   \ifx\FV@breakanywhereinlinestretch\FV@None
2840     \let\FV@breakanywhereinlinestretch\relax
2841   \else\ifx\FV@breakanywhereinlinestretch\@empty
2842     \let\FV@breakanywhereinlinestretch\relax
2843   \fi\fi}
2844 \fvset{breakanywhereinlinestretch=none}
2845 \def\FV@ApplyBreakAnywhereInlineStretch{%
2846   \ifx\FV@breakanywhereinlinestretch\relax
2847   \else
2848     \let\FancyVerbBreakAnywhereBreak@Orig\FancyVerbBreakAnywhereBreak
2849     \def\FancyVerbBreakAnywhereBreak{%
2850       \nobreak\hspace{0pt plus \FV@breakanywhereinlinestretch}%
2851       \FancyVerbBreakAnywhereBreak@Orig}%
2852   \fi}

```

`\FV@BreakBefore`

Allow line breaking (almost) anywhere, but only before specified characters.

```

2853 \define@key{FV}{breakbefore}{%
2854   \ifstrempy{#1}%
2855   {\let\FV@BreakBefore\@empty
2856     \let\FancyVerbBreakStart\relax
2857     \let\FancyVerbBreakStop\relax
2858     \let\FV@Break@DefaultToken\FV@Break@NBToken}%
2859   {\def\FV@BreakBefore{#1}%
2860     \let\FancyVerbBreakStart\FV@Break
2861     \let\FancyVerbBreakStop\FV@EndBreak
2862     \let\FV@Break@DefaultToken\FV@Break@BeforeAfterToken}%
2863   }
2864 \fvset{breakbefore={}}

```

`FV@breakbeforeinrun`

Determine whether breaking before specified characters is always allowed before each individual character, or is only allowed before the first in a run of identical characters.

```

2865 \newbool{FV@breakbeforeinrun}
2866 \define@booleankey{FV}{breakbeforeinrun}%
2867   {\booltrue{FV@breakbeforeinrun}}%
2868   {\boolfalse{FV@breakbeforeinrun}}%
2869 \fvset{breakbeforeinrun=false}

```

`\FV@BreakBeforePrep`

We need a way to break before characters if and only if they have been specified as breaking characters. It would be possible to do that via a nested conditional, but that would be messy. It is much simpler to create an empty macro whose name contains the character, and test for the existence of this macro. This needs to be done inside a `\begingroup... \endgroup` so that the macros do not have to be cleaned up manually. A good place to do this is in `\FV@FormattingPrep`, which is inside a group and before processing starts. The macro is added to `\FV@FormattingPrep@PreHook`, which contains `fvextra` extensions to `\FV@FormattingPrep`, after `\FV@BreakAfterPrep` is defined below.

The procedure here is a bit roundabout. We need to use `\FV@EscChars` to handle character escapes, but the character redefinitions need to be kept local, requiring that we work within a `\begingroup... \endgroup`. So we loop through the breaking tokens and assemble a macro that will itself define character macros. Only this defining macro is declared global, and it contains *expanded* characters so that there is no longer any dependence on `\FV@EscChars`.

`\FV@BreakBeforePrep@PygmentsHook` allows additional break preparation for Pygments-based packages such as `minted` and `pythontex`. When Pygments highlights code, it converts some characters into macros; they do not appear literally. As a result, for breaking to occur correctly, breaking macros need to be created for these character macros and not only for the literal characters themselves.

A pdfTeX-compatible version for working with UTF-8 is defined later, and `\FV@BreakBeforePrep` is `\let` to it under pdfTeX as necessary.

```

2870 \def\FV@BreakBeforePrep{%
2871   \ifx\FV@BreakBefore\@empty\relax
2872   \else
2873     \gdef\FV@BreakBefore@Def{%
2874       \begingroup
2875       \def\FV@BreakBefore@Process##1##2\FV@Undefined{%
2876         \expandafter\FV@BreakBefore@Process@i\expandafter{##1}%
2877         \expandafter\ifx\expandafter\relax\detokenize{##2}\relax
2878         \else
2879           \FV@BreakBefore@Process##2\FV@Undefined
2880         \fi
2881       }%
2882       \def\FV@BreakBefore@Process@i##1{%
2883         \g@addto@macro\FV@BreakBefore@Def{%
2884           \@namedef{FV@BreakBefore@Token\detokenize{##1}}{}}%
2885       }%
2886       \FV@EscChars
2887       \expandafter\FV@BreakBefore@Process\FV@BreakBefore\FV@Undefined
2888       \endgroup
2889       \FV@BreakBefore@Def
2890       \FV@BreakBeforePrep@PygmentsHook
2891     \fi
2892   }
2893 \def\FV@BreakBeforePrep@PygmentsHook{}
```

`\FV@BreakAfter`

Allow line breaking (almost) anywhere, but only after specified characters.

```

2894 \define@key{FV}{breakafter}{%
2895   \ifstrempy{#1}%
2896   {\let\FV@BreakAfter\@empty
2897     \let\FancyVerbBreakStart\relax
2898     \let\FancyVerbBreakStop\relax
2899     \let\FV@Break@DefaultToken\FV@Break@NBToken}%
2900   {\def\FV@BreakAfter{#1}%
2901     \let\FancyVerbBreakStart\FV@Break
2902     \let\FancyVerbBreakStop\FV@EndBreak
2903     \let\FV@Break@DefaultToken\FV@Break@BeforeAfterToken}%
2904   }
2905 \fvset{breakafter={}}
```

`FV@breakafterinrun`

Determine whether breaking after specified characters is always allowed after each individual character, or is only allowed after the last in a run of identical characters.

```

2906 \newbool{FV@breakafterinrun}
2907 \define@booleankey{FV}{breakafterinrun}%
2908 {\booltrue{FV@breakafterinrun}}%
2909 {\boolfalse{FV@breakafterinrun}}%
2910 \fvset{breakafterinrun=false}

```

`\FV@BreakAfterPrep`

This is the `breakafter` equivalent of `\FV@BreakBeforePrep`. It is also used within `\FV@FormattingPrep`. The order of `\FV@BreakBeforePrep` and `\FV@BreakAfterPrep` is important; `\FV@BreakAfterPrep` must always be second, because it checks for conflicts with `breakbefore`.

A pdfTeX-compatible version for working with UTF-8 is defined later, and `\FV@BreakAfterPrep` is `\let` to it under pdfTeX as necessary.

```

2911 \def\FV@BreakAfterPrep{%
2912   \ifx\FV@BreakAfter\@empty\relax
2913   \else
2914     \gdef\FV@BreakAfter@Def{%
2915       \begingroup
2916       \def\FV@BreakAfter@Process##1##2\FV@Undefined{%
2917         \expandafter\FV@BreakAfter@Process@i\expandafter{##1}%
2918         \expandafter\ifx\expandafter\relax\detokenize{##2}\relax
2919         \else
2920           \FV@BreakAfter@Process##2\FV@Undefined
2921         \fi
2922       }%
2923       \def\FV@BreakAfter@Process@i##1{%
2924         \ifcsname FV@BreakBefore@Token\detokenize{##1}\endcsname
2925         \ifbool{FV@breakbeforeinrun}%
2926           {\ifbool{FV@breakafterinrun}%
2927             {}%
2928             {\PackageError{fvextra}%
2929              {Conflicting breakbeforeinrun and breakafterinrun for "\detokenize{##1}"}%
2930              {Conflicting breakbeforeinrun and breakafterinrun for "\detokenize{##1}"}}}%
2931           {\ifbool{FV@breakafterinrun}%
2932             {\PackageError{fvextra}%
2933              {Conflicting breakbeforeinrun and breakafterinrun for "\detokenize{##1}"}%
2934              {Conflicting breakbeforeinrun and breakafterinrun for "\detokenize{##1}"}}}%
2935           {}}%
2936       \fi
2937       \g@addto@macro\FV@BreakAfter@Def{%
2938         \@namedef{FV@BreakAfter@Token\detokenize{##1}}{}}%
2939     }%
2940     \FV@EscChars
2941     \expandafter\FV@BreakAfter@Process\FV@BreakAfter\FV@Undefined
2942     \endgroup
2943     \FV@BreakAfter@Def
2944     \FV@BreakAfterPrep@PygmentsHook
2945   \fi
2946 }
2947 \def\FV@BreakAfterPrep@PygmentsHook{}

```

Now that `\FV@BreakBeforePrep` and `\FV@BreakAfterPrep` are defined, add them to `\FV@FormattingPrep@PreHook`, which is the `fvextra` extension to `\FV@FormattingPrep`. The ordering here is important, since `\FV@BreakAfterPrep` contains compatibility checks with `\FV@BreakBeforePrep`, and thus must be used after it. Also, we have to check for the pdfTeX engine with `inputenc` using UTF-8, and use the UTF macros instead when that is the case.

```

2948 \g@addto@macro\FV@FormattingPrep@PreHook{%
2949   \ifFV@pdfTeXinputenc
2950     \ifdefstring{\inputencodingname}{utf8}%
2951     {\let\FV@BreakBeforePrep\FV@BreakBeforePrep@UTF
2952      \let\FV@BreakAfterPrep\FV@BreakAfterPrep@UTF}%
2953     {}}%
2954 \fi
2955 \FV@BreakBeforePrep\FV@BreakAfterPrep}

```

`\FancyVerbBreakAnywhereSymbolPre`

The pre-break symbol for breaks introduced by `breakanywhere`. That is, the symbol before breaks that occur between characters, rather than at spaces.

```

2956 \define@key{FV}{breakanywheresymbolpre}{%
2957   \ifstrempy{#1}%
2958   {\def\FancyVerbBreakAnywhereSymbolPre{}}%
2959   {\def\FancyVerbBreakAnywhereSymbolPre{\hbox{#1}}}}
2960 \fvset{breakanywheresymbolpre={\,\footnotesize\ensuremath{\_}\rfloor}}

```

`\FancyVerbBreakAnywhereSymbolPost`

The post-break symbol for breaks introduced by `breakanywhere`.

```

2961 \define@key{FV}{breakanywheresymbolpost}{%
2962   \ifstrempy{#1}%
2963   {\def\FancyVerbBreakAnywhereSymbolPost{}}%
2964   {\def\FancyVerbBreakAnywhereSymbolPost{\hbox{#1}}}}
2965 \fvset{breakanywheresymbolpost={}}

```

`\FancyVerbBreakBeforeSymbolPre`

The pre-break symbol for breaks introduced by `breakbefore`.

```

2966 \define@key{FV}{breakbeforesymbolpre}{%
2967   \ifstrempy{#1}%
2968   {\def\FancyVerbBreakBeforeSymbolPre{}}%
2969   {\def\FancyVerbBreakBeforeSymbolPre{\hbox{#1}}}}
2970 \fvset{breakbeforesymbolpre={\,\footnotesize\ensuremath{\_}\rfloor}}

```

`\FancyVerbBreakBeforeSymbolPost`

The post-break symbol for breaks introduced by `breakbefore`.

```

2971 \define@key{FV}{breakbeforesymbolpost}{%
2972   \ifstrempy{#1}%
2973   {\def\FancyVerbBreakBeforeSymbolPost{}}%
2974   {\def\FancyVerbBreakBeforeSymbolPost{\hbox{#1}}}}
2975 \fvset{breakbeforesymbolpost={}}

```

`\FancyVerbBreakAfterSymbolPre`

The pre-break symbol for breaks introduced by `breakafter`.

```

2976 \define@key{FV}{breakaftersymbolpre}{%
2977   \ifstrempy{#1}%
2978   {\def\FancyVerbBreakAfterSymbolPre{}}%
2979   {\def\FancyVerbBreakAfterSymbolPre{\hbox{#1}}}}
2980 \fvset{breakaftersymbolpre={\,\footnotesize\ensuremath{\_}\rfloor}}

```

`\FancyVerbBreakAfterSymbolPost`

The post-break symbol for breaks introduced by `breakafter`.

```
2981 \define@key{FV}{breakaftersymbolpost}{%
2982   \ifstrempy{#1}%
2983   {\def\FancyVerbBreakAfterSymbolPost{}}%
2984   {\def\FancyVerbBreakAfterSymbolPost{\hbox{#1}}}}
2985 \fvset{breakaftersymbolpost={}}
```

`\FancyVerbBreakAnywhereBreak`

The macro governing breaking for `breakanywhere=true`.

```
2986 \newcommand{\FancyVerbBreakAnywhereBreak}{%
2987   \discretionary{\FancyVerbBreakAnywhereSymbolPre}%
2988   {\FancyVerbBreakAnywhereSymbolPost}{}}
```

`\FancyVerbBreakBeforeBreak`

The macro governing breaking for `breakbefore=true`.

```
2989 \newcommand{\FancyVerbBreakBeforeBreak}{%
2990   \discretionary{\FancyVerbBreakBeforeSymbolPre}%
2991   {\FancyVerbBreakBeforeSymbolPost}{}}
```

`\FancyVerbBreakAfterBreak`

The macro governing breaking for `breakafter=true`.

```
2992 \newcommand{\FancyVerbBreakAfterBreak}{%
2993   \discretionary{\FancyVerbBreakAfterSymbolPre}%
2994   {\FancyVerbBreakAfterSymbolPost}{}}
```

`breaknonspaceingroup`

`FV@breaknonspaceingroup`

When inserting breaks, insert breaks within groups (typically `{...}`) but depends on `commandchars` instead of skipping over them. This isn't the default because it is incompatible with many macros since it inserts breaks into all arguments. For those cases, redefining macros to use `\FancyVerbBreakStart... \FancyVerbBreakStop` to insert breaks is better.

```
2995 \newbool{FV@breaknonspaceingroup}
2996 \define@booleankey{FV}{breaknonspaceingroup}%
2997 {\booltrue{FV@breaknonspaceingroup}}%
2998 {\boolfalse{FV@breaknonspaceingroup}}
2999 \fvset{breaknonspaceingroup=false}
```

`breakpreferspaces`

`\FV@BreakHyphenation`

Adjust hyphenation settings for `breaklines`.

When `breakbefore`, `breakafter`, or `breakanywhere` are in use, `\finalhyphendemerits=0` prevents the final “word” on a line from being put into a line segment by itself after line breaking. Otherwise, \TeX tries to avoid a line break (hyphenation) within a “word” on the penultimate line segment, and may accomplish this by introducing an unnecessary line break at the space before the last “word.”

`breakpreferspaces` (`\linepenalty`) determines whether line breaks are preferentially inserted at normal spaces (`breakcollapsespaces=true`, `showspaces=false`) rather than at other locations allowed by `breakbefore`, `breakafter`, or `breakanywhere`.

```
3000 \newbool{FV@breakpreferspaces}
3001 \booltrue{FV@breakpreferspaces}
3002 \define@booleankey{FV}{breakpreferspaces}%
3003 {\booltrue{FV@breakpreferspaces}}%
```

```

3004 {\boolfalse{FV@breakpreferspaces}}
3005 \def\FV@BreakHyphenation{%
3006   \finalhyphendemerits=0\relax
3007   \ifbool{FV@breakpreferspaces}{\linepenalty=\M\relax}}
3008 \g@addto@macro\FV@FormattingPrep@PreHook{\FV@BreakHyphenation}

```

12.12.2 Line breaking implementation

Helper macros

`\FV@LineBox`

A box for saving a line of text, so that its dimensions may be determined and thus we may figure out if it needs line breaking.

```
3009 \newsavebox{\FV@LineBox}
```

`\FV@LineIndentBox`

A box for saving the indentation of code, so that its dimensions may be determined for use in auto-indentation of continuation lines.

```
3010 \newsavebox{\FV@LineIndentBox}
```

`\FV@LineIndentChars`

A macro for storing the indentation characters, if any, of a given line. For use in auto-indentation of continuation lines

```
3011 \let\FV@LineIndentChars\@empty
```

`\FV@GetLineIndent`

A macro that takes a line and determines the indentation, storing the indentation chars in `\FV@LineIndentChars`.

```

3012 \def\FV@GetLineIndent{%
3013   \@ifnextchar\FV@Sentinel
3014   {\FV@GetLineIndent@End}%
3015   {\ifx\@let@token\FV@FVSpaceToken
3016     \let\FV@Next\FV@GetLineIndent@Whitespace
3017     \else\ifx\@let@token\FV@FVTabToken
3018       \let\FV@Next\FV@GetLineIndent@Whitespace
3019       \else\ifcsname FV@PYG@Redefed\endcsname
3020         \ifx\@let@token\FV@PYG@Redefed
3021           \let\FV@Next\FV@GetLineIndent@Pygments
3022         \else
3023           \let\FV@Next\FV@GetLineIndent@End
3024         \fi
3025       \else
3026         \let\FV@Next\FV@GetLineIndent@End
3027       \fi\fi\fi
3028     \FV@Next}}
3029 \def\FV@GetLineIndent@End#1\FV@Sentinel{}
3030 \def\FV@GetLineIndent@Whitespace#1{%
3031   \expandafter\def\expandafter\FV@LineIndentChars\expandafter{\FV@LineIndentChars#1}%
3032   \FV@GetLineIndent}
3033 \def\FV@GetLineIndent@Pygments#1#2#3{%
3034   \FV@GetLineIndent#3}

```

Tab expansion

The `fancyvrb` option `obeytabs` uses a clever algorithm involving boxing and unboxing to expand tabs based on tab stops rather than a fixed number of equivalent space characters. (See the definitions of `\FV@ObeyTabs` and `\FV@TrueTab` in section 12.10.4.) Unfortunately, since this involves `\hbox`, it interferes with the line breaking algorithm, and an alternative is required.

There are probably many ways tab expansion could be performed while still allowing line breaks. The current approach has been chosen because it is relatively straightforward and yields identical results to the case without line breaks. Line breaking involves saving a line in a box, and determining whether the box is too wide. During this process, if `obeytabs=true`, `\FV@TrueTabSaveWidth`, which is inside `\FV@TrueTab`, is `\let` to a version that saves the width of every tab in a macro. When a line is broken, all tabs within it will then use a variant of `\FV@TrueTab` that sequentially retrieves the saved widths. This maintains the exact behavior of the case without line breaks.

Note that the special version of `\FV@TrueTab` is based on the `fvextra` patched version of `\FV@TrueTab`, not on the original `\FV@TrueTab` defined in `fancyvrb`.

`\FV@TrueTab@UseWidth`

Version of `\FV@TrueTab` that uses pre-computed tab widths.

```
3035 \def\FV@TrueTab@UseWidth{%
3036   \@tempdima=\csname FV@TrueTab:Width\arabic{FV@TrueTabCounter}\endcsname sp\relax
3037   \stepcounter{FV@TrueTabCounter}%
3038   \hbox to\@tempdima{\hss\FV@TabChar}}
```

Line scanning and break insertion macros

The strategy here is to scan through text token by token, inserting potential breaks at appropriate points. The final text with breaks inserted is stored in `\FV@BreakBuffer`, which is ultimately passed on to a wrapper macro like `\FancyVerbFormatText` or `\FancyVerbFormatInline`.

If user macros insert breaks via `\FancyVerbBreakStart... \FancyVerbBreakStop`, this invokes an additional scanning/insertion pass within each macro after expansion. The scanning/insertion only applies to the part of the expanded macros wrapped in `\FancyVerbBreakStart... \FancyVerbBreakStop`. At the time this occurs, during macro processing, text will already be wrapped in a wrapper macro like `\FancyVerbFormatText` or `\FancyVerbFormatInline`. That is, the built-in break insertion occurs before any typesetting, but user macro break insertion occurs during typesetting.

Token comparison is currently based on `\ifx`. This is sufficient for verbatim text but a comparison based on `\detokenize` might be better for cases when `commandchars` is in use. For example, with `commandchars` characters other than the curly braces `{}` might be the group tokens.

It would be possible to insert each token/group into the document immediately after it is scanned, instead of accumulating them in a “buffer.” But that would interfere with macros. Even in the current approach, macros that take optional arguments are problematic, since with some settings breaks will interfere with optional arguments.⁹

⁹Through a suitable definition that tracks the current state and looks for square brackets, this

The last token is tracked with `\FV@LastToken`, to allow lookbehind when breaking by groups of identical characters. `\FV@LastToken` is `\let` to `\FV@Undefined` any time the last token was something that shouldn't be compared against (for example, a non-empty group), and it is not reset whenever the last token may be ignored (for example, `{}`). When setting `\FV@LastToken`, it is vital always to use `\let\FV@LastToken=...` so that `\let\FV@LastToken==` will work (so that the equals sign = won't break things).

`FV@BreakBufferDepth`

Track buffer depth while inserting breaks. Some macros and command sequences require recursive processing. For example, groups `{...}` (with `commandchars` and `breaknonspaceingroup`), math, and nested `\FancyVerbBreakStart... \FancyVerbBreakStop`. Depth starts at zero. The current buffer at depth n is always `\FV@BreakBuffer`, with other buffers `\FV@BreakBuffer<n>` etc. named via `\csname` to allow for the integer.

```
3039 \newcounter{FV@BreakBufferDepth}
```

`\FV@BreakBuffer@Append`

Append to `\FV@BreakBuffer`.

```
3040 \def\FV@BreakBuffer@Append#1{%
```

```
3041 \expandafter\def\expandafter\FV@BreakBuffer\expandafter{\FV@BreakBuffer#1}}
```

`\FV@BreakBufferStart`

Create a new buffer, either at the beginning of scanning or during recursion. The single mandatory argument is the macro for handling tokens, which is `\let` to `\FV@Break@Token`. An intermediate `\FV@BreakBufferStart@i` is used to optimize `\ifx` comparisons for `\FV@BreakBufferStart` during scanning.

For recursion, `\FV@BreakBuffer<n>` and `\FV@Break@Token<n>` store the state (buffer and token handling macro) immediately prior to recursion with depth $<n>$.

```
3042 \def\FV@BreakBufferStart{%
```

```
3043 \FV@BreakBufferStart@i}
```

```
3044 \def\FV@BreakBufferStart@i#1{%
```

```
3045 \ifnum\value{FV@BreakBufferDepth}>0\relax
```

```
3046 \expandafter\let\csname FV@BreakBuffer\arabic{FV@BreakBufferDepth}\endcsname
```

```
3047 \FV@BreakBuffer
```

```
3048 \expandafter\let\csname FV@Break@Token\arabic{FV@BreakBufferDepth}\endcsname
```

```
3049 \FV@Break@Token
```

```
3050 \fi
```

```
3051 \def\FV@BreakBuffer{}%
```

```
3052 \let\FV@Break@Token=#1%
```

```
3053 \stepcounter{FV@BreakBufferDepth}%
```

```
3054 \let\FV@LastToken=\FV@Undefined
```

```
3055 \FV@Break@Scan}
```

`FV@UserMacroBreaks`

Whether a user macro is inserting breaks, as opposed to `fvextra`'s standard scanning routine. When breaks come from `fvextra`, `\FV@BreakBufferStop` does nothing with `\FV@BreakBuffer` at buffer depth 0, since `\FV@InsertBreaks` handles buffer insertion. When breaks come from user macros, `\FV@BreakBufferStop` needs to insert `\FV@BreakBuffer` at buffer depth 0.

```
3056 \newbool{FV@UserMacroBreaks}
```

might be circumvented. Then again, in verbatim contexts, macro use should be minimal, so the restriction to macros without optional arguments should generally not be an issue.

`\FV@BreakBufferStop`

Complete the current buffer. The single mandatory argument is a wrapper macro for `\FV@BreakBuffer`'s contents (for example, insert recursively scanned group into braces `{...}`). If the mandatory argument is empty, no wrapper is used.

For `fvextra`'s standard scanning: If this is the main buffer (depth 0), stop scanning—which ultimately allows `\FV@BreakBuffer` to be handled by `\FV@InsertBreaks`. For user macros: Insert `\FV@BreakBuffer` at buffer depth 0. Otherwise for both cases: Append the current buffer to the previous buffer, and continue scanning.

An intermediate `\FV@BreakBufferStop@i` is used to optimize `\ifx` comparisons for `\FV@BreakBufferStop` during scanning.

```
3057 \def\FV@BreakBufferStop{%
3058   \FV@BreakBufferStop@i}
3059 \def\FV@BreakBufferStop@i#1{%
3060   \addtocounter{FV@BreakBufferDepth}{-1}%
3061   \let\FV@LastToken=\FV@Undefined
3062   \ifnum\value{FV@BreakBufferDepth}<0\relax
3063     \PackageError{fvextra}%
3064     {Line break insertion error (extra \string\FancyVerbBreakStop?)}%
3065     {Line break insertion error (extra \string\FancyVerbBreakStop?)}%
3066     \def\FV@BreakBuffer{}%
3067   \fi
3068   \ifnum\value{FV@BreakBufferDepth}>0\relax
3069     \expandafter\@firstoftwo
3070   \else
3071     \expandafter\@secondoftwo
3072   \fi
3073   {\expandafter\FV@BreakBufferStop@ii\expandafter{\FV@BreakBuffer}{#1}}%
3074   {\ifbool{FV@UserMacroBreaks}%
3075     {\expandafter\let\expandafter\FV@BreakBuffer\expandafter\FV@Undefined\FV@BreakBuffer}%
3076     {}}}
3077 \def\FV@BreakBufferStop@ii#1#2{%
3078   \ifstrempy{#2}%
3079     {\FV@BreakBufferStop@iii{#1}}%
3080     {\expandafter\FV@BreakBufferStop@iii\expandafter{#2{#1}}}}
3081 \def\FV@BreakBufferStop@iii#1{%
3082   \expandafter\let\expandafter\FV@BreakBufferUpLevel
3083   \csname FV@BreakBuffer\arabic{FV@BreakBufferDepth}\endcsname
3084   \expandafter\def\expandafter\FV@BreakBuffer\expandafter{\FV@BreakBufferUpLevel#1}%
3085   \expandafter\let\expandafter\FV@Break@Token
3086   \csname FV@Break@Token\arabic{FV@BreakBufferDepth}\endcsname
3087   \FV@Break@Scan}
```

`\FV@InsertBreaks`

This inserts breaks within text (`#2`) and stores the result in `\FV@BreakBuffer`. Then it invokes a macro (`#1`) on the result. That allows `\FancyVerbFormatInline` and `\FancyVerbFormatText` to operate on the final text (with breaks) directly, rather than being given text without breaks or text wrapped with macros that will (potentially recursively) insert breaks. (Breaks inserted by user macros are not yet present, though, since they are only inserted—potentially recursively—during macro processing.)

The initial `\ifx` skips break insertion when break insertion is turned off

(`\FancyVerbBreakStart` is `\relax`).

The current definition of `\FV@Break@Token` is swapped for a UTF-8 compatible one under pdfTeX when necessary. In what follows, the default macros are defined after `\FV@Break`, since they make the algorithms simpler to understand. The more complex UTF variants are defined afterward.

```

3088 \def\FV@InsertBreaks#1#2{%
3089   \ifx\FancyVerbBreakStart\relax
3090     \expandafter\@firstoftwo
3091   \else
3092     \expandafter\@secondoftwo
3093   \fi
3094   {#1{#2}}%
3095   {\ifFV@pdfTeXinputenc
3096     \ifdefstring{\inputencodingname}{utf8}%
3097     {\ifx\FV@Break@DefaultToken\FV@Break@AnyToken
3098       \let\FV@Break@DefaultToken\FV@Break@AnyToken@UTF
3099     \else
3100       \ifx\FV@Break@DefaultToken\FV@Break@BeforeAfterToken
3101         \let\FV@Break@DefaultToken\FV@Break@BeforeAfterToken@UTF
3102       \fi
3103     \fi}%
3104   }%
3105   \fi
3106   \setcounter{FV@BreakBufferDepth}{0}%
3107   \boolfalse{FV@UserMacroBreaks}%
3108   \FancyVerbBreakStart#2\FancyVerbBreakStop
3109   \setcounter{FV@BreakBufferDepth}{0}%
3110   \booltrue{FV@UserMacroBreaks}%
3111   \expandafter\FV@InsertBreaks@i\expandafter{\FV@BreakBuffer}{#1}}
3112 \def\FV@InsertBreaks@i#1#2{%
3113   \let\FV@BreakBuffer\FV@Undefined
3114   #2{#1}}

```

`\FV@Break`

The entry macro for break insertion. Whatever is delimited (after expansion) by `\FV@Break... \FV@endBreak` will be scanned token by token/group by group, and accumulated (with any added breaks) in `\FV@BreakBuffer`. After scanning is complete, `\FV@BreakBuffer` will be inserted.

```

3115 \def\FV@Break{%
3116   \FV@BreakBufferStart{\FV@Break@DefaultToken}}

```

`\FV@endBreak`

```

3117 \def\FV@endBreak{%
3118   \FV@BreakBufferStop{}}

```

`\FV@Break@Scan`

Look ahead via `\@ifnextchar`. Don't do anything if we're at the end of the region to be scanned. Otherwise, invoke a macro to deal with what's next based on whether it is math, or a group, or something else.

This and some following macros are defined inside of groups to ensure proper catcodes.

The check against `\FV@BreakBufferStart` should typically not be necessary; it is included for completeness and to allow for future extensions and customization. `\FV@BreakBufferStart` is only inserted raw (rather than wrapped in

`\FancyVerbBreakStart`) in token processing macros, where it initiates (or restarts) scanning and is not itself scanned.

```

3119 \begingroup
3120 \catcode`\$=3
3121 \gdef\FV@Break@Scan{%
3122   \@ifnextchar\FancyVerbBreakStart%
3123   }{%
3124   {\ifx\@let@token\FancyVerbBreakStop
3125     \let\FV@Break@Next\relax
3126     \else\ifx\@let@token\FV@Break@BufferStart
3127       \let\FV@Break@Next\relax
3128       \else\ifx\@let@token\FV@Break@BufferStop
3129         \let\FV@Break@Next\relax
3130         \else\ifx\@let@token$
3131           \let\FV@Break@Next\FV@Break@Math
3132           \else\ifx\@let@token\bgroup
3133             \let\FV@Break@Next\FV@Break@Group
3134             \else
3135               \let\FV@Break@Next\FV@Break@Token
3136               \fi\fi\fi\fi
3137             \FV@Break@Next}}
3138 \endgroup

```

`\FV@Break@Math`

Grab an entire math span, and insert it into `\FV@Break@Buffer`. Due to grouping, this works even when math contains things like `\text{${x$}`. After dealing with the math span, continue scanning.

```

3139 \begingroup
3140 \catcode`\$=3%
3141 \gdef\FV@Break@Math$#1${%
3142   \FV@Break@BufferStart{\FV@Break@NBToken}#1\FV@Break@BufferStop{\FV@Break@MathTemplate}}
3143 \gdef\FV@Break@MathTemplate#1{#1$}
3144 \endgroup

```

`\FV@Break@Group`

Grab the group, and insert it into `\FV@Break@Buffer` (as a group) before continuing scanning.

```

3145 \def\FV@Break@Group#1{%
3146   \ifstrempy{#1}%
3147   {\FV@Break@Buffer@Append{}}%
3148   \FV@Break@Scan}%
3149   {\ifbool{FV@breaknonspaceingroup}%
3150     {\FV@Break@BufferStart{\FV@Break@DefaultToken}%
3151       #1\FV@Break@BufferStop{\FV@Break@GroupTemplate}}%
3152     {\FV@Break@BufferStart{\FV@Break@NBToken}%
3153       #1\FV@Break@BufferStop{\FV@Break@GroupTemplate}}}}
3154 \def\FV@Break@GroupTemplate#1{#1}

```

`\FV@Break@NBToken`

Append token to buffer while adding no breaks (NB) and reset last token.

```

3155 \def\FV@Break@NBToken#1{%
3156   \FV@Break@Buffer@Append{#1}%
3157   \let\FV@LastToken=\FV@Undefined
3158   \FV@Break@Scan}

```

`\FV@Break@AnyToken`

Deal with breaking around any token. This doesn't break macros with *mandatory* arguments, because `\FancyVerbBreakAnywhereBreak` is inserted *before* the token. Groups themselves are added without any special handling. So a macro would end up right next to its original arguments, without anything being inserted. Optional arguments will cause this approach to fail; there is currently no attempt to identify them, since that is a much harder problem.

If it is ever necessary, it would be possible to create a more sophisticated version involving catcode checks via `\ifcat`. Something like this:

```
\begingroup
\catcode`\a=11%
\catcode`\+=12%
\gdef\FV@Break...
  \ifcat\noexpand#1a%
    \FV@BreakBuffer@Append...
  \else
...
\endgroup
```

```
3159 \def\FV@Break@AnyToken#1{%
3160   \ifx\FV@FVSpaceToken#1\relax
3161     \expandafter\@firstoftwo
3162   \else
3163     \expandafter\@secondoftwo
3164   \fi
3165   {\let\FV@LastToken=#1\FV@BreakBuffer@Append{#1}\FV@Break@Scan}%
3166   {\ifx\FV@LastToken\FV@FVSpaceToken
3167     \expandafter\@firstoftwo
3168   \else
3169     \expandafter\@secondoftwo
3170   \fi
3171   {\let\FV@LastToken=#1%
3172     \FV@BreakBuffer@Append{#1}\FV@Break@Scan}%
3173   {\let\FV@LastToken=#1%
3174     \FV@BreakBuffer@Append{\FancyVerbBreakAnywhereBreak#1}\FV@Break@Scan}}}
```

`\FV@Break@BeforeAfterToken`

Deal with breaking around only specified tokens. This is a bit trickier. We only break if a macro corresponding to the token exists. We also need to check whether the specified token should be grouped, that is, whether breaks are allowed between identical characters. All of this has to be written carefully so that nothing is accidentally inserted into the stream for future scanning.

Dealing with tokens followed by empty groups (for example, `\x{}`) is particularly challenging when we want to avoid breaks between identical characters. When a token is followed by a group, we need to save the current token for later reference (`\x` in the example), then capture and save the following group, and then—only if the group was empty—see if the following token is identical to the old saved token.

The `\csname @let@token\endcsname` prevents issues if `\@let@token` is ever `\else` or `\fi`.

```
3175 \def\FV@Break@BeforeAfterToken#1{%
```

```

3176 \ifcsname FV@BreakBefore@Token\detokenize{#1}\endcsname
3177 \let\FV@Break@Next\FV@Break@BeforeTokenBreak
3178 \else
3179 \ifcsname FV@BreakAfter@Token\detokenize{#1}\endcsname
3180 \let\FV@Break@Next\FV@Break@AfterTokenBreak
3181 \else
3182 \let\FV@Break@Next\FV@Break@BeforeAfterTokenNoBreak
3183 \fi
3184 \fi
3185 \FV@Break@Next{#1}%
3186 }
3187 \def\FV@Break@BeforeAfterTokenNoBreak#1{%
3188 \FV@BreakBuffer@Append{#1}%
3189 \let\FV@LastToken=#1%
3190 \FV@Break@Scan}
3191 \def\FV@Break@BeforeTokenBreak#1{%
3192 \ifbool{FV@breakbeforeinrun}%
3193 {\ifcsname FV@BreakAfter@Token\detokenize{#1}\endcsname
3194 \ifx#1\FV@FVSpaceToken
3195 \FV@BreakBuffer@Append{\FancyVerbSpaceBreak}%
3196 \else
3197 \FV@BreakBuffer@Append{\FancyVerbBreakBeforeBreak}%
3198 \fi
3199 \let\FV@Break@Next\FV@Break@BeforeTokenBreak@AfterRescan
3200 \def\FV@RescanToken{#1}%
3201 \else
3202 \ifx#1\FV@FVSpaceToken
3203 \FV@BreakBuffer@Append{\FancyVerbSpaceBreak#1}%
3204 \else
3205 \FV@BreakBuffer@Append{\FancyVerbBreakBeforeBreak#1}%
3206 \fi
3207 \let\FV@Break@Next\FV@Break@Scan
3208 \let\FV@LastToken=#1%
3209 \fi}%
3210 {\ifx#1\FV@LastToken\relax
3211 \ifcsname FV@BreakAfter@Token\detokenize{#1}\endcsname
3212 \let\FV@Break@Next\FV@Break@BeforeTokenBreak@AfterRescan
3213 \def\FV@RescanToken{#1}%
3214 \else
3215 \FV@BreakBuffer@Append{#1}%
3216 \let\FV@Break@Next\FV@Break@Scan
3217 \let\FV@LastToken=#1%
3218 \fi
3219 \else
3220 \ifcsname FV@BreakAfter@Token\detokenize{#1}\endcsname
3221 \ifx#1\FV@FVSpaceToken
3222 \FV@BreakBuffer@Append{\FancyVerbSpaceBreak}%
3223 \else
3224 \FV@BreakBuffer@Append{\FancyVerbBreakBeforeBreak}%
3225 \fi
3226 \let\FV@Break@Next\FV@Break@BeforeTokenBreak@AfterRescan
3227 \def\FV@RescanToken{#1}%
3228 \else
3229 \ifx#1\FV@FVSpaceToken

```

```

3230         \FV@BreakBuffer@Append{\FancyVerbSpaceBreak#1}%
3231     \else
3232         \FV@BreakBuffer@Append{\FancyVerbBreakBeforeBreak#1}%
3233     \fi
3234     \let\FV@Break@Next\FV@Break@Scan
3235     \let\FV@LastToken=#1%
3236 \fi
3237 \fi}%
3238 \FV@Break@Next}
3239 \def\FV@Break@BeforeTokenBreak@AfterRescan{%
3240 \expandafter\FV@Break@AfterTokenBreak\FV@RescanToken}
3241 \def\FV@Break@AfterTokenBreak#1{%
3242 \let\FV@LastToken=#1%
3243 \@ifnextchar\FV@FVSpaceToken%
3244 {\ifx#1\FV@FVSpaceToken
3245 \expandafter\@firstoftwo
3246 \else
3247 \expandafter\@secondoftwo
3248 \fi
3249 {\FV@Break@AfterTokenBreak@i{#1}}%
3250 {\FV@BreakBuffer@Append{#1}%
3251 \FV@Break@Scan}}%
3252 {\FV@Break@AfterTokenBreak@i{#1}}}
3253 \def\FV@Break@AfterTokenBreak@i#1{%
3254 \ifbool{FV@breakafterinrun}%
3255 {\ifx#1\FV@FVSpaceToken
3256 \FV@BreakBuffer@Append{#1\FancyVerbSpaceBreak}%
3257 \else
3258 \FV@BreakBuffer@Append{#1\FancyVerbBreakAfterBreak}%
3259 \fi
3260 \let\FV@Break@Next\FV@Break@Scan}%
3261 {\ifx\@let@token#1\relax
3262 \FV@BreakBuffer@Append{#1}%
3263 \let\FV@Break@Next\FV@Break@Scan
3264 \else
3265 \expandafter\ifx\csgname @let@token\endcsgname\bgroup\relax
3266 \FV@BreakBuffer@Append{#1}%
3267 \let\FV@Break@Next\FV@Break@AfterTokenBreak@Group
3268 \else
3269 \ifx#1\FV@FVSpaceToken
3270 \FV@BreakBuffer@Append{#1\FancyVerbSpaceBreak}%
3271 \else
3272 \FV@BreakBuffer@Append{#1\FancyVerbBreakAfterBreak}%
3273 \fi
3274 \let\FV@Break@Next\FV@Break@Scan
3275 \fi
3276 \fi}%
3277 \FV@Break@Next
3278 }
3279 \def\FV@Break@AfterTokenBreak@Group#1{%
3280 \ifstrempy{#1}%
3281 {\FV@BreakBuffer@Append{}}%
3282 \@ifnextchar\FV@LastToken%
3283 {\FV@Break@Scan}%

```

```

3284     {\ifx\FV@LastToken\FV@FVSpaceToken
3285       \FV@BreakBuffer@Append{\FancyVerbSpaceBreak}%
3286     \else
3287       \FV@BreakBuffer@Append{\FancyVerbBreakAfterBreak}%
3288     \fi
3289     \FV@Break@Scan}}}%
3290 {\ifx\FV@LastToken\FV@FVSpaceToken
3291   \FV@BreakBuffer@Append{\FancyVerbSpaceBreak}%
3292   \else
3293     \FV@BreakBuffer@Append{\FancyVerbBreakAfterBreak}%
3294   \fi
3295   \FV@Break@Group{#1}}}}

```

Line scanning and break insertion macros for pdfTeX with UTF-8

The macros above work with the XeTeX and LuaTeX engines and are also fine for pdfTeX with 8-bit character encodings. Unfortunately, pdfTeX works with multi-byte UTF-8 code points at the byte level, making things significantly trickier. The code below re-implements the macros in a manner compatible with the `inputenc` package with option `utf8`. Note that there is no attempt for compatibility with `utf8x`; `utf8` has been significantly improved in recent years and should be sufficient in the vast majority of cases. And implementing variants for `utf8` was already sufficiently painful.

Create macros conditionally:

```

3296 \ifFV@pdfTeXinputenc
\FV@BreakBeforePrep@UTF
  We need UTF variants of the breakbefore and breakafter prep macros. These are only ever used with inputenc with UTF-8. There is no need for encoding checks here; checks are performed in \FV@FormattingPrep@PreHook (checks are inserted into it after the non-UTF macro definitions).
3297 \def\FV@BreakBeforePrep@UTF{%
3298   \ifx\FV@BreakBefore\@empty\relax
3299   \else
3300     \gdef\FV@BreakBefore@Def{}%
3301     \begingroup
3302     \def\FV@BreakBefore@Process##1{%
3303       \ifcsname FV@U8:\detokenize{##1}\endcsname
3304         \expandafter\let\expandafter\FV@Break@Next\csname FV@U8:\detokenize{##1}\endcsname
3305         \let\FV@UTF@octets@after\FV@BreakBefore@Process@ii
3306       \else
3307         \ifx##1\FV@Undefined
3308           \let\FV@Break@Next\@gobble
3309         \else
3310           \let\FV@Break@Next\FV@BreakBefore@Process@i
3311         \fi
3312       \fi
3313     \FV@Break@Next##1%
3314   }%
3315   \def\FV@BreakBefore@Process@i##1{%
3316     \expandafter\FV@BreakBefore@Process@ii\expandafter{##1}}%
3317   \def\FV@BreakBefore@Process@ii##1{%
3318     \g@addto@macro\FV@BreakBefore@Def{%
3319       \namedef{FV@BreakBefore@Token\detokenize{##1}}{}}}%

```

```

3320     \FV@BreakBefore@Process
3321   }%
3322   \FV@EscChars
3323   \expandafter\FV@BreakBefore@Process\FV@BreakBefore\FV@Undefined
3324   \endgroup
3325   \FV@BreakBefore@Def
3326   \FV@BreakBeforePrep@PygmentsHook
3327   \fi
3328 }

\FV@BreakAfterPrep@UTF

3329 \def\FV@BreakAfterPrep@UTF{%
3330   \ifx\FV@BreakAfter\@empty\relax
3331   \else
3332     \gdef\FV@BreakAfter@Def{%
3333     \begingroup
3334     \def\FV@BreakAfter@Process##1{%
3335       \ifcsname FV@U8:\detokenize{##1}\endcsname
3336         \expandafter\let\expandafter\FV@Break@Next\csname FV@U8:\detokenize{##1}\endcsname
3337         \let\FV@UTF@octets@after\FV@BreakAfter@Process@ii
3338       \else
3339         \ifx##1\FV@Undefined
3340           \let\FV@Break@Next\@gobble
3341         \else
3342           \let\FV@Break@Next\FV@BreakAfter@Process@i
3343         \fi
3344       \fi
3345       \FV@Break@Next##1%
3346     }%
3347     \def\FV@BreakAfter@Process@i##1{%
3348       \expandafter\FV@BreakAfter@Process@ii\expandafter{##1}}%
3349     \def\FV@BreakAfter@Process@ii##1{%
3350       \ifcsname FV@BreakBefore@Token\detokenize{##1}\endcsname
3351         \ifbool{FV@breakbeforeinrun}%
3352           {\ifbool{FV@breakafterinrun}%
3353           }%
3354           {\PackageError{fvextra}%
3355            {Conflicting breakbeforeinrun and breakafterinrun for "\detokenize{##1}"}%
3356            {Conflicting breakbeforeinrun and breakafterinrun for "\detokenize{##1}}}%
3357         {\ifbool{FV@breakafterinrun}%
3358          {\PackageError{fvextra}%
3359           {Conflicting breakbeforeinrun and breakafterinrun for "\detokenize{##1}"}%
3360           {Conflicting breakbeforeinrun and breakafterinrun for "\detokenize{##1}}}%
3361          }%
3362         \fi
3363         \g@addto@macro\FV@BreakAfter@Def{%
3364           \@namedef{FV@BreakAfter@Token\detokenize{##1}}{}}%
3365         \FV@BreakAfter@Process
3366       }%
3367     \FV@EscChars
3368     \expandafter\FV@BreakAfter@Process\FV@BreakAfter\FV@Undefined
3369     \endgroup
3370     \FV@BreakAfter@Def
3371     \FV@BreakAfterPrep@PygmentsHook

```

```

3372 \fi
3373 }

```

`\FV@Break@AnyToken@UTF`

Instead of just adding each token to `\FV@BreakBuffer` with a preceding break, also check for multi-byte code points and capture the remaining bytes when they are encountered.

```

3374 \def\FV@Break@AnyToken@UTF#1{%
3375 \ifcsname FV@U8:\detokenize{#1}\endcsname
3376 \expandafter\let\expandafter\FV@Break@Next\csname FV@U8:\detokenize{#1}\endcsname
3377 \let\FV@UTF@octets@after\FV@Break@AnyToken@UTF@i
3378 \else
3379 \let\FV@Break@Next\FV@Break@AnyToken@UTF@i
3380 \fi
3381 \FV@Break@Next{#1}%
3382 }
3383 \def\FV@Break@AnyToken@UTF@i#1{%
3384 \def\FV@CurrentToken{#1}%
3385 \ifx\FV@CurrentToken\FV@ActiveSpaceToken\relax
3386 \expandafter\@firstoftwo
3387 \else
3388 \expandafter\@secondoftwo
3389 \fi
3390 {\let\FV@LastToken\FV@CurrentToken
3391 \FV@BreakBuffer@Append{#1}\FV@Break@Scan}%
3392 {\ifx\FV@LastToken\FV@ActiveSpaceToken
3393 \expandafter\@firstoftwo
3394 \else
3395 \expandafter\@secondoftwo
3396 \fi
3397 {\let\FV@LastToken\FV@CurrentToken
3398 \FV@BreakBuffer@Append{#1}\FV@Break@Scan}%
3399 {\let\FV@LastToken\FV@CurrentToken
3400 \FV@BreakBuffer@Append{\FancyVerbBreakAnywhereBreak#1}\FV@Break@Scan}}

```

`\FV@Break@BeforeAfterToken@UTF`

Due to the way that the flow works, `#1` will sometimes be a single byte and sometimes be a multi-byte UTF-8 code point. As a result, it is vital use `\detokenize` in the UTF-8 leading byte checks; `\string` would only deal with the first byte. It is also important to keep track of the distinction between `\FV@Break@Next#1` and `\FV@Break@Next{#1}`. In some cases, a multi-byte sequence is being passed on as a single argument, so it must be enclosed in curly braces; in other cases, it is being re-inserted into the scanning stream and curly braces must be avoided lest they be interpreted as part of the original text.

```

3401 \def\FV@Break@BeforeAfterToken@UTF#1{%
3402 \ifcsname FV@U8:\detokenize{#1}\endcsname
3403 \expandafter\let\expandafter\FV@Break@Next\csname FV@U8:\detokenize{#1}\endcsname
3404 \let\FV@UTF@octets@after\FV@Break@BeforeAfterToken@UTF@i
3405 \else
3406 \let\FV@Break@Next\FV@Break@BeforeAfterToken@UTF@i
3407 \fi
3408 \FV@Break@Next{#1}%
3409 }
3410 \def\FV@Break@BeforeAfterToken@UTF@i#1{%

```

```

3411 \ifcsname FV@BreakBefore@Token\detokenize{#1}\endcsname
3412 \let\FV@Break@Next\FV@Break@BeforeTokenBreak@UTF
3413 \else
3414 \ifcsname FV@BreakAfter@Token\detokenize{#1}\endcsname
3415 \let\FV@Break@Next\FV@Break@AfterTokenBreak@UTF
3416 \else
3417 \let\FV@Break@Next\FV@Break@BeforeAfterTokenNoBreak@UTF
3418 \fi
3419 \fi
3420 \FV@Break@Next{#1}%
3421 }
3422 \def\FV@Break@BeforeAfterTokenNoBreak@UTF#1{%
3423 \FV@BreakBuffer@Append{#1}%
3424 \def\FV@LastToken{#1}%
3425 \FV@Break@Scan}
3426 \def\FV@Break@BeforeTokenBreak@UTF#1{%
3427 \def\FV@CurrentToken{#1}%
3428 \ifbool{FV@breakbeforeinrun}%
3429 {\ifcsname FV@BreakAfter@Token\detokenize{#1}\endcsname
3430 \ifx\FV@CurrentToken\FV@ActiveSpaceToken
3431 \FV@BreakBuffer@Append{\FancyVerbSpaceBreak}%
3432 \else
3433 \FV@BreakBuffer@Append{\FancyVerbBreakBeforeBreak}%
3434 \fi
3435 \let\FV@Break@Next\FV@Break@BeforeTokenBreak@AfterRescan@UTF
3436 \def\FV@RescanToken{#1}%
3437 \else
3438 \ifx\FV@CurrentToken\FV@ActiveSpaceToken
3439 \FV@BreakBuffer@Append{\FancyVerbSpaceBreak#1}%
3440 \else
3441 \FV@BreakBuffer@Append{\FancyVerbBreakBeforeBreak#1}%
3442 \fi
3443 \let\FV@Break@Next\FV@Break@Scan
3444 \def\FV@LastToken{#1}%
3445 \fi}%
3446 {\ifx\FV@CurrentToken\FV@LastToken\relax
3447 \ifcsname FV@BreakAfter@Token\detokenize{#1}\endcsname
3448 \let\FV@Break@Next\FV@Break@BeforeTokenBreak@AfterRescan@UTF
3449 \def\FV@RescanToken{#1}%
3450 \else
3451 \FV@BreakBuffer@Append{#1}%
3452 \let\FV@Break@Next\FV@Break@Scan
3453 \def\FV@LastToken{#1}%
3454 \fi
3455 \else
3456 \ifcsname FV@BreakAfter@Token\detokenize{#1}\endcsname
3457 \ifx\FV@CurrentToken\FV@ActiveSpaceToken
3458 \FV@BreakBuffer@Append{\FancyVerbSpaceBreak}%
3459 \else
3460 \FV@BreakBuffer@Append{\FancyVerbBreakBeforeBreak}%
3461 \fi
3462 \let\FV@Break@Next\FV@Break@BeforeTokenBreak@AfterRescan@UTF
3463 \def\FV@RescanToken{#1}%
3464 \else

```

```

3465     \ifx\FV@CurrentToken\FV@ActiveSpaceToken
3466     \FV@BreakBuffer@Append{\FancyVerbSpaceBreak#1}%
3467     \else
3468     \FV@BreakBuffer@Append{\FancyVerbBreakBeforeBreak#1}%
3469     \fi
3470     \let\FV@Break@Next\FV@Break@Scan
3471     \def\FV@LastToken{#1}%
3472     \fi
3473     \fi}%
3474     \FV@Break@Next}
3475 \def\FV@Break@BeforeTokenBreak@AfterRescan@UTF{%
3476 \expandafter\FV@Break@AfterTokenBreak@UTF\expandafter{\FV@RescanToken}}
3477 \def\FV@Break@AfterTokenBreak@UTF#1{%
3478 \def\FV@LastToken{#1}%
3479 \ifnextchar\FV@FVSpaceToken%
3480 {\ifx\FV@LastToken\FV@ActiveSpaceToken
3481 \expandafter\@firstoftwo
3482 \else
3483 \expandafter\@secondoftwo
3484 \fi
3485 {\FV@Break@AfterTokenBreak@UTF@i{#1}}%
3486 {\FV@BreakBuffer@Append{#1}%
3487 \FV@Break@Scan}}%
3488 {\FV@Break@AfterTokenBreak@UTF@i{#1}}}
3489 \def\FV@Break@AfterTokenBreak@UTF@i#1{%
3490 \ifbool{FV@breakafterinrun}%
3491 {\ifx\FV@LastToken\FV@ActiveSpaceToken
3492 \FV@BreakBuffer@Append{#1\FancyVerbSpaceBreak}%
3493 \else
3494 \FV@BreakBuffer@Append{#1\FancyVerbBreakAfterBreak}%
3495 \fi
3496 \let\FV@Break@Next\FV@Break@Scan}%
3497 {\FV@BreakBuffer@Append{#1}%
3498 \expandafter\ifx\cename @let@token\endcename\bgroup\relax
3499 \let\FV@Break@Next\FV@Break@AfterTokenBreak@Group@UTF
3500 \else
3501 \let\FV@Break@Next\FV@Break@AfterTokenBreak@UTF@ii
3502 \fi}%
3503 \FV@Break@Next}
3504 \def\FV@Break@AfterTokenBreak@UTF@ii#1{%
3505 \ifcename FV@U8:\detokenize{#1}\endcename
3506 \expandafter\let\expandafter\FV@Break@Next\cename FV@U8:\detokenize{#1}\endcename
3507 \let\FV@UTF@octets@after\FV@Break@AfterTokenBreak@UTF@ii
3508 \else
3509 \def\FV@NextToken{#1}%
3510 \ifx\FV@LastToken\FV@NextToken
3511 \else
3512 \ifx\FV@LastToken\FV@ActiveSpaceToken
3513 \FV@BreakBuffer@Append{\FancyVerbSpaceBreak}%
3514 \else
3515 \FV@BreakBuffer@Append{\FancyVerbBreakAfterBreak}%
3516 \fi
3517 \fi
3518 \let\FV@Break@Next\FV@Break@Scan

```

```

3519 \fi
3520 \FV@Break@Next#1}
3521 \def\FV@Break@AfterTokenBreak@Group@UTF#1{%
3522 \ifstrempy{#1}%
3523 {\FV@BreakBuffer@Append{}}%
3524 \@ifnextchar\bgroup
3525 {\ifx\FV@LastToken\FV@ActiveSpaceToken
3526 \FV@BreakBuffer@Append{\FancyVerbSpaceBreak}%
3527 \else
3528 \FV@BreakBuffer@Append{\FancyVerbBreakAfterBreak}%
3529 \fi
3530 \FV@Break@Group}%
3531 {\FV@Break@AfterTokenBreak@Group@UTF#1}}%
3532 {\ifx\FV@LastToken\FV@ActiveSpaceToken
3533 \FV@BreakBuffer@Append{\FancyVerbSpaceBreak}%
3534 \else
3535 \FV@BreakBuffer@Append{\FancyVerbBreakAfterBreak}%
3536 \fi
3537 \FV@Break@Group{#1}}}}
3538 \def\FV@Break@AfterTokenBreak@Group@UTF#i#1{%
3539 \ifcsname FV@U8:\detokenize{#1}\endcsname
3540 \expandafter\let\expandafter\FV@Break@Next\csname FV@U8:\detokenize{#1}\endcsname
3541 \let\FV@UTF@octets@after\FV@Break@AfterTokenBreak@Group@UTF#i
3542 \else
3543 \def\FV@NextToken{#1}%
3544 \ifx\FV@LastToken\FV@NextToken
3545 \else
3546 \ifx\FV@LastToken\FV@ActiveSpaceToken
3547 \FV@BreakBuffer@Append{\FancyVerbSpaceBreak}%
3548 \else
3549 \FV@BreakBuffer@Append{\FancyVerbBreakAfterBreak}%
3550 \fi
3551 \fi
3552 \let\FV@Break@Next\FV@Break@Scan
3553 \fi
3554 \FV@Break@Next#1}

```

End the conditional creation of the pdfTeX UTF macros:

```

3555 \fi

```

Line processing before scanning

`\FV@makeLineNumber`

The `lineno` package is used for formatting wrapped lines and inserting break symbols. We need a version of `lineno`'s `\makeLineNumber` that is adapted for our purposes. This is adapted directly from the example `\makeLineNumber` that is given in the `lineno` documentation under the discussion of internal line numbers. The `\FV@SetLineBreakLast` is needed to determine the internal line number of the last segment of the broken line, so that we can disable the right-hand break symbol on this segment. When a right-hand break symbol is in use, a line of code will be processed twice: once to determine the last internal line number, and once to use this information only to insert right-hand break symbols on the appropriate lines. During the second run, `\FV@SetLineBreakLast` is disabled by `\letting` it

```

to \relax.
3556 \def\FV@makeLineNumber{%
3557   \hss
3558   \FancyVerbBreakSymbolLeftLogic{\FancyVerbBreakSymbolLeft}%
3559   \hbox to \FV@BreakSymbolSepLeft{\hfill}%
3560   \rlap{\hskip\linewidth
3561     \hbox to \FV@BreakSymbolSepRight{\hfill}%
3562     \FancyVerbBreakSymbolRightLogic{\FancyVerbBreakSymbolRight}%
3563     \FV@SetLineBreakLast
3564   }%
3565 }

```

\FV@RaggedRight

We need a copy of the default `\raggedright` to ensure that everything works with classes or packages that use a special definition.

```

3566 \def\FV@RaggedRight{%
3567   \let\\@centercr
3568   \@rightskip\@flushglue\rightskip\@rightskip\leftskip\z@skip\parindent\z@}

```

\FV@LineWidth

This is the effective line width within a broken line.

```

3569 \newdimen\FV@LineWidth

```

\FV@SaveLineBox

This is the macro that does most of the work. It was inspired by Marco Daniel's code at <http://tex.stackexchange.com/a/112573/10742>.

This macro is invoked when a line is too long. We modify `\FV@LineWidth` to take into account `breakindent` and `breakautoindent`, and insert `\hboxes` to fill the empty space. We also account for `breaksymbolindentleft` and `breaksymbolindentright`, but *only* when there are actually break symbols. The code is placed in a `\parbox`. Break symbols are inserted via `lineno's internallinenumbers*`, which does internal line numbers without continuity between environments (the `linenumber` counter is automatically reset). The beginning of the line has negative `\hspace` inserted to pull it out to the correct starting position. `\struts` are used to maintain correct line heights. The `\parbox` is followed by an empty `\hbox` that takes up the space needed for a right-hand break symbol (if any). `\FV@BreakByTokenAnywhereHook` is a hook for using `breakbytokenanywhere` when working with Pygments. Since it is within `internallinenumbers*`, its effects do not escape.

```

3570 \def\FV@SaveLineBox#1{%
3571   \savebox{\FV@LineBox}{%
3572     \advance\FV@LineWidth by -\FV@BreakIndent
3573     \hbox to \FV@BreakIndent{\hfill}%
3574     \ifbool{FV@breakautoindent}%
3575       {\let\FV@LineIndentChars\@empty
3576        \FV@GetLineIndent#1\FV@Sentinel
3577        \savebox{\FV@LineIndentBox}{\FV@LineIndentChars}%
3578        \hbox to \wd\FV@LineIndentBox{\hfill}%
3579        \advance\FV@LineWidth by -\wd\FV@LineIndentBox
3580        \setcounter{FV@TrueTabCounter}{0}}%
3581     {}%
3582     \ifdefempty{\FancyVerbBreakSymbolLeft}{}%
3583     {\hbox to \FV@BreakSymbolIndentLeft{\hfill}%

```

```

3584     \advance\FV@LineWidth by -\FV@BreakSymbolIndentLeft}%
3585 \ifdefempty{\FancyVerbBreakSymbolRight}{}%
3586   {\advance\FV@LineWidth by -\FV@BreakSymbolIndentRight}%
3587 \parbox[t]{\FV@LineWidth}{%
3588   \FV@RaggedRight
3589   \leftlinenumbers*
3590   \begin{internallinenumbers*}%
3591   \let\makeLineNumber\FV@makeLineNumber
3592   \noindent\hspace*{-\FV@BreakIndent}%
3593   \ifdefempty{\FancyVerbBreakSymbolLeft}{}%
3594     \hspace*{-\FV@BreakSymbolIndentLeft}}%
3595   \ifbool{FV@breakautoindent}%
3596     {\hspace*{-\wd\FV@LineIndentBox}}%
3597     {}%
3598   \FV@BreakByTokenAnywhereHook
3599   \strut\FV@InsertBreaks{\FancyVerbFormatText}{#1}\nobreak\strut
3600   \end{internallinenumbers*}
3601 }%
3602 \ifdefempty{\FancyVerbBreakSymbolRight}{}%
3603   {\hbox to \FV@BreakSymbolIndentRight{\hfill}}%
3604 }%
3605 }
3606 \def\FV@BreakByTokenAnywhereHook{}

```

\FV@ListProcessLine@Break

This macro is based on the original `\FV@ListProcessLine` and follows it as closely as possible. `\FV@LineWidth` is reduced by `\FV@FrameSep` and `\FV@FrameRule` so that text will not overrun frames. This is done conditionally based on which frames are in use. We save the current line in a box, and only do special things if the box is too wide. For uniformity, all text is placed in a `\parbox`, even if it doesn't need to be wrapped.

If a line is too wide, then it is passed to `\FV@SaveLineBox`. If there is no right-hand break symbol, then the saved result in `\FV@LineBox` may be used immediately. If there is a right-hand break symbol, then the line must be processed a second time, so that the right-hand break symbol may be removed from the final segment of the broken line (since it does not continue). During the first use of `\FV@SaveLineBox`, the counter `FancyVerbLineBreakLast` is set to the internal line number of the last segment of the broken line. During the second use of `\FV@SaveLineBox`, we disable this (`\let\FV@SetLineBreakLast\relax`) so that the value of `FancyVerbLineBreakLast` remains fixed and thus may be used to determine when a right-hand break symbol should be inserted.

```

3607 \expandafter\let\expandafter\FV@iffp\csname fp_compare:nNnTF\endcsname
3608 \def\FV@ListProcessLine@Break#1{%
3609   \hbox to \hsize{%
3610     \kern\leftmargin
3611     \hbox to \linewidth{%
3612       \FV@LineWidth\linewidth
3613       \ifx\FV@RightListFrame\relax\else
3614         \advance\FV@LineWidth by -\FV@FrameSep
3615         \advance\FV@LineWidth by -\FV@FrameRule
3616       \fi
3617       \ifx\FV@LeftListFrame\relax\else
3618         \advance\FV@LineWidth by -\FV@FrameSep

```

```

3619     \advance\FV@LineWidth by -\FV@FrameRule
3620 \fi
3621 \ifx\FV@Tab\FV@TrueTab
3622     \let\FV@TrueTabSaveWidth\FV@TrueTabSaveWidth@Save
3623     \setcounter{FV@TrueTabCounter}{0}%
3624 \fi
3625 \sbox{\FV@LineBox}{%
3626     \let\FancyVerbBreakStart\relax
3627     \let\FancyVerbBreakStop\relax
3628     \FancyVerbFormatLine{%
3629         \%FancyVerbHighlightLine %<-- Default definition using \rlap breaks breaking
3630         {\FV@ObeyTabs{\FancyVerbFormatText{#1}}}}}%
3631 \ifx\FV@Tab\FV@TrueTab
3632     \let\FV@TrueTabSaveWidth\relax
3633 \fi
3634 \ifnum
3635     \FV@iffp{\the\wd\FV@LineBox}>{\FV@LineWidth}%
3636     {1}% width greater than line
3637     {\FV@iffp{\the\wd\FV@LineBox}<{0}{1}{0}}% width overflows
3638     >0
3639 \relax
3640     \setcounter{FancyVerbLineBreakLast}{0}%
3641     \ifx\FV@Tab\FV@TrueTab
3642         \let\FV@Tab\FV@TrueTab@UseWidth
3643         \setcounter{FV@TrueTabCounter}{0}%
3644     \fi
3645     \FV@SaveLineBox{#1}%
3646     \ifdefempty{\FancyVerbBreakSymbolRight}{}%
3647         \let\FV@SetLineBreakLast\relax
3648         \setcounter{FV@TrueTabCounter}{0}%
3649         \FV@SaveLineBox{#1}}%
3650     \FV@LeftListNumber
3651     \FV@LeftListFrame
3652     \FV@BGColor@List{%
3653         \FancyVerbFormatLine{%
3654             \FancyVerbHighlightLine{\usebox{\FV@LineBox}}}}%
3655     \FV@RightListFrame
3656     \FV@RightListNumber
3657     \ifx\FV@Tab\FV@TrueTab@UseWidth
3658         \let\FV@Tab\FV@TrueTab
3659     \fi
3660 \else
3661     \let\FancyVerbBreakStart\relax
3662     \let\FancyVerbBreakStop\relax
3663     \FV@LeftListNumber
3664     \FV@LeftListFrame
3665     \FV@BGColor@List{%
3666         \FancyVerbFormatLine{%
3667             \FancyVerbHighlightLine{%
3668                 \parbox[t]{\FV@LineWidth}{%
3669                     \noindent\strut\FV@ObeyTabs{\FancyVerbFormatText{#1}\strut}}}}%
3670     \FV@RightListFrame
3671     \FV@RightListNumber
3672 \fi}%

```

```
3673 \hss}\FV@bgcoloroverlap\baselineskip\z@\lineskip\z@}
```

12.13 Pygments compatibility

This section makes line breaking compatible with [Pygments](#), which is used by several packages including `minted` and `pythontex` for syntax highlighting. A few additional line breaking options are also defined for working with Pygments.

`\FV@BreakBeforePrep@Pygments`

Pygments converts some characters into macros to ensure that they appear literally. As a result, `breakbefore` and `breakafter` would fail for these characters. This macro checks for the existence of breaking macros for these characters, and creates breaking macros for the corresponding Pygments character macros as necessary.

The argument that the macro receives is the detokenized name of the main Pygments macro, with the trailing space that detokenization produces stripped. All macro names must end with a space, because the breaking algorithm uses detokenization on each token when checking for breaking macros, and this will produce a trailing space.

```
3674 \def\FV@BreakBeforePrep@Pygments#1{%
3675   \ifcsname FV@BreakBefore@Token\@backslashchar\endcsname
3676     \@namedef{FV@BreakBefore@Token#1Zbs }{ }%
3677   \fi
3678   \ifcsname FV@BreakBefore@Token\FV@underscorechar\endcsname
3679     \@namedef{FV@BreakBefore@Token#1Zus }{ }%
3680   \fi
3681   \ifcsname FV@BreakBefore@Token\@charlb\endcsname
3682     \@namedef{FV@BreakBefore@Token#1Zob }{ }%
3683   \fi
3684   \ifcsname FV@BreakBefore@Token\@charrb\endcsname
3685     \@namedef{FV@BreakBefore@Token#1Zcb }{ }%
3686   \fi
3687   \ifcsname FV@BreakBefore@Token\detokenize{~}\endcsname
3688     \@namedef{FV@BreakBefore@Token#1Zca }{ }%
3689   \fi
3690   \ifcsname FV@BreakBefore@Token\FV@ampchar\endcsname
3691     \@namedef{FV@BreakBefore@Token#1Zam }{ }%
3692   \fi
3693   \ifcsname FV@BreakBefore@Token\detokenize{<}\endcsname
3694     \@namedef{FV@BreakBefore@Token#1Zlt }{ }%
3695   \fi
3696   \ifcsname FV@BreakBefore@Token\detokenize{>}\endcsname
3697     \@namedef{FV@BreakBefore@Token#1Zgt }{ }%
3698   \fi
3699   \ifcsname FV@BreakBefore@Token\FV@hashchar\endcsname
3700     \@namedef{FV@BreakBefore@Token#1Zsh }{ }%
3701   \fi
3702   \ifcsname FV@BreakBefore@Token\@percentchar\endcsname
3703     \@namedef{FV@BreakBefore@Token#1Zpc }{ }%
3704   \fi
3705   \ifcsname FV@BreakBefore@Token\FV@dollarchar\endcsname
3706     \@namedef{FV@BreakBefore@Token#1Zdl }{ }%
3707   \fi
```

```

3708 \ifcsname FV@BreakBefore@Token\detokenize{-}\endcsname
3709 \namedef{FV@BreakBefore@Token#1Zhy }{ }%
3710 \fi
3711 \ifcsname FV@BreakBefore@Token\detokenize{'}\endcsname
3712 \namedef{FV@BreakBefore@Token#1Zsq }{ }%
3713 \fi
3714 \ifcsname FV@BreakBefore@Token\detokenize{"}\endcsname
3715 \namedef{FV@BreakBefore@Token#1Zdq }{ }%
3716 \fi
3717 \ifcsname FV@BreakBefore@Token\FV@tildechar\endcsname
3718 \namedef{FV@BreakBefore@Token#1Zti }{ }%
3719 \fi
3720 \ifcsname FV@BreakBefore@Token\detokenize{@}\endcsname
3721 \namedef{FV@BreakBefore@Token#1Zat }{ }%
3722 \fi
3723 \ifcsname FV@BreakBefore@Token\detokenize{[]\endcsname
3724 \namedef{FV@BreakBefore@Token#1Zlb }{ }%
3725 \fi
3726 \ifcsname FV@BreakBefore@Token\detokenize{[]}\endcsname
3727 \namedef{FV@BreakBefore@Token#1Zrb }{ }%
3728 \fi
3729 }

```

\FV@BreakAfterPrep@Pygments

```

3730 \def\FV@BreakAfterPrep@Pygments#1{%
3731 \ifcsname FV@BreakAfter@Token\@backslashchar\endcsname
3732 \namedef{FV@BreakAfter@Token#1Zbs }{ }%
3733 \fi
3734 \ifcsname FV@BreakAfter@Token\FV@underscorechar\endcsname
3735 \namedef{FV@BreakAfter@Token#1Zus }{ }%
3736 \fi
3737 \ifcsname FV@BreakAfter@Token\@charlb\endcsname
3738 \namedef{FV@BreakAfter@Token#1Zob }{ }%
3739 \fi
3740 \ifcsname FV@BreakAfter@Token\@charrb\endcsname
3741 \namedef{FV@BreakAfter@Token#1Zcb }{ }%
3742 \fi
3743 \ifcsname FV@BreakAfter@Token\detokenize{~}\endcsname
3744 \namedef{FV@BreakAfter@Token#1Zca }{ }%
3745 \fi
3746 \ifcsname FV@BreakAfter@Token\FV@ampchar\endcsname
3747 \namedef{FV@BreakAfter@Token#1Zam }{ }%
3748 \fi
3749 \ifcsname FV@BreakAfter@Token\detokenize{<}\endcsname
3750 \namedef{FV@BreakAfter@Token#1Zlt }{ }%
3751 \fi
3752 \ifcsname FV@BreakAfter@Token\detokenize{>}\endcsname
3753 \namedef{FV@BreakAfter@Token#1Zgt }{ }%
3754 \fi
3755 \ifcsname FV@BreakAfter@Token\FV@hashchar\endcsname
3756 \namedef{FV@BreakAfter@Token#1Zsh }{ }%
3757 \fi
3758 \ifcsname FV@BreakAfter@Token\@percentchar\endcsname
3759 \namedef{FV@BreakAfter@Token#1Zpc }{ }%

```

```

3760 \fi
3761 \ifcsname FV@BreakAfter@Token\FV@dollarchar\endcsname
3762 \namedef{FV@BreakAfter@Token#1Zdl }{ }%
3763 \fi
3764 \ifcsname FV@BreakAfter@Token\detokenize{-}\endcsname
3765 \namedef{FV@BreakAfter@Token#1Zhy }{ }%
3766 \fi
3767 \ifcsname FV@BreakAfter@Token\detokenize{'}\endcsname
3768 \namedef{FV@BreakAfter@Token#1Zsq }{ }%
3769 \fi
3770 \ifcsname FV@BreakAfter@Token\detokenize{"}\endcsname
3771 \namedef{FV@BreakAfter@Token#1Zdq }{ }%
3772 \fi
3773 \ifcsname FV@BreakAfter@Token\FV@tildechar\endcsname
3774 \namedef{FV@BreakAfter@Token#1Zti }{ }%
3775 \fi
3776 \ifcsname FV@BreakAfter@Token\detokenize{@}\endcsname
3777 \namedef{FV@BreakAfter@Token#1Zat }{ }%
3778 \fi
3779 \ifcsname FV@BreakAfter@Token\detokenize{[]}\endcsname
3780 \namedef{FV@BreakAfter@Token#1Zlb }{ }%
3781 \fi
3782 \ifcsname FV@BreakAfter@Token\detokenize{[]}\endcsname
3783 \namedef{FV@BreakAfter@Token#1Zrb }{ }%
3784 \fi
3785 }

```

breakbytoken

When Pygments is used, do not allow breaks within **Pygments tokens**. So, for example, breaks would not be allowed within a string, but could occur before or after it. This has no affect when Pygments is not in use, and is only intended for minted, pythontex, and similar packages.

```

3786 \newbool{FV@breakbytoken}
3787 \define@booleankey{FV}{breakbytoken}%
3788 {\booltrue{FV@breakbytoken}}%
3789 {\boolfalse{FV@breakbytoken}\boolfalse{FV@breakbytokenanywhere}}

```

breakbytokenanywhere

`breakbytoken` prevents breaks *within* tokens. Breaks outside of tokens may still occur at spaces. This option also enables breaks between immediately adjacent tokens that are not separated by spaces. Its definition is tied in with `breakbytoken` so that `breakbytoken` may be used as a check for whether either option is in use; essentially, `breakbytokenanywhere` is treated as a special case of `breakbytoken`.

```

3790 \newbool{FV@breakbytokenanywhere}
3791 \define@booleankey{FV}{breakbytokenanywhere}%
3792 {\booltrue{FV@breakbytokenanywhere}\booltrue{FV@breakbytoken}}%
3793 {\boolfalse{FV@breakbytokenanywhere}\boolfalse{FV@breakbytoken}}

```

\FancyVerbBreakByTokenAnywhereBreak

This is the break introduced when `breakbytokenanywhere=true`. Alternatives would be `\discretionary{}{}{} or \linebreak[0]`.

```

3794 \def\FancyVerbBreakByTokenAnywhereBreak{\allowbreak{}}

```

texcomments

`texcomments` retokenizes the contents of Pygments comment tokens using the catcodes in place before the verbatim context.

```
3795 \newbool{FV@texcomments}
3796 \define@booleankey{FV}{texcomments}%
3797 {\booltrue{FV@texcomments}}%
3798 {\boolfalse{FV@texcomments}}
```

`\VerbatimPygments`

This is the command that activates Pygments features. It must be invoked before `\begin{Verbatim}`, etc., but inside a `\begingroup... \endgroup` so that its effects do not escape into the rest of the document (for example, within the beginning of an environment). It takes two arguments: The Pygments macro that literally appears (`\PYG` for `minted` and `pythontex`), and the Pygments macro that should actually be used (`\PYG` for `minted`, `\PYG<style_name>` for `pythontex`). The two are distinguished because it can be convenient to highlight everything using the same literal macro name, and then `\let` it to appropriate values to change styles, rather than redoing all highlighting to change styles. It modifies `\FV@PygmentsHook`, which is at the beginning of `\FV@FormattingPrep@PreHook`, to make the actual changes at the appropriate time.

```
3799 \def\VerbatimPygments#1#2{%
3800   \FV@AddToHook{\FV@PygmentsHook}{\FV@VerbatimPygments{#1}{#2}}
```

`\FV@VerbatimPygments`

This does all the actual work. Again, `#1` is the Pygments macro that literally appears, and `#2` is the macro that is actually to be used.

The `breakbefore` and `breakafter` hooks are redefined. This requires some trickery to get the detokenized name of the main Pygments macro without the trailing space that detokenization of a macro name produces.

In the `non-breakbytoken` case, `#1` is redefined to use `#2` internally, bringing in `\FancyVerbBreakStart` and `\FancyVerbBreakStop` to allow line breaks.

In the `breakbytoken` cases, an `\hbox` is used to prevent breaks within the macro (breaks could occur at spaces even without `\FancyVerbBreakStart`). The `breakbytokenanywhere` case is similar but a little tricky. `\FV@BreakByTokenAnywhereHook`, which is inside `\FV@SaveLineBox` where line breaking occurs, is used to define `\FV@BreakByTokenAnywhereBreak` so that it will “do nothing” the first time it is used and on subsequent invocations become `\FancyVerbBreakByTokenAnywhereBreak`. Because the hook is within the `internallinenumbers*` environment, the redefinition doesn’t escape, and the default global definition of `\FV@BreakByTokenAnywhereBreak` as `\relax` is not affected. We don’t want the actual break to appear before the first Pygments macro in case it might cause a spurious break after leading whitespace. But we must have breaks *before* Pygments macros because otherwise lookahead would be necessary.

An intermediate variable `\FV@PYG` is defined to avoid problems in case `#1=#2`. There is also a check for a non-existent `#2` (`\PYG<style_name>` may not be created until a later compile in the `pythontex` case); if `#2` does not exist, fall back to `#1`. For the existence check, `\ifx... \relax` must be used instead of `\ifcsname`, because `#2` will be a macro, and will typically be created with `\csname... \endcsname` which will `\let` the macro to `\relax` if it doesn’t already exist.

`\FV@PYG@Redefed` is `\let` to the Pygments macro that appears literally (after redefinition), so that it can be detected elsewhere to allow for special processing, such as in `breakautoindent`.

Escape (esc) tokens are always retokenized. Comment (c) tokens are retokenized if the texcomments option is true. Reference for token abbreviations: <https://github.com/pygments/pygments/blob/master/pygments/token.py>.

```

3801 \def\FV@VerbatimPygments#1#2{%
3802   \ifx#2\relax
3803     \let\FV@PYG@orig=#1\relax
3804   \else
3805     \let\FV@PYG@orig=#2\relax
3806   \fi
3807   \let#1\FV@PYG
3808   \ifbool{FV@breaklines}%
3809     {\edef\FV@PYG@name{\expandafter\FV@DetokMacro@StripSpace\detokenize{#1}}%
3810     \def\FV@BreakBeforePrep@PygmentsHook{%
3811       \expandafter\FV@BreakBeforePrep@Pygments\expandafter{\FV@PYG@name}}%
3812     \def\FV@BreakAfterPrep@PygmentsHook{%
3813       \expandafter\FV@BreakAfterPrep@Pygments\expandafter{\FV@PYG@name}}%
3814     \ifbool{FV@breakbytoken}%
3815       {\ifbool{FV@breakbytokenanywhere}%
3816         {\def\FV@BreakByTokenAnywhereHook{%
3817           \def\FV@BreakByTokenAnywhereBreak{%
3818             \let\FV@BreakByTokenAnywhereBreak\FancyVerbBreakByTokenAnywhereBreak}}%
3819           \def\FV@PYG@retoked##1##2{%
3820             \FV@BreakByTokenAnywhereBreak
3821             \leavevmode\hbox{\FV@PYG@orig{##1}{##2}}}%
3822           {\def\FV@PYG@retoked##1##2{%
3823             \leavevmode\hbox{\FV@PYG@orig{##1}{##2}}}}%
3824           {\def\FV@PYG@retoked##1##2{%
3825             \ifbool{FV@PYG@doretok}%
3826               {\FV@PYG@orig{##1}{##2}}%
3827               {\FV@PYG@orig{##1}{\FancyVerbBreakStart##2\FancyVerbBreakStop}}}}}%
3828         {\let\FV@PYG@retoked\FV@PYG@orig}%
3829         \let\FV@PYG@Redefed\FV@PYG}
3830   \let\FV@BreakByTokenAnywhereBreak\relax
3831   \def\FV@DetokMacro@StripSpace#1 {#1}
3832   \newbool{FV@PYG@doretok}
3833   \begingroup
3834   \catcode`\+=12
3835   \gdef\FV@PYG@setretok#1+{%
3836     \ifx\relax#1\@empty
3837     \else
3838       \ifstrequal{#1}{c}%
3839         {\ifbool{FV@texcomments}{\booltrue{FV@PYG@doretok}}{}}%
3840         {\ifstrequal{#1}{esc}{\booltrue{FV@PYG@doretok}}{}}%
3841       \expandafter\FV@PYG@setretok
3842     \fi}
3843 \endgroup
3844 \def\FV@PYG#1#2{%
3845   \expandafter\FV@PYG@i\expandafter{\detokenize{#1}}{#2}}
3846 \def\FV@PYG@i#1#2{%
3847   \begingroup
3848   \boolfalse{FV@PYG@doretok}%
3849   \FV@PYG@setretok#1+\relax+%
3850   \ifbool{FV@PYG@doretok}%
3851     {\FVExtraDetokenizeVArg%

```

```
3852     \FVExtraRetokenizeVArg{\FV@PYG@retoked{#1}}{\FancyVerbRestoreCodes}}{#2}}%
3853     {\FV@PYG@retoked{#1}{#2}}%
3854     \endgroup}%
```